




Features

- Formerly a Riedon™ product
- Resistance range from 0.01 to 250K Ω
- Resistance tolerances as low as $\pm 0.01\%$
- Power rating: 5 to 50 watts
- Excellent pulse handling
- Low TCR: ± 20 PPM/°C standard

- Various terminal options available
- All-welded construction
- Operating temperature range: -55 °C to +275 °C
- Designed to MIL-R-39009 / MIL-R-18546 power ratings
- RoHS compliant*

UAL Series – Riedon™ Aluminum Housed Power Wirewound Resistors by Bourns

Electrical Characteristics

Bourns Model Number	MIL-R-39009 MIL-R-18546 Style	Power Rating @ 25 °C (W)			Resistance Range (Ω) ^{1 2}
		Commercial	MIL	Free Air	
UAL5	RER-60 / RE-60	7.5 ^a	5 ^a	4.5	0.01 to 22 K
UAL10	RER-65 / RE-65	10 ^a	10 ^a	7.5	0.01 to 47 K
UAL25	RER-70 / RE-70	25 ^b	20 ^b	12	0.01 to 90 K
UAL50	RER-75 / RE-75	50 ^c	30 ^c	20	0.01 to 250 K

¹ For non-inductive windings, divide maximum resistance by 2

² E-24 / E-96, [contact Bourns](#) for availability of other values

^a Heat Sink Required: 1.0 mm (0.040 in.) Alum. Plate, 832 cm² (129 in.²) or equiv.

^b Heat Sink Required: 1.0 mm (0.040 in.) Alum. Plate, 1077 cm² (167 in.²) or equiv.

^c Heat Sink Required: 1.5 mm (0.059 in.) Alum. Plate, 1877 cm² (291 in.²) or equiv.

Specifications

Specification	Value
Tolerances	$\pm 0.01\%$ to $\pm 10\%$ (1 % Standard)
Temperature Coefficient	>10 Ω : ± 20 PPM/°C 1 Ω to 10 Ω : ± 50 PPM/°C <1 Ω : Other TCR values available. Contact Bourns .
Temperature Range	-55 °C to +275 °C
Dielectric Strength	UAL5,10: 1500 VAC; UAL25: 2500 VAC; UAL50: 3500 VAC
Construction	Centerless ground ceramic core Matte tin over copper High-temperature epoxy molding compound, Flame resistant per UL 94V-0 Anodized aluminum housing All welded terminations

Environmental Performance

Specification (MIL-STD 202)	ΔR
Dielectric	$\pm 0.2\% + 0.05\ \Omega$
Load Life	$\pm 1\% + 0.05\ \Omega$
Storage	$\pm 0.2\% + 0.05\ \Omega$
Moisture Resistance	$\pm 0.2\% + 0.05\ \Omega$
Thermal Shock	$\pm 0.2\% + 0.05\ \Omega$
5X Overload (5 s)	$\pm 0.2\% + 0.05\ \Omega$
Shock	$\pm 0.1\% + 0.05\ \Omega$
Vibration	$\pm 0.1\% + 0.05\ \Omega$
Optional Lead Configuration	Wire, Flexible, Teflon, Quick Disconnect, Flying Leads, Formed

Additional Information

Click these links for more information:



How To Order

UAL 25 - 10R F 1 -

Model _____
 UAL (standard)
 UALN (non-inductive)

Power Code _____
 (See Electrical Characteristics table)

Resistance Code _____
 For values $\leq 10K\ \Omega$,
 "R" represents decimal point
 (Example: 10R = 10 Ω)
 For values $> 10K\ \Omega$,
 "K" represents decimal point
 (Example 1K5 = 1.5K Ω)

Tolerance _____
 X** = $\pm 0.01\%$ D = $\pm 0.5\%$
 W** = $\pm 0.02\%$ F = $\pm 1\%$
 V** = $\pm 0.025\%$ G = $\pm 2\%$
 U** = $\pm 0.05\%$ H = $\pm 3\%$
 B = $\pm 0.1\%$ J = $\pm 5\%$
 T = $\pm 0.2\%$ K = $\pm 10\%$
 C = $\pm 0.25\%$

Internal Use _____

Terminal _____
 (Blank) - 2 terminal solder lug
 4T = 4 terminal solder lug
 4TR = 4 terminal solder lug
 (2 terminal at right angle)
 4 = 4 terminal axial lead

(Specific TCR value available upon request.)

**[Contact Bourns](#) for tolerances $\leq \pm 0.01\%$.



WARNING
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

"Bourns" is a registered trademark of Bourns, Inc. in the United States and other countries.


In April 2023, BE Services Company, Inc., a subsidiary of Bourns, Inc., purchased certain assets of Riedon, Inc., including its logo and trademarks and the right to continue to manufacture former Riedon™ products.

"Riedon Logo" is a registered trademark of BE Services Company, Inc., in the United States.

"Riedon" is a trademark of BE Services Company, Inc.

UAL Series – Riedon™ Aluminum Housed Power Wirewound Resistors by Bourns **BOURNS®**

Product Dimensions



Bourns Model Number	A	B	C	D	E	F	G	H	J
UAL5	$\frac{11.3 \pm 0.13}{(.444 \pm .005)}$	$\frac{12.4 \pm 0.13}{(.490 \pm .005)}$	$\frac{15.2 \pm 0.8}{(.600 \pm .031)}$	$\frac{28.5 \pm 3.10}{(1.125 \pm .120)}$	$\frac{8.5 \pm 0.4}{(.334 \pm .015)}$	$\frac{16.4 \pm 0.4}{(.646 \pm .015)}$	$\frac{8.1 \pm 0.4}{(.320 \pm .015)}$	$\frac{1.7 \pm 0.25}{(.065 \pm .010)}$	$\frac{3.6 \pm 0.25}{(.140 \pm .010)}$
UAL10	$\frac{14.3 \pm 0.13}{(.562 \pm .005)}$	$\frac{15.9 \pm 0.13}{(.625 \pm .005)}$	$\frac{19.1 \pm 0.8}{(.750 \pm .031)}$	$\frac{33.5 \pm 3.10}{(1.320 \pm .120)}$	$\frac{10.9 \pm 0.4}{(.430 \pm .015)}$	$\frac{20.3 \pm 0.4}{(.800 \pm .015)}$	$\frac{10.2 \pm 0.4}{(.400 \pm .015)}$	$\frac{1.9 \pm 0.25}{(.075 \pm .010)}$	$\frac{4.8 \pm 0.25}{(.190 \pm .010)}$
UAL25	$\frac{18.3 \pm 0.13}{(.719 \pm .005)}$	$\frac{19.8 \pm 0.13}{(.781 \pm .005)}$	$\frac{27.0 \pm 0.8}{(1.062 \pm .031)}$	$\frac{47.5 \pm 3.10}{(1.870 \pm .120)}$	$\frac{13.5 \pm 0.4}{(.530 \pm .015)}$	$\frac{27.4 \pm 0.4}{(1.080 \pm .015)}$	$\frac{14.2 \pm 0.4}{(.560 \pm .015)}$	$\frac{2.2 \pm 0.25}{(.085 \pm .010)}$	$\frac{6.6 \pm 0.25}{(.260 \pm .010)}$
UAL50	$\frac{39.7 \pm 0.13}{(1.563 \pm .005)}$	$\frac{21.4 \pm 0.13}{(.844 \pm .005)}$	$\frac{50.0 \pm 0.8}{(1.968 \pm .031)}$	$\frac{70.0 \pm 3.10}{(2.720 \pm .120)}$	$\frac{15.6 \pm 0.4}{(.615 \pm .015)}$	$\frac{29.0 \pm 0.4}{(1.140 \pm .015)}$	$\frac{15.6 \pm 0.4}{(.615 \pm .015)}$	$\frac{2.2 \pm 0.25}{(.085 \pm .010)}$	$\frac{7.6 \pm 0.25}{(.300 \pm .010)}$

Bourns Model Number	K	L	M	N	O	P	Q	R
UAL5	$\frac{2.0 \pm 0.25}{(.078 \pm .010)}$	$\frac{2.4 \pm 0.13}{(.093 \pm .005)}$	$\frac{2.0 \pm 0.4}{(.078 \pm .015)}$	$\frac{1.3 \pm 0.15}{(.050 \pm .006)}$	$\frac{6.8 \pm 3.10}{(.266 \pm .120)}$	$\frac{6.2 \pm 0.8}{(.245 \pm .031)}$	$\frac{1.30 \pm 0.05}{(.051 \pm .002)}$	$\frac{2.2 \pm 0.8}{(.085 \pm .031)}$
UAL10	$\frac{2.4 \pm 0.25}{(.093 \pm .010)}$	$\frac{2.4 \pm 0.13}{(.093 \pm .005)}$	$\frac{2.6 \pm 0.4}{(.102 \pm .015)}$	$\frac{2.0 \pm 0.15}{(.080 \pm .006)}$	$\frac{7.9 \pm 3.10}{(.312 \pm .120)}$	$\frac{7.9 \pm 0.8}{(.312 \pm .031)}$	$\frac{2.49 \pm 0.05}{(.098 \pm .002)}$	$\frac{4.0 \pm 0.8}{(.160 \pm .031)}$
UAL25	$\frac{4.4 \pm 0.25}{(.172 \pm .010)}$	$\frac{3.2 \pm 0.13}{(.125 \pm .005)}$	$\frac{3.2 \pm 0.4}{(.125 \pm .015)}$	$\frac{2.0 \pm 0.15}{(.080 \pm .006)}$	$\frac{11.1 \pm 3.10}{(.438 \pm .120)}$	$\frac{9.9 \pm 0.8}{(.391 \pm .031)}$	$\frac{2.49 \pm 0.05}{(.098 \pm .002)}$	$\frac{4.7 \pm 0.8}{(.185 \pm .031)}$
UAL50	$\frac{5.0 \pm 0.25}{(.196 \pm .010)}$	$\frac{3.2 \pm 0.13}{(.125 \pm .005)}$	$\frac{3.2 \pm 0.4}{(.125 \pm .015)}$	$\frac{2.0 \pm 0.15}{(.080 \pm .006)}$	$\frac{11.1 \pm 3.10}{(.438 \pm .120)}$	$\frac{10.7 \pm 0.8}{(.422 \pm .031)}$	$\frac{2.49 \pm 0.05}{(.098 \pm .002)}$	$\frac{4.7 \pm 0.8}{(.185 \pm .031)}$

DIMENSIONS: $\frac{\text{MM}}{(\text{INCHES})}$


Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

UAL Series – Riedon™ Aluminum Housed Power Wirewound Resistors by Bourns **BOURNS®**

Power Derating Curves



Packaging Specifications¹

UAL5 / UAL10 / UAL25

Bulk 250 pcs. max.

UAL50

Bulk 100 pcs. max.

Note:

¹ All UAL models are max. 40 lbs. / shipping box

BOURNS®

Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com

Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com

Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

www.bourns.com

REV. 10/24

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>