

MAYA-W3 series

Host-based Wi-Fi™ 6/6E and Bluetooth® LE modules for the IoT



Small, low-power, secure modules for IoT applications

- Single-band, dual-band, and tri-band Wi-Fi 6/6E
- Bluetooth Dual-mode, qualified against Bluetooth Core 5.4
- Bluetooth LE Audio
- Efficient coexistence management between internal and external radios
- Variants with PCB-antenna, U.FL connector(s), and antenna pins
- Secure boot and secure OTP

10.4 x 14.3 x 1.9 mm



Product description

The MAYA-W3 series host-based modules are designed, built, and tested to meet the high reliability and quality requirements of a wide range of industrial applications, such as smart manufacturing, tracking and telematics, building automation, professional appliances, healthcare, and EV charging infrastructures.

MAYA-W3 modules provide SISO Wi-Fi 6/6E operation with 20 MHz channel width, improved network availability in dense Wi-Fi environments, and MU-MIMO. The modules can work as access point, station, in P2P connections, or combinations of these. Qualified against Bluetooth Core 5.4, MAYA-W3 supports Bluetooth LE, including the use of isochronous channels for LE Audio.

At 10.4 x 14.3 mm, MAYA-W3 are among the most compact Wi-Fi 6/6E SMD modules available in the market.

All u-blox modules undergo extensive qualification tests to ensure reliability over their life-time, and each module is fully tested before leaving the assembly line.

The MAYA-W3 series is based on the CYW5551/2/3 chips from Infineon.

Key features

- Variants with antenna pins, U.FL connectors, and embedded PCB antenna
- Wi-Fi 6/6E, tri-band, dual-band, and single-band; single stream, supporting MU-MIMO
- 20 MHz Wi-Fi channels
- Wi-Fi 802.11a/b/g/n/ac/ax/-d/e/h/i/r/w
- Bluetooth 5.4 supporting LE Audio
- Wi-Fi security: WPA3, WPA2, WAPI, AES
- High-power Bluetooth: up to +20 dBm
- Secure boot
- Industrial temperature range -40 °C to +85 °C

	MAYA-W331	MAYA-W333	MAYA-W336	MAYA-W361	MAYA-W363	MAYA-W366	MAYA-W381	MAYA-W382	MAYA-W383	MAYA-W386
Grade										
Automotive										
Professional	•		•							•
Standard										
Radio										
Chip inside	CYW55511	CYW55512	CYW55513							
Bluetooth qualification	5.4	5.4	5.4							
Bluetooth profiles	HCI	HCI	HCI							
Bluetooth Classic	•	•	•							•
Bluetooth Low Energy	•	•	•							
Bluetooth output power conducted [dBm]	up to 20	up to 20	up to 20							
Wi-Fi IEEE 802.11 stds				Wi-Fi 6 (802.11a/b/g/n/ac/ax)						
Wi-Fi freq. band [GHz]	2.4	2.4 and 5	2.4, 5, and 6							
Wi-Fi output power [dBm]	18	18	18							
Antenna type	p p a	p p a	p u p a							
Number of antennas	2 1 1	2 1 1	2 1 1	2 1 1 1						
OS support										
Android / Linux drivers	•	•	•							•
RTOS (via NXP MCU)	•	•	•							•
Interfaces										
High-speed UART (Bluetooth)	1	1	1							
PCM, I2S (Bluetooth audio)	1	1	1							
SDIO (Wi-Fi) [version]	3.0	3.0	3.0							
Features										
Micro access points [max]	16	16	16							
Wi-Fi direct	•	•	•							•
WPA3	•	•	•							•
RF calibration in OTP	•	•	•							•
Programmed MAC addr.	•	•	•							•
Secure boot	•	•	•							•

p = antenna pin(s)

a = internal PCB antenna and pin

u = U.FL antenna connector

Features

Wi-Fi standards	Wi-Fi 6/E IEEE 802.11a/b/g/n/ac/ax IEEE 802.11d/e/h/i/r/w
Wi-Fi channels	2.4 GHz: 1-14 5 GHz: 36-196 6 GHz: 1-233
Bluetooth	Bluetooth Dual-Mode (Classic and LE) including long range, power management, LE Audio
Antennas	MAYA-W331, MAYA-W361 and MAYA-W381: 2 antenna pins MAYA-W382: single U.FL connector MAYA-W333, MAYA-W363 and MAYA-W383: single antenna pin MAYA-W336, MAYA-W366 and MAYA-W386: 1 antenna via pin or embedded in PCB
Wi-Fi output Tx-power	18 dBm (Wi-Fi 6, 5 GHz, 20 MHz channel)
RX sensitivity	Wi-Fi 6 2.4 GHz: -95 dBm (indicative) Wi-Fi 6 5 GHz: -94 dBm (indicative) Bluetooth Classic: -94 dBm (indicative) Bluetooth LE: -100.5 dBm (1 Mbit/s, indicative)
Security	128-bit AES hardware encryption Secure boot

Software features

RF calibration	Available in on-board OTP memory
MAC addresses	Available in on-board OTP memory
Security	WPA2 (CCMP, AES) WPA3 WAPI
Wi-Fi operational modes	Station, access point, Wi-Fi direct, or any combination of these
Driver support	Free of charge drivers for Linux and Android
Wi-Fi/Bluetooth coexistence	Internal TDM mechanism Central hardware packet traffic arbitration for external radio WCI-2 interface for external radio coexistence

Interfaces

Wi-Fi	SDIO 3.0 (4-bit, up to 100 MHz clock)
Bluetooth	4-wire high-speed UART PCM and I2S for Bluetooth audio
Coexistence	WCI-2 (2-wire) Zigbee (3-wire) UWB (3-wire) 4-wire LTE
Other	GPIOs

Package

Dimensions	10.4 x 14.3 x 1.9 mm
Mounting	Soldering, 90 pins (LGA)

Environmental data, quality, and reliability

Operating temperature	-40 °C to +85 °C
Moisture sensitivity level	4
RoHS and REACH compliance	

Electrical data

RF power supply	3.13 – 3.46 VDC
I/O power supply	3.3 VDC or 1.8 VDC

Certifications and approvals

Type approvals	Europe (RED); US (FCC); Canada (ISED); Japan (Giteki) Other certifications to be considered upon request
Bluetooth	Qualified against Bluetooth Core 5.4 Bluetooth Dual-Mode

Support products

EVK-MAYA-W381	Evaluation kit for dual antenna MAYA-W3
EVK-MAYA-W386	Evaluation kit for single antenna MAYA-W3
M2-MAYA-W382-10C	M.2 card evaluation kit for MAYA-W3 modules

Product variants

MAYA-W331	Single-band Wi-Fi 6 and Bluetooth 5.4 module with two separate antenna pins
MAYA-W333	Single-band Wi-Fi 6 and Bluetooth 5.4 module with one antenna pin
MAYA-W336	Single-band Wi-Fi 6 and Bluetooth 5.4 module with embedded PCB antenna
MAYA-W361	Dual-band Wi-Fi 6 and Bluetooth 5.4 module with two separate antenna pins
MAYA-W363	Dual-band Wi-Fi 6 and Bluetooth 5.4 module with one antenna pin
MAYA-W366	Dual-band Wi-Fi 6 and Bluetooth 5.4 module with embedded PCB antenna
MAYA-W381	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with two separate antenna pins
MAYA-W382	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with a single U.FL antenna connector
MAYA-W383	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with one antenna pin
MAYA-W386	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with embedded PCB antenna

Further information

For contact information, see www.u-blox.com/contact-u-blox.

For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents and product statuses, please visit www.u-blox.com.

Copyright © 2025, u-blox AG

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[u-blox](#):

[MAYA-W363-00B](#) [MAYA-W366-00B](#) [MAYA-W386-00B](#) [MAYA-W383-00B](#) [MAYA-W333-00B](#) [MAYA-W336-00B](#)
[MAYA-W381-00B](#) [EVK-MAYA-W381-00C](#)