

NEO-F10N module

u-blox F10 standard precision GNSS module



L1/L5 dual-band GNSS receiver for meter-level accuracy in urban environments

- Effective multipath mitigation to boost urban accuracy
- Exceptional RF interference immunity with co-located cellular modems
- Proven excellent performance, even with small antennas
- Upgradeable firmware for future-proof designs
- Pin-compatible with previous NEO products for easy migration



12.2 × 16.0 × 2.4 mm



NEO-F10N-00B-00

NEO-F10N-00B-20

Grade	NEO-F10N-00B-00	
GNSS	NEO-F10N-00B-20	
Automotive		
Professional	•	•
Standard		
GPS / QZSS	•	•
Galileo	•	•
BeiDou	•	•
NavIC	•	•
Bands	L1/L5/E5a/B2a	L1/L5/E5a/B2a
Interfaces		
UART	1	1
Features		
Upgradeable firmware	•	•
Carrier phase output		•
Additional SAW	•	•
Additional LNA	•	•
RTC crystal	•	•
Oscillator	T	T
Time pulse output	1	1
Power supply		
2.7 V – 3.6 V	•	•

T = TCXO



Features

Receiver type	u-blox F10 engine GPS L1C/A, L5 QZSS L1C/A, L1S, L1Sb, L5 GAL E1B/C, E5a BDS B1C, B2a NavIC L5 SBAS L1C/A, BDSBAS B1C
Nav. update rate ¹	up to 10 Hz
Horizontal position accuracy ²	1.0 m CEP (with SBAS) 1.5 m CEP (without SBAS)
Acquisition	Cold start 28 s Aided start 2 s Hot start 2 s
Sensitivity	Tracking and nav. -167 dBm Reacquisition -159 dBm Cold start -148 dBm Hot start -159 dBm
Oscillator	TCXO
RTC crystal	Built-in

Tracking features

Odometer	Measures traveled distance with support for different user profiles
Protection level	Real-time position accuracy estimate with 95% confidence

Security features

Signal integrity	RF interference & jamming detection and reporting Spoofing detection and reporting
Device integrity	Secure boot of firmware downloaded from host or flash Receiver configuration lock by command
Secure interface	Signed UBX messages (HMAC-SHA256) JTAG debug interface disabled by default

Compatible u-blox location services

AssistNow	Achieves premium performance in challenging IoT environments
-----------	--------------------------------------------------------------

1 = The highest navigation rate can limit the number of supported constellations
2 = Depends on atmospheric conditions, GNSS antenna, multipath conditions, satellite visibility, and geometry

Package

24-pin LCC (Leadless Chip Carrier) 12.2 x 16.0 x 2.4 mm, 1.0 g

Environmental data, quality, and reliability

Operating temp.	-40 °C to +85 °C
Storage temp.	-40 °C to +85 °C
Environmental grade	2015/863/EU RoHS-3
EMC (electromagnetic compatibility)	2014/53/EU RED
Environmental testing	Qualified according to u-blox qualification policy, based on a subset of AEC-Q104
Quality management	Manufactured and fully tested in IATF 16949 certified production sites

Electrical data

Supply voltage	2.7 V to 3.6 V
Power consumption	63 mW (3 GNSS)
Backup supply	1.65 V to 3.6 V

Interfaces

Serial interfaces	1 UART
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Time pulse output	Configurable: 0.25 Hz to 10 MHz
Raw data output	Code phase data, carrier phase data
Supported antennas	Active and passive
Protocols	NMEA, UBX binary

Support products

u-blox support products provide reference design, and allow efficient integration and evaluation of u-blox positioning technology.
ANN-MB5 L1/L5 multi-band active GNSS antenna
EVK-F10N u-blox F10 GNSS evaluation kit for NEO-F10N
u-center 2 Highly intuitive software for GNSS performance evaluation

Product variants

NEO-F10N-00B-00	u-blox F10 GNSS LCC module, upgradeable firmware in flash memory, SAW filter, LNA
NEO-F10N-00B-20	u-blox F10 GNSS LCC module, upgradeable firmware in flash memory, SAW filter, LNA, carrier phase raw data

Further information

For contact information, see www.u-blox.com/contact-u-blox.
For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents and product statuses, please visit www.u-blox.com.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[u-blox](#):

[NEO-F10N-00B](#) [NEO-F10N-00B-20](#)