

## NEW! Turn-Tell™ Labels

- Innovative label design allows labels to rotate for visibility from any angle, and for repositioning on the wire/cable to align legends and improve aesthetics
- Labels can be easily installed on existing terminated wires and assemblies without disconnecting the wires/cables

- Available in P1 Cassettes for the LS8E or LS8EQ printers and in computer printable rolls, for use with Easy-Mark™ Labeling Software and desktop thermal transfer printers
- Temperature range: -40°F to 200°F (-40°C to 93°C)



| Part Number | Part Description                   | Width |      | Length |       | Print-On Area Height |      | Min. Cable O.D. |     | Max. Wire O.D. |      | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|------------------------------------|-------|------|--------|-------|----------------------|------|-----------------|-----|----------------|------|----------------|----------------|
|             |                                    | In.   | mm   | In.    | mm    | In.                  | mm   | In.             | mm  | In.            | mm   |                |                |
| R100X075V1T | White, 18 – 14 AWG wire/cable.     | 1.00  | 25.4 | 0.75   | 19.1  | 0.25                 | 6.4  | 0.12            | 3.1 | 0.16           | 4.1  | 2500           | 10000          |
| R100X125V1T | White, 12 – 10 AWG wire/cable.     | 1.00  | 25.4 | 1.25   | 31.8  | 0.38                 | 9.7  | 0.16            | 4.1 | 0.22           | 5.6  | 2500           | 10000          |
| R100X150V1T | White, Cat 5/5e/6 cable.           | 1.00  | 25.4 | 1.50   | 38.1  | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.11 | 2500           | 10000          |
| R100X150V2T | Blue, Cat 5/5e/6 cable.            | 1.00  | 25.4 | 1.50   | 38.1  | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.11 | 2500           | 10000          |
| R100X150V3T | Green, Cat 5/5e/6 cable.           | 1.00  | 25.4 | 1.50   | 38.1  | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.11 | 2500           | 10000          |
| R100X150V7T | Red, Cat 5/5e/6 cable.             | 1.00  | 25.4 | 1.50   | 38.1  | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.11 | 2500           | 10000          |
| R100X150V8T | Yellow, Cat 5/5e/6 cable.          | 1.00  | 25.4 | 1.50   | 38.1  | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.11 | 2500           | 10000          |
| R100X225V1T | White, 8 – 4 AWG wire/cable.       | 1.00  | 25.4 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 2500           | 10000          |
| R100X225V2T | Blue, 8 – 4 AWG wire/cable.        | 1.00  | 25.4 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 2500           | 10000          |
| R100X225V3T | Green, 8 – 4 AWG wire/cable.       | 1.00  | 25.4 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 2500           | 10000          |
| R100X225V7T | Red, 8 – 4 AWG wire/cable.         | 1.00  | 25.4 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 2500           | 10000          |
| R100X225V8T | Yellow, 8 – 4 AWG wire/cable.      | 1.00  | 25.4 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 2500           | 10000          |
| R100X400V1T | White, 2 AWG – 250 MCM wire/cable. | 1.00  | 25.4 | 4.00   | 101.6 | 1.00                 | 25.4 | 0.39            | 9.9 | 0.95           | 24.1 | 1000           | 4000           |
| R200X225V1T | White, 8 – 4 AWG wire/cable.       | 2.00  | 50.8 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 1000           | 4000           |
| R200X400V1T | White, 2 AWG – 250 MCM wire/cable. | 2.00  | 50.8 | 4.00   | 101.6 | 1.00                 | 25.4 | 0.39            | 9.9 | 0.95           | 24.1 | 1000           | 4000           |

Order number of labels required in multiples of Std. Pkg. Qty.

## Thermal Transfer Marker Plates



- Non-adhesive marker plates offer crisp, clear legends with superior legibility
- Attachable in a horizontal or vertical orientation
- Available in a variety of colors and sizes
- Use with Panduit RMR4BL resin thermal transfer ribbon
- Temperature range: -58°F to 221°F (-50°C to 105°C)

| Part Number  | Part Description                       | Width |      | Height |      | Print-On Area Width |      | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--------------|----------------------------------------|-------|------|--------|------|---------------------|------|----------------|----------------|
|              |                                        | In.   | mm   | In.    | mm   | In.                 | mm   |                |                |
| M300X100Y6T* | Yellow, thermal transfer marker plate. | 3.00  | 76.2 | 1.00   | 25.4 | 1.80                | 45.7 | 1              | 4              |
| M300X100Y7T  | White, thermal transfer marker plate.  | 3.00  | 76.2 | 1.00   | 25.4 | 1.80                | 45.7 | 1              | 4              |
| M300X050Y6T* | Yellow, thermal transfer marker plate. | 3.00  | 76.2 | 0.50   | 12.7 | 1.80                | 45.7 | 1              | 4              |
| M300X050Y7T  | White, thermal transfer marker plate.  | 3.00  | 76.2 | 0.50   | 12.7 | 1.80                | 45.7 | 1              | 4              |
| M200X100Y6T* | Yellow, thermal transfer marker plate. | 2.00  | 50.8 | 1.00   | 25.4 | 0.80                | 20.3 | 1              | 4              |
| M200X100Y7T  | White, thermal transfer marker plate.  | 2.00  | 50.8 | 1.00   | 25.4 | 0.80                | 20.3 | 1              | 4              |
| M200X050Y6T* | Yellow, thermal transfer marker plate. | 2.00  | 50.8 | 0.50   | 12.7 | 1.07                | 27.3 | 1              | 4              |
| M200X050Y7T  | White, thermal transfer marker plate.  | 2.00  | 50.8 | 0.50   | 12.7 | 1.07                | 27.3 | 1              | 4              |

\*Other colors available, replace Y6 with AC (Blue), AE (Green), AF (Gray), AG (Orange), and AI (Red).  
Order number of marker plates required in multiples of Std. Pkg. Qty.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Panduit:

[R100X075V1T](#) [R100X125V1T](#) [R100X150V1T](#) [R100X225V1T](#) [R100X400V1T](#) [R200X225V1T](#) [R200X400V1T](#)  
[M200X050Y6T](#) [M200X050Y7T](#) [M200X100Y6T](#) [M200X100Y7T](#) [M300X050Y6T](#) [M300X050Y7T](#) [M300X100Y6T](#)  
[M300X100Y7T](#)