Micropower Dual CMOS Voltage Comparator

NCV2393, TS393

The NCV2393 and TS393 are micropower CMOS dual voltage comparators. They feature extremely low consumption of 6 μA typical per comparator and operate over a wide temperature range of T_A = −40 to 125°C. The NCV2393 and TS393 are available in an SOIC−8 package.


Features

- Extremely Low Supply Current: 6 μA Typical Per Channel
- Wide Supply Range: 2.7 to 16 V
- Extremely Low Input Bias Current: 1 pA Typical
- Extremely Low Input Offset Current: 1 pA Typical
- Input Common Mode Range Includes V_{SS}
- High Input Impedance: 10^{12} Ω
- Pin−to−Pin Compatibility with Dual Bipolar LM393
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q100 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant




SOIC-8
CASE 751

PIN CONNECTIONS



MARKING DIAGRAM



A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping†
NCV2393DR2G	SOIC−8 (Pb−Free)	2,500 / Tape & Reel
TS393DR2G	SOIC−8 (Pb−Free)	2,500 / Tape & Reel

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2014

PIN DESCRIPTION

Pin	Name	Type	Description
1	OUT 1	Output	Output of comparator 1. The open−drain output requires an external pull−up resistor.
2	IN− 1	Input	Inverting input of comparator 1
3	IN+ 1	Input	Non−inverting input of comparator 1
4	VSS	Power	Negative supply
5	IN+ 2	Input	Non−inverting input of comparator 2
6	IN− 2	Input	Inverting input of comparator 2
7	OUT 2	Output	Output of comparator 2. The open−drain output requires an external pull−up resistor.
8	VDD	Power	Positive supply

ABSOLUTE MAXIMUM RATINGS (Note 1)

Over operating free−air temperature, unless otherwise stated

Parameter	Limit	Unit
Supply Voltage, V_S (V_{DD}−V_{SS})	18	V
INPUT AND OUTPUT PINS		
Input Voltage (Note 2)	18	V
Input Differential Voltage, V_{ID} (Note 3)	±18	V
Input Current (through ESD protection diodes)	50	mA
Output Voltage	18	V
Output Current	20	mA
TEMPERATURE		
Storage Temperature	−65 to +150	°C
Junction Temperature	150	°C
ESD RATINGS		
Human Body Model	1500	V
Machine Model	50	V
LATCH−UP RATINGS		
Latch−up Current	100	mA

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Stresses beyond the absolute maximum ratings can lead to reduced reliability and damage.
2. Excursions of input voltages may exceed the power supply level. As long as the common mode voltage [V_{CM} = (V_{IN}+ + V_{IN}−)/2] remains within the specified range, the comparator will provide a stable output state. However, the maximum current through the ESD diodes of the input stage must strictly be observed.
3. Input differential voltage is the non−inverting input terminal with respect to the inverting input terminal. To prevent damage to the gates, each comparator includes back−to−back zener didoes between input terminals. When differential voltage exceeds 6.2 V, the diodes turn on. Input resistors of 1 kΩ have been integrated to limit the current in this event.
4. This device series incorporates ESD protection and is tested by the following methods:
   ESD Human Body Model tested per AEC−Q100−002 (JEDEC standard: JESD22−A114)
   ESD Machine Model tested per AEC−Q100−003 (JEDEC standard: JESD22−A115)
   Latch−up Current tested per JEDEC standard: JESD78.

THERMAL INFORMATION (Note 5)

Symbol	Thermal Metric	Value	Unit
θ_{JA}	Junction−to−Ambient (Note 6)	190	°C/W
Ψ_{JT}	Junction−to−Case Top	107	°C/W

5. Short−circuits can cause excessive heating and destructive dissipation. Values are typical.
6. Multilayer board, 1 oz. copper, 400 mm^2 copper area, both junctions heated equally

Share Feedback
Your Opinion Matters

OPERATING CONDITIONS

Symbol	Parameter	Limit	Unit
V_S	Supply Voltage (V_{DD} – V_{SS})	+2.7 to +16	V
T_A	Operating Free Air Temperature Range	–40 to +125	°C

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

ELECTRICAL CHARACTERISTICS: V_S = +3 V

(**Boldface** limits apply over the specified temperature range, T_A = –40°C to +125°C, guaranteed by characterization and/or design.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
V_{OS}	Offset Voltage	V_{CM} = mid–supply		1.4	13	mV
					14	mV
I_{IB}	Input Bias Current (Note 7)	V_{CM} = mid–supply		1		pA
					600	**pA**
I_{OS}	Input Offset Current (Note 7)	V_{CM} = mid–supply		1		pA
					300	**pA**
V_{CM}	Input Common Mode Range		V_{SS}		V_{DD} – 1.5	V
			V_{SS}		**V_{DD} – 2**	**V**
CMRR	Common Mode Rejection Ratio	V_{CM} = V_{SS} to V_{CM} = V_{DD} – 1.5 V		70		dB
OUTPUT CHARACTERISTICS						
V_{OL}	Output Voltage Low	V_{ID} = –1 V, I_{OL} = +6 mA		V_{SS} + 300	V_{SS} + 450	mV
					V_{SS} + 700	**mV**
I_{OH}	Output Current High	V_{ID} = +1 V, V_{OH} = +3 V		2	40	nA
					1000	**nA**
DYNAMIC PERFORMANCE						
t_{PLH}	Propagation Delay Low to High	V_{CM} = mid–supply, f = 10 kHz, R_{PU} = 5.1 kΩ, C_L = 50 pF; 5 mV overdrive		2.1		μs
		TTL input		0.6		μs
t_{PHL}	Propagation Delay High to Low	V_{CM} = mid–supply, f = 10 kHz, R_{PU} = 5.1 kΩ, C_L = 50 pF; 5 mV overdrive		3.9		μs
		TTL input		0.2		μs
POWER SUPPLY						
PSRR	Power Supply Rejection Ratio	V_S = +3 V to +5 V		70		dB
I_{DD}	Quiescent Current	Per channel, no load, output = LOW		6	15	μA
					20	**μA**

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

7. Guaranteed by characterization and/or design.

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS: V_S = **+5 V**, unless otherwise noted
(**Boldface** limits apply over the specified temperature range, T_A = −40°C to +125°C, guaranteed by characterization and/or design.)

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
INPUT CHARACTERISTICS							
V_{OS}	Offset Voltage	V_{CM} = mid−supply V, V_S = 5 V to 10 V			1.4	13	mV
						14	mV
I_{IB}	Input Bias Current (Note 8)	V_{CM} = mid−supply			1		pA
						600	**pA**
I_{OS}	Input Offset Current (Note 8)	V_{CM} = mid−supply			1		pA
						300	**pA**
V_{CM}	Input Common Mode Range			V_{SS}		V_{DD} − 1.5	V
				V_{SS}		**V_{DD} − 2**	**V**
CMRR	Common Mode Rejection Ratio	V_{CM} = V_{SS} to V_{CM} = V_{DD} − 1.5 V			71		dB
OUTPUT CHARACTERISTICS							
V_{OL}	Output Voltage Low	V_{ID} = −1 V, I_{OL} = +6 mA			V_{SS} + 260	V_{SS} + 350	mV
						V_{SS} + 550	**mV**
I_{OH}	Output Current High	V_{ID} = +1 V, V_{OH} = +5 V			2	40	nA
						1000	**nA**
DYNAMIC PERFORMANCE							
t_{FALL}	Fall Time	50 mV overdrive, f = 10 kHz, R_{PU} = 5.1 kΩ, C_L = 50 pF			25		ns
t_{PLH}	Propagation Delay Low to High	V_{CM} = mid−supply, f = 10 kHz, R_{PU} = 5.1 kΩ, C_L = 50 pF	5 mV overdrive		2.1		μs
			10 mV overdrive		1.2		μs
			20 mV overdrive		0.8		μs
			40 mV overdrive		0.5		μs
			TTL input		0.6		μs
t_{PHL}	Propagation Delay High to Low	V_{CM} = mid−supply, f = 10 kHz, R_{PU} = 5.1 kΩ, C_L = 50 pF	5 mV overdrive		5.8		μs
			10 mV overdrive		3.2		μs
			20 mV overdrive		1.7		μs
			40 mV overdrive		1.0		μs
			TTL input		0.3		μs
POWER SUPPLY							
PSRR	Power Supply Rejection Ratio	VS = +5 V to = +10 V			80		dB
I_{DD}	Quiescent Current	Per channel, no load, output = LOW			6	15	μA
						20	**μA**

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

8. Guaranteed by characterization and/or design

Share Feedback
Your Opinion Matters

TYPICAL OPERATING CHARACTERISTICS




Figure 1. I_{IB} and I_{OS} vs. Temperature




Figure 2. V_{OL} vs. I_{OL}




Figure 3. V_{OL} vs. Temperature




Figure 4. I_{DD} vs. V_S




Figure 5. I_{DD} vs. Temperature




Figure 6. Propagation Delay vs. V_S

Share Feedback
Your Opinion Matters

TYPICAL OPERATING CHARACTERISTICS (continued)




Figure 7. t_{PLH} vs. Overdrive




Figure 8. t_{PHL} vs. Overdrive




Figure 9. Fall Time vs. V_S




Figure 10. V_{OS} vs. V_{CM} (V_S = 3 V)




Figure 11. V_{OS} vs. V_{CM} (V_S = 5 V)

Share Feedback
Your Opinion Matters

TYPICAL OPERATING CHARACTERISTICS (continued)




Figure 12. V_{OS} vs. V_{CM} (V_S = 10 V)




Figure 13. Offset Voltage Distribution

Share Feedback
Your Opinion Matters

REVISION HISTORY

Revision	Description of Changes	Date
6	Rebranded the Data Sheet to **onsemi** format.	5/20/2025


Share Feedback
Your Opinion Matters



SCALE 1:1

SOIC−8 NB
CASE 751−07
ISSUE AK


DATE 16 FEB 2011



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751−01 THRU 751−06 ARE OBSOLETE. NEW STANDARD IS 751−07.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	4.80	5.00	0.189	0.197
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.053	0.069
D	0.33	0.51	0.013	0.020
G	1.27 BSC		0.050 BSC	
H	0.10	0.25	0.004	0.010
J	0.19	0.25	0.007	0.010
K	0.40	1.27	0.016	0.050
M	0°	8°	0°	8°
N	0.25	0.50	0.010	0.020
S	5.80	6.20	0.228	0.244


SOLDERING FOOTPRINT*



SCALE 6:1 (mm / inches)

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

XXXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 1 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

SOIC−8 NB
CASE 751−07
ISSUE AK

DATE 16 FEB 2011

STYLE 1:
PIN 1. EMITTER
2. COLLECTOR
3. COLLECTOR
4. EMITTER
5. EMITTER
6. BASE
7. BASE
8. EMITTER

STYLE 2:
PIN 1. COLLECTOR, DIE, #1
2. COLLECTOR, #1
3. COLLECTOR, #2
4. COLLECTOR, #2
5. BASE, #2
6. EMITTER, #2
7. BASE, #1
8. EMITTER, #1

STYLE 3:
PIN 1. DRAIN, DIE #1
2. DRAIN, #1
3. DRAIN, #2
4. DRAIN, #2
5. GATE, #2
6. SOURCE, #2
7. GATE, #1
8. SOURCE, #1

STYLE 4:
PIN 1. ANODE
2. ANODE
3. ANODE
4. ANODE
5. ANODE
6. ANODE
7. ANODE
8. COMMON CATHODE

STYLE 5:
PIN 1. DRAIN
2. DRAIN
3. DRAIN
4. DRAIN
5. GATE
6. GATE
7. SOURCE
8. SOURCE

STYLE 6:
PIN 1. SOURCE
2. DRAIN
3. DRAIN
4. SOURCE
5. SOURCE
6. GATE
7. GATE
8. SOURCE

STYLE 7:
PIN 1. INPUT
2. EXTERNAL BYPASS
3. THIRD STAGE SOURCE
4. GROUND
5. DRAIN
6. GATE 3
7. SECOND STAGE Vd
8. FIRST STAGE Vd

STYLE 8:
PIN 1. COLLECTOR, DIE #1
2. BASE, #1
3. BASE, #2
4. COLLECTOR, #2
5. COLLECTOR, #2
6. EMITTER, #2
7. EMITTER, #1
8. COLLECTOR, #1

STYLE 9:
PIN 1. EMITTER, COMMON
2. COLLECTOR, DIE #1
3. COLLECTOR, DIE #2
4. EMITTER, COMMON
5. EMITTER, COMMON
6. BASE, DIE #2
7. BASE, DIE #1
8. EMITTER, COMMON

STYLE 10:
PIN 1. GROUND
2. BIAS 1
3. OUTPUT
4. GROUND
5. GROUND
6. BIAS 2
7. INPUT
8. GROUND

STYLE 11:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 12:
PIN 1. SOURCE
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 13:
PIN 1. N.C.
2. SOURCE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 14:
PIN 1. N−SOURCE
2. N−GATE
3. P−SOURCE
4. P−GATE
5. P−DRAIN
6. P−DRAIN
7. N−DRAIN
8. N−DRAIN

STYLE 15:
PIN 1. ANODE 1
2. ANODE 1
3. ANODE 1
4. ANODE 1
5. CATHODE, COMMON
6. CATHODE, COMMON
7. CATHODE, COMMON
8. CATHODE, COMMON

STYLE 16:
PIN 1. EMITTER, DIE #1
2. BASE, DIE #1
3. EMITTER, DIE #2
4. BASE, DIE #2
5. COLLECTOR, DIE #2
6. COLLECTOR, DIE #2
7. COLLECTOR, DIE #1
8. COLLECTOR, DIE #1

STYLE 17:
PIN 1. VCC
2. V2OUT
3. V1OUT
4. TXE
5. RXE
6. VEE
7. GND
8. ACC

STYLE 18:
PIN 1. ANODE
2. ANODE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. CATHODE
8. CATHODE

STYLE 19:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. MIRROR 2
7. DRAIN 1
8. MIRROR 1

STYLE 20:
PIN 1. SOURCE (N)
2. GATE (N)
3. SOURCE (P)
4. GATE (P)
5. DRAIN
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 21:
PIN 1. CATHODE 1
2. CATHODE 2
3. CATHODE 3
4. CATHODE 4
5. CATHODE 5
6. COMMON ANODE
7. COMMON ANODE
8. CATHODE 6

STYLE 22:
PIN 1. I/O LINE 1
2. COMMON CATHODE/VCC
3. COMMON CATHODE/VCC
4. I/O LINE 3
5. COMMON ANODE/GND
6. I/O LINE 4
7. I/O LINE 5
8. COMMON ANODE/GND

STYLE 23:
PIN 1. LINE 1 IN
2. COMMON ANODE/GND
3. COMMON ANODE/GND
4. LINE 2 IN
5. LINE 2 OUT
6. COMMON ANODE/GND
7. COMMON ANODE/GND
8. LINE 1 OUT

STYLE 24:
PIN 1. BASE
2. EMITTER
3. COLLECTOR/ANODE
4. COLLECTOR/ANODE
5. CATHODE
6. CATHODE
7. COLLECTOR/ANODE
8. COLLECTOR/ANODE

STYLE 25:
PIN 1. VIN
2. N/C
3. REXT
4. GND
5. IOUT
6. IOUT
7. IOUT
8. IOUT

STYLE 26:
PIN 1. GND
2. dv/dt
3. ENABLE
4. ILIMIT
5. SOURCE
6. SOURCE
7. SOURCE
8. VCC

STYLE 27:
PIN 1. ILIMIT
2. OVLO
3. UVLO
4. INPUT+
5. SOURCE
6. SOURCE
7. SOURCE
8. DRAIN

STYLE 28:
PIN 1. SW_TO_GND
2. DASIC_OFF
3. DASIC_SW_DET
4. GND
5. V_MON
6. VBULK
7. VBULK
8. VIN

STYLE 29:
PIN 1. BASE, DIE #1
2. EMITTER, #1
3. BASE, #2
4. EMITTER, #2
5. COLLECTOR, #2
6. COLLECTOR, #2
7. COLLECTOR, #1
8. COLLECTOR, #1

STYLE 30:
PIN 1. DRAIN 1
2. DRAIN 1
3. GATE 2
4. SOURCE 2
5. SOURCE 1/DRAIN 2
6. SOURCE 1/DRAIN 2
7. SOURCE 1/DRAIN 2
8. GATE 1

DOCUMENT NUMBER:	**98ASB42564B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOIC−8 NB**		**PAGE 2 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales