

QS Family

QFN Style Solder-Down Computer-on-Modules

- Solder-down version
- 27mm square
- 2.3mm total height
- QFN type lead style
 - 1mm pitch
 - 100 pads
 - Thermal pad
- Visual solder joint inspection possible after soldering
- Single-sided assembly, high speed design compliant
- 3.3V power supply



Key Features

- Processor STM32MP157
Dual Arm® Cortex®-A7 650MHz
Arm® Cortex®-M4 209MHz
- RAM 256MB or 512MB DDR3L
- ROM 4GB eMMC
- Wi-Fi® (option) 802.11a/b/g/n/ac
Dual band 2.4 GHz and 5 GHz
- Bluetooth® (option) 5.2 BR/EDR/LE
- Grade Industrial
- Temperature -25°C to 85°C ^{/E85}
-40°C to 85°C ^{/I}
- Display support
Display Interface 24-bit RGB
MIPI® DSI (2-lanes)
- GPU*) 3D GPU: Vivante®
OpenGL® ES 2.0
- Connectivity
 - Gb Ethernet, USB2.0, eMMC/SD
 - UART, I²C, SPI, PWM, SAI, CAN


OS Support

- Linux

**Dual
Cortex®-A7**



STM32MP1 Block Diagram



	QSMP-1530C	QSMP-1570	QSMP-1570W
Processor	2x Cortex®-A7 up to 650 MHz 1x Cortex®-M4 up to 200 MHz		
RAM	256 MB	512 MB	
ROM	4GB eMMC		
Wi-Fi®	-	-	yes
Bluetooth®	-	-	yes
Display Interface	24-bit RGB + 2-lane MIPI-DSI		
3D GPU	yes		
CAN	2x FD-CAN		
Security	Secure Boot, Cryptography		
Temperature	-25°C to 85°C	-25°C to 85°C	-40°C to 85°C
Order Code	QSMP/157C/256S/4GF/E85	QSMP/157C/512S/4GF/E85	QSMP/157C/512S/4GF/WLAN/I


QFN Style Computer On Module Advantages

Defined Return Path

The reason PCB layout becomes more and more important is because of the trend to faster, higher integrated, smaller formfactors, and lower power electronic circuits. The higher the switching frequencies are, the more radiation may occur on a PCB. With good layout, many EMI problems can be minimized to meet the required specifications.

When a module or component is used in a design, the supplier specifies the basis for such a layout. It's not only the pinout which should lead to an easy wiring without the need for crossings. He has also provide a proper solution for the signal path back to the module. If this return path, mostly the ground plane, cannot be connected near the signal pin, the return current has to take another way and this may result in a loop area. The larger the area, the more radiation and EMI problems may occur.

Ka-Ro QSCOM modules uses a large ground pad on the bottom side. With this a defined ground plane connection is available for all signals. In addition to have a good return path for all signals this large ground pad can be used for cooling.





Easy Wiring - Even 2-layer printed circuit boards can be used.

With a solid ground plane on the bottom layer, high speed signals can be routed on the top layer at a defined impedance. However, this is only possible if a peripheral or plug can be connected directly without crossing the routing.

Advanced Soldering

Using a large solder pad underneath the component has not only electrical and thermal advantages. This is also used to hold the component at a defined height during soldering, without the solder being compressed by the weight, which could result in short circuits.

Standard Contact Assignments




Soldering Recommendations

Ka-Ro QSCOM modules are compatible with industrial standard reflow profile for Pb-free solders. Ka-Ro will give following recommendations for soldering the module to ensure reliable solder joint and operation of the module after soldering. Since the profile used is process and layout dependent, the optimum profile should be studied case by case. Thus following recommendations should be taken as a starting point guide.

- Refer to technical documentations of particular solder paste for reflow profile configurations
- Avoid using more than one flow.
- A 150 μ m stencil thickness is recommended.
- Aperture size of the stencil should be 1:1 with the pad size.
- A low residue, “no clean” solder paste should be used due to low mounted height of the component.

Recommended stencil design




Aperture size of the stencil is 1:1 with the pad size. Four 1.7mm diameter bumps are used for each of the 4.3mm square GND pads sections giving a 50% solder paste padding. The lower component settling with this ensures that the pads at the edge are always soldered even at vertical misalignment by distortion or warping.

Thermal Considerations

The QSCOM module consume more than 1 W of DC power. In any application where high ambient temperatures for more than a few seconds can occur, it is important that a sufficient cooling surface is provided to dissipate the heat. The thermal pad at the bottom of the module must be connected to the application board ground planes by soldering. The application board should provide a number of vias under and around the pad to conduct the produced heat to the board ground planes, and preferably to a copper surface on the other side of the board in order to conduct and spread the heat. The module internal thermal resistance should in most cases be negligible compared to the thermal resistance from the module into air, and common equations for surface area required for cooling can be used to estimate the temperature rise of the module. Only copper planes on the circuit board surfaces with a solid thermal connection to the module ground pad will dissipate heat. For an application with high load the maximum allowed ambient temperature should be reduced due to inherent heating of the module, especially with small fully plastic enclosed applications where heat transfer to ambient air is low due to low thermal conductivity of plastic. The module measured on the evaluation board exhibits a temperature rise of about 20°C above ambient temperature. An insufficiently cooled module will rapidly heat beyond operating range in ambient room temperature.

Packaging



PINOUT (STM32MP1 pads named PA, PB, etc. can be used as GPIO ports)

PIN	QSCOM STANDARD	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks Additional functions
1st SPI							
1	SPIA_NSS	PE11	- TIM1_CH2 DFSDM1_CKIN4	SPI4_NSS - USART6_CK	- SAI2_SD_B -	FMC_D8/FMC_DA8 DCMI_D4 LCD_G3 EVENTOUT	
2	SPIA_MISO	PE5	- TRACED3 SAI1_CK2 DFSDM1_CKIN3	SPI4_MISO TIM15_CH1 SAI1_SCK_A SDMMC2_D0DIR	SDMMC1_D0DIR SDMMC2_D6 - SDMMC1_D6	FMC_A21 DCMI_D6 LCD_G0 EVENTOUT	
3	SPIA_MOSI	PE14	- TIM1_CH4 -	SPI4_MOSI -	UART8_RTS/UART8_DE - SAI2_MCLK_B SDMMC1_D123DIR	FMC_D11/FMC_DA11 LCD_G0 LCD_CLK EVENTOUT	
4	SPIA_SCK	PE2	TRACECLK SAI1_CK1 -	I2C4_SCL SPI4_SCK SAI1_MCLK_A -	QUADSPI_BK1_IO2 - ETH1_RGMII_TXD3	FMC_A23 - EVENTOUT	
I2C							
5	I2CA_SCL	PA11	- TIM1_CH4 I2C6_SCL -	I2C5_SCL SPI2_NSS/I2S2_WS UART4_RX USART1_CTS/USART1_NSS	- FDCAN1_RX -	- - LCD_R4 EVENTOUT	
6	I2CA_SDA	PA12	- TIM1_ETR I2C6_SDA -	I2C5_SDA - UART4_TX USART1_RTS/USART1_DE	SAI2_FS_B FDCAN1_TX -	- - LCD_R5 EVENTOUT	
7	INTA	PD12	LPTIM1_IN1 TIM4_CH1 LPTIM2_IN1	I2C4_SCL I2C1_SCL -	QUADSPI_BK1_IO1 SAI2_FS_A -	FMC_ALE/FMC_A17 - EVENTOUT	
8	I2CB_SCL	PZ0	- I2C6_SCL I2C2_SCL -	SPI1_SCK/I2S1_CK -	SPI6_SCK -	- - EVENTOUT	
9	I2CB_SDA	PZ1	- I2C6_SDA I2C2_SDA TRACED7	I2C5_SDA SPI1_MISO/I2S1_SDI I2C4_SDA USART1_RX	SPI6_MISO -	- - EVENTOUT	
10	INTB	PF15	- -	I2C4_SDA I2C1_SDA -	- -	FMC_A9 - EVENTOUT	
CAN							
11	CANA_RX	PD0	- I2C6_SDA DFSDM1_CKIN6	I2C5_SDA - SAI3_SCK_A -	UART4_RX FDCAN1_RX SDMMC3_CMD DFSDM1_DATIN7	FMC_D2/FMC_DA2 - EVENTOUT	
12	CANA_TX	PD1	- I2C6_SCL DFSDM1_DATIN6	I2C5_SCL - SAI3_SD_A -	UART4_TX FDCAN1_TX SDMMC3_D0 DFSDM1_CKIN7	FMC_D3/FMC_DA3 - EVENTOUT	
13	CANB_RX	PB5	ETH_CLK TIM17_BKIN TIM3_CH2 SAI4_D1	I2C1_SMBA SPI1_MOSI/I2S1_SDO I2C4_SMBA SPI3_MOSI/I2S3_SDO	SPI6_MOSI FDCAN2_RX SAI4_SD_A ETH1_PPS_OUT	UART5_RX DCMI_D10 LCD_G7 EVENTOUT	
14	CANB_TX	PB13	- TIM1_CH1N DFSDM1_CKOUT	LPTIM2_OUT SPI2_SCK/I2S2_CK DFSDM1_CKIN1 USART3_CTS/USART3_NSS	FDCAN2_TX - ETH1_RGMII_TXD1	- - UART5_TX EVENTOUT	
SAI							
15	SAI_TX	PD11	- - LPTIM2_IN2	I2C4_SMBA I2C1_SMBA -	- QUADSPI_BK1_IO0 SAI2_SD_A -	FMC_CLE/FMC_A16 - EVENTOUT	
16	SAI_RX	PA0	- TIM2_CH1/TIM2_ETR TIM5_CH1 TIM8_ETR	TIM15_BKIN -	UART4_TX SDMMC2_CMD SAI2_SD_B CRS/ETH1_MII_CRS	- - EVENTOUT	ADC1_INP16, WKUP1
17	SAI_SCK	PD13	- LPTIM1_OUT TIM4_CH2 -	I2C4_SDA I2C1_SDA I2S3_MCK -	- QUADSPI_BK1_IO3 SAI2_SCK_A -	FMC_A18 DSI_TE - EVENTOUT	

PIN	QSCOM STANDARD	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks Additional functions
18	SAI_FS	PI7	- - TIM8_CH3	- - -	- - SAI2_FS_A -	- DCMI_D7 LCD_B7 EVENTOUT	
ETHERNET							
19	ENET_RST	PA4	HDP0 - TIM5_ETR	SAI4_D2 SPI1_NSS/I2S1_WS SPI3_NSS/I2S3_WS USART2_CK	SPI6_NSS - - -	SAI4_FS_A DCMI_HSYNC LCD_VSYNC EVENTOUT	ADC1_INP18, ADC2_INP18, DAC_OUT1
20	ENET_CK125	PG5	- TIM1_ETR -	- - -	- - ETH1_RGMII_CLK125	FMC_A15 - EVENTOUT	
21	ENET_INT	PA9	- TIM1_CH2 -	I2C3_SMBA SPI2_SCK/I2S2_CK -	SDMMC2_CD1R SDMMC2_D5 -	DCMI_D0 LCD_R5 EVENTOUT	
22	ENET_MDIO	PA2	- TIM2_CH3 TIM5_CH3 LPTIM4_OUT	TIM15_CH1 - USART2_TX	SAI2_SCK_B SDMMC2_D0DIR ETH1_MDIO	MDIOS_MDIO - LCD_R1 EVENTOUT	ADC1_INP14, WKUP2
23	ENET_MDC	PC1	TRACED0 - SAI1_D1 DFSDM1_DATIN0	DFSDM1_CKIN4 SPI2_MOSI/I2S2_SDO SAI1_SD_A -	- SDMMC2_CK ETH1_MDC	MDIOS_MDC - EVENTOUT	ADC1_INP11, ADC1_INN10, ADC2_INP11, ADC2_INN10, TAMP_IN3, WKUP6
24	ENET_RXC	PA1	ETH_CLK TIM2_CH2 TIM5_CH2 LPTIM3_OUT	TIM15_CH1N - USART2_RTS/USART2_DE	UART4_RX QUADSPI_BK1_IO3 SAI2_MCLK_B ETH1_RGMII_RX_CLK/ ETH1_RMII_REF_CLK	- - LCD_R2 EVENTOUT	ADC1_INP17, ADC1_INN16
25	ENET_RX_CTL	PA7	- TIM1_CH1N TIM3_CH2 TIM8_CH1N	SAI4_D1 SPI1_MOSI/I2S1_SDO -	SPI6_MOSI TIM14_CH1 QUADSPI_CLK ETH1_RGMII_RX_CTL/ ETH1_RMII_CRS_DV	SAI4_SD_A - EVENTOUT	ADC1_INP7, ADC1_INN3, ADC2_INP7, ADC2_INN3
26	ENET_RXD0	PC4	- - DFSDM1_CKIN2	I2S1_MCK -	SPDIFRX_IN2 - ETH1_RGMII_RXD0/ ETH1_RMII_RXD0	- - EVENTOUT	ADC1_INP4, ADC2_INP4
27	ENET_RXD1	PC5	- - SAI1_D3 DFSDM1_DATIN2	SAI4_D4 - SAI1_D4 -	SPDIFRX_IN3 - ETH1_RGMII_RXD1/ ETH1_RMII_RXD1	SAI4_D3 - EVENTOUT	ADC1_INP8, ADC1_INN4, ADC2_INP8, ADC2_INN4
28	ENET_RXD2	PB0	- TIM1_CH2N TIM3_CH3 TIM8_CH2N	- DFSDM1_CKOUT	UART4_CTS LCD_R3 -	MDIOS_MDIO - LCD_G1 EVENTOUT	ADC1_INP9, ADC1_INN5, ADC2_INP9, ADC2_INN5
29	ENET_RXD3	PH7	- - -	I2C3_SCL SPI5_MISO -	- - ETH1_RGMII_RXD3	MDIOS_MDC DCMI_D9 EVENTOUT	
30	ENET_TX_CTL	PB11	- TIM2_CH4 - LPTIM2_ETR	I2C2_SDA DFSDM1_CKIN7 USART3_RX	- - ETH1_RGMII_TX_CTL/ ETH1_RMII_TX_EN	- DSI_TE LCD_G5 EVENTOUT	
31	ENET_TXC	PG4	- TIM1_BKIN2 -	- - -	- - ETH1_RGMII_GTX_CLK	FMC_A14 - EVENTOUT	
32	ENET_TXD3	PB8	HDP6 TIM16_CH1 TIM4_CH3 DFSDM1_CKIN7	I2C1_SCL SDMMC1_CKIN I2C4_SCL SDMMC2_CKIN	UART4_RX FDCAN1_RX SDMMC2_D4 ETH1_RGMII_TXD3	SDMMC1_D4 DCMI_D6 LCD_B6 EVENTOUT	
33	ENET_TXD2	PC2	- - DFSDM1_CKIN1	- SPI2_MISO/I2S2_SDI DFSDM1_CKOUT -	- - ETH1_RGMII_TXD2	- DCMI_PIXCLK EVENTOUT	ADC1_INP12, ADC1_INN11

PIN	QSCOM STANDARD	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks Additional functions
34	ENET_TXD1	PG14	TRACED1 LPTIM1_ETR - -	- SPI6_MOSI SAI4_D1 USART6_TX	- QUADSPI_BK2_IO3 SAI4_SD_A ETH1_RGMII_TXD1/ ETH1_RMII_TXD1	FMC_A25 - LCD_B0 EVENTOUT	
35	ENET_TXD0	PG13	TRACED0 LPTIM1_OUT SAI1_CK2 -	SAI4_CK1 SPI6_SCK SAI1_SCK_A USART6_CTS/USART6_NSS	- SAI4_MCLK_A ETH1_RGMII_TXD0/ ETH1_RMII_TXD0	FMC_A24 - LCD_R0 EVENTOUT	

SD

36	SD_CD	PB7	- TIM17_CH1N TIM4_CH2 -	I2C1_SDA - I2C4_SDA USART1_RX	- - SDMMC2_D1 DFSDM1_CKIN5	FMC_NL DCMI_VSYNC - EVENTOUT	
37	SD_D1	PC9	TRACED1 - TIM3_CH4 TIM8_CH4	I2C3_SDA I2S_CKIN - -	UART5_CTS QUADSPI_BK1_IO0 - -	SDMMC1_D1 DCMI_D3 LCD_B2 EVENTOUT	
38	SD_D0	PC8	TRACED0 - TIM3_CH3 TIM8_CH3	- - UART4_TX USART6_CK	UART5_RTS/UART5_DE - - -	SDMMC1_D0 DCMI_D2 - EVENTOUT	
39	SD_CLK	PC12	TRACECLK MCO2 SAI4_D3 -	- - SPI3_MOSI/I2S3_SDO USART3_CK	UART5_TX - SAI4_SD_B -	SDMMC1_CK DCMI_D9 - EVENTOUT	
40	SD_CMD	PD2	- - TIM3_ETR -	I2C5_SMBA - UART4_RX -	UART5_RX - - -	SDMMC1_CMD DCMI_D11 - EVENTOUT	
41	SD_D3	PC11	TRACED3 - - DFSDM1_DATIN5	- - SPI3_MISO/I2S3_SDI USART3_RX	UART4_RX QUADSPI_BK2_NCS SAI4_SCK_B -	SDMMC1_D3 DCMI_D4 - EVENTOUT	
42	SD_D2	PC10	TRACED2 - - DFSDM1_CKIN5	- - SPI3_SCK/I2S3_CK USART3_TX	UART4_TX QUADSPI_BK1_IO1 SAI4_MCLK_B -	SDMMC1_D2 DCMI_D8 LCD_R2 EVENTOUT	

USB

43	USBA_VBUS		Not connected				
44	USBA_DN	USB_DM1					
45	USBA_DP	USB_DP1					
46	USBB_VBUS	OTG_VBUS					
47	USBB_DN	USB_DM2					
48	USBB_DP	USB_DP2					

POWER SUPPLY & RESET

49	VIN	3.3V power supply input					
50							
51	NRST_PWREN	This dual function pin is used as reset input and peripheral power supply enable output. NRST_PWREN is directly connected to STM32MP1 NRST and NRST_CORE and enables the DDR memory power supply VDD_DDR. 10nF capacitors on NRST and NRST_CORE protects the device against parasitic resets. The STM32MP1 has permanent internal pull-up resistors to 3.3V. Refer also to STM32MP1 datasheet, chap. 6.3.18 NRST and NRST_CORE pin characteristics.					
52	BOOT_MODE						H: Boot from FLASH L: Boot from UART/USB

DISPLAY

53	LCD_DE CSI_DP2 LVDS1_TX2P	PE13	HDP2 TIM1_CH3 - DFSDM1_CKIN5	- SPI4_MISO - -	- - SAI2_FS_B -	FMC_D10/FMC_DA10 DCMI_D6 LCD_DE EVENTOUT	
54	LCD_VSYNC CSI_DN2 LVDS1_TX2N	PI9	HDP1 - - -	- - - -	UART4_RX FDCAN1_RX - -	- - LCD_VSYNC EVENTOUT	
55	LCD_HSYNC CSI_DP0 LVDS1_TX0P	PI10	HDP0 - - -	- - - -	USART3_CTS/USART3_NSS - - ETH1_GMII_RX_ER/ ETH1_MII_RX_ER	- - LCD_HSYNC EVENTOUT	

PIN	QSCOM STANDARD	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks Additional functions
56	LCD_CLK CSI_DN0 LVDS1_TX0N	PG7	TRACED5 - - -	- - SAI1_MCLK_A USART6_CK	UART8_RTS/UART8_DE QUADSPI_CLK - QUADSPI_BK2_IO3	- DCMI_D13 LCD_CLK EVENTOUT	
57	LCD_R1 CSI_CKN LVDS1_CLKN	PH3	- - - CKIN4	- - - -	QUADSPI_BK2_IO1 SAI2_MCLK_B ETH1_GMII_COL/ ETH1_MII_COL	- - LCD_R1 EVENTOUT	
58	LCD_R2 CSI_DP1 LVDS1_TX1P	PH8	- TIM5_ETR -	I2C3_SDA - - -	- - - -	- DCMI_HSYNC LCD_R2 EVENTOUT	
59	LCD_R3 CSI_DN1 LVDS1_TX1N	PH9	- TIM12_CH2 -	I2C3_SMBA - - -	- - - -	- DCMI_D0 LCD_R3 EVENTOUT	
60	LCD_R4 CSI_DP3 LVDS1_TX3P	PH10	- TIM5_CH1 -	I2C4_SMBA I2C1_SMBA - -	- - - -	- DCMI_D1 LCD_R4 EVENTOUT	
61	LCD_R5 CSI_DN3 LVDS1_TX3N	PH11	- TIM5_CH2 -	I2C4_SCL I2C1_SCL - -	- - - -	- DCMI_D2 LCD_R5 EVENTOUT	
62	LCD_R6 DSI_DP2 LVDS0_TX2P	PH12	HDP2 - TIM5_CH3 -	I2C4_SDA I2C1_SDA - -	- - - -	- DCMI_D3 LCD_R6 EVENTOUT	
63	LCD_R7 DSI_DN2 LVDS0_TX2N	PE15	HDP3 TIM1_BKIN - -	TIM15_BKIN - - USART2_CTS/USART2_NSS	UART8_CTS - FMC_NCE2 -	FMC_D12/FMC_DA12 - LCD_R7 EVENTOUT	
64	LCD_G2	PH13	- - TIM8_CH1N	- - -	UART4_TX FDCAN1_TX -	- LCD_G2 EVENTOUT	
65	LCD_G3	PH14	- - TIM8_CH2N	- - -	UART4_RX FDCAN1_RX -	- DCMI_D4 LCD_G3 EVENTOUT	
66	LCD_G4	PH15	- - TIM8_CH3N	- - -	- - -	- DCMI_D11 LCD_G4 EVENTOUT	
67	LCD_G5	PI0	- TIM5_CH4 -	SPI2_NSS/I2S2_WS - -	- - -	- DCMI_D13 LCD_G5 EVENTOUT	
68	LCD_G6	PI1	- - TIM8_BKIN2	SPI2_SCK/I2S2_CK - -	- - -	- DCMI_D8 LCD_G6 EVENTOUT	
69	LCD_G7	PI2	- - TIM8_CH4	SPI2_MISO/I2S2_SDI - -	- - -	- DCMI_D9 LCD_G7 EVENTOUT	
70	LCD_B1	PG12	LPTIM1_IN1 - -	SPI6_MISO SAI4_CK2 USART6_RTS/USART6_DE	SPDIFRX_IN1 LCD_B4 SAI4_SCK_A ETH1_PHY_INTN	FMC_NE4 - LCD_B1 EVENTOUT	
71	LCD_B2	PG10	TRACED10 - - -	- - - -	UART8_CTS LCD_G3 SAI2_SD_B QUADSPI_BK2_IO2	FMC_NE3 DCMI_D2 LCD_B2 EVENTOUT	
72	LCD_B3	PD10	RTC_REFIN TIM16_BKIN - DFSDM1_CKOUT	I2C5_SMBA SPI3_MISO/I2S3_SDI SAI3_FS_B USART3_CK	- - - -	FMC_D15/FMC_DA15 - LCD_B3 EVENTOUT	
73	LCD_B4	PI4	- - TIM8_BKIN	- - -	- SAI2_MCLK_A -	- DCMI_D5 LCD_B4 EVENTOUT	
74	LCD_B5	PI5	- - TIM8_CH1	- - -	- SAI2_SCK_A -	- DCMI_VSYNC LCD_B5 EVENTOUT	
75	LCD_B6	PI6	- - TIM8_CH2	- - -	- SAI2_SD_A -	- DCMI_D6 LCD_B6 EVENTOUT	

PIN	QSCOM STANDARD	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks Additional functions
76	LCD_B7	PD8	- - DFSDM1_CKIN3	- SAI3_SCK_B USART3_TX	- SPDIFRX_IN1 -	FMC_D13/FMC_DA13 - LCD_B7 EVENTOUT	
Display Control							
77	LCD_EN	PA10	- TIM1_CH3 -	- SPI3_NSS/I2S3_WS USART1_RX	- - MDIOS_MDIO	SAI4_FS_B DCMI_D1 LCD_B1 EVENTOUT	
78	LCD_BL	PA15	DBTRGI TIM2_CH1 /TIM2_ETR SAI4_D2 SDMMC1_CDIR	CEC SPI1_NSS/I2S1_WS SPI3_NSS/I2S3_WS SPI6_NSS	UART4_RTS/UART4_DE SDMMC2_D5 SDMMC2_CDIR SDMMC1_D5	SAI4_FS_A UART7_TX LCD_R1 EVENTOUT	
MISC							
79	LCD_R0 CSI_CKP LVDS1_CLKP	PH2	- LPTIM1_IN2 -	- - -	QUADSPI_BK2_IO0 SAI2_SCK_B ETH1_GMII_CRS/ ETH1_MII_CRS	- - LCD_R0 EVENTOUT	
80	LCD_G0 DSI_DP3 LVDS0_TX3P	PB1	- TIM1_CH3N TIM3_CH4 TIM8_CH3N	- DFSDM1_DATIN1 -	LCD_R6 - ETH1_RGMII_RXD3	MDIOS_MDC - LCD_G0 EVENTOUT	ADC1_INP5, ADC2_INP5
81	LCD_G1 DSI_DN3 LVDS0_TX3N	PE6	TRACED2 TIM1_BKIN2 SAI1_D1 -	TIM15_CH2 SPI4_MOSI SAI1_SD_A SDMMC2_D0	SDMMC1_D2 - SAI2_MCLK_B	FMC_A22 DCMI_D7 LCD_G1 EVENTOUT	
82	LCD_B0	PE4	TRACED1 - SAI1_D2 DFSDM1_DATIN3	TIM15_CH1N SPI4_NSS SAI1_FS_A SDMMC2_CKIN	SDMMC1_CKIN SDMMC2_D4 - SDMMC1_D4	FMC_A20 DCMI_D4 LCD_B0 EVENTOUT	
MIPI-DSI							
83	DSI_DP1 LVDS0_TX1P	DSI_ DP1					
84	DSI_DN1 LVDS0_TX1N	DSI_ DN1					
85	DSI_DP0 LVDS0_TX0P	DSI_ DP0					
86	DSI_DN0 LVDS0_TX0N	DSI_ DN0					
87	DSI_CKP LVDS0_CLKP	DSI_ CKP					
88	DSI_CKN LVDS0_CLKN	DSI_ CKN					
UART							
89	UARTA_RXD	PB2	TRACED4 RTC_OUT2 SAI1_D1 DFSDM1_CKIN1	USART1_RX I2S_CKIN SAI1_SD_A SPI3_MOSI/I2S3_SDO	UART4_RX QUADSPI_CLK - -	- - EVENTOUT	
90	UARTA_TXD	PG11	TRACED11 - -	USART1_TX - UART4_TX -	SPDIFRX_IN0 - ETH1_RGMII_TX_CTL/ ETH1_RMII_TX_EN	- DCMI_D3 LCD_B3 EVENTOUT	
91	UARTB_RXD	PB12	- TIM1_BKIN I2C6_SMBA -	I2C2_SMBA SPI2_NSS/I2S2_WS DFSDM1_DATIN1 USART3_CK	USART3_RX FDCAN2_RX - ETH1_R(G)MII_TXD0	- - UART5_RX EVENTOUT	
92	UARTB_TXD	PB10	TIM2_CH3 - LPTIM1_IN1	I2C2_SCL SPI2_SCK/I2S2_CK DFSDM1_DATIN7 USART3_TX	QUADSPI_BK1_NCS - ETH1_(G)MII_RX_ER	- - LCD_G4 EVENTOUT	
93	UARTC_RXD	PD6	- TIM16_CH1N SAI1_D1 DFSDM1_CKIN4	DFSDM1_DATIN1 SPI3_MOSI/I2S3_SDO SAI1_SD_A USART2_RX	- - - -	FMC_NWAIT DCMI_D10 LCD_B2 EVENTOUT	
94	UARTC_TXD	PD5	- - -	- - USART2_TX	- SDMMC3_D2 -	FMC_NWE - EVENTOUT	
95	UARTC_CTS	PD3	HDP5 - DFSDM1_CKOUT	SPI2_SCK/I2S2_CK DFSDM1_DATIN0 USART2_CTS / USART2_NSS	SDMMC1_D123DIR SDMMC2_D7 SDMMC2_D123DIR SDMMC1_D7	FMC_CLK DCMI_D5 LCD_G7 EVENTOUT	Input signal

PIN	QSCOM STANDARD	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks Additional functions
96	UARTC_RTS	PD4	- - - -	- - SAI3_FS_A USART2_RTS/ USART2_DE	- - SDMMC3_D1 DFSDM1_CKIN0	FMC_NOE - - EVENTOUT	
2nd SPI							
97	SPIB_NSS	PZ3	- - I2C6_SDA I2C2_SDA	I2C5_SDA SPI1_NSS/I2S1_WS I2C4_SDA USART1_CTS/USART1_NSS	SPI6_NSS - - -	- - - EVENTOUT	
98	SPIB_MISO	PA6	- TIM1_BKIN TIM3_CH1 TIM8_BKIN	SAI4_CK2 SPI1_MISO/I2S1_SDI - -	SPI6_MISO TIM13_CH1 - MDIOS_MDC	SAI4_SCK_A DCMI_PIXCLK LCD_G2 EVENTOUT	ADC1_INP3, ADC2_INP3
99	SPIB_MOSI	PZ2	- - I2C6_SCL I2C2_SCL	I2C5_SMBA SPI1_MOSI/I2S1_SDO I2C4_SMBA USART1_TX	SPI6_MOSI - - -	- - - EVENTOUT	
100	SPIB_SCK	PA5	- TIM2_CH1/TIM2_ETR - TIM8_CH1N	SAI4_CK1 SPI1_SCK/I2S1_CK - -	SPI6_SCK - - -	SAI4_MCLK_A - LCD_R4 EVENTOUT	ADC1_INP19, ADC1_INN18, ADC2_INP19, ADC2_INN18, DAC_OUT2

Onboard wiring

Pins used for manufacturing and debugging – leave unconnected					
PIN	(MP1 PAD NAME)	PIN	(MP1 PAD NAME)	PIN	(MP1 PAD NAME)
C1	JTAG_TDI (JTDI)			C3	JTAG_TCK (JTCK-SWCLK)
		B2	JTAG_TDO (JTDO-TRACESWO)		
A1	JTAG_TRST_B (NJTRST)			A3	JTAG_TMS (JTMS-SWDIO)

PIN	USED FOR	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks
Onboard peripherals wiring							
	SERIAL FLASH	PB6 10K-PU	- TIM16_CH1N TIM4_CH1 -	I2C1_SCL CEC I2C4_SCL USART1_TX	- FDCAN2_TX QUADSPI_BK1_NCS DFSDM1_DATIN5	UART5_TX DCMI_D5 - EVENTOUT	
		PF10 10K-PU	- TIM16_BKIN SAI1_D3 SAI4_D4 -	- - SAI1_D4 -	QUADSPI_CLK - -	SAI4_D3 DCMI_D11 LCD_DE EVENTOUT	
		PF8 10K-PU	TRACED12 TIM16_CH1N -	SPI5_MISO SAI1_SCK_B UART7_RTS/UART7_DE	TIM13_CH1 QUADSPI_BK1_IO0 -	- - EVENTOUT	
		PF9 10K-PU	TRACED13 TIM17_CH1N -	SPI5_MOSI SAI1_FS_B UART7_CTS	TIM14_CH1 QUADSPI_BK1_IO1 -	- - EVENTOUT	
	eMMC	PG6 10K-PU	TRACED14 TIM17_BKIN -	- - -	- - SDMMC2_CMD	DCMI_D12 LCD_R7 EVENTOUT	
		PE3 10K-PU	TRACED0 - -	TIM15_BKIN - SAI1_SD_B -	- SDMMC2_CK -	FMC_A19 - EVENTOUT	
		PB14 10K-PU	- TIM1_CH2N TIM12_CH1 TIM8_CH2N	USART1_TX SPI2_MISO/I2S2_SDI DFSDM1_DATIN2 USART3_RTS/USART3_DE	SDMMC2_D0 - -	- - EVENTOUT	
		PB15	RTC_REFIN TIM1_CH3N TIM12_CH2 TIM8_CH3N	USART1_RX SPI2_MOSI/I2S2_SDO DFSDM1_CKIN2 -	SDMMC2_D1 - -	- - EVENTOUT	
		PB3	TRACED9 TIM2_CH2 -	SAI4_CK1 SPI1_SCK/I2S1_CK SPI3_SCK/I2S3_CK -	SPI6_SCK SDMMC2_D2 -	SAI4_MCLK_A UART7_RX - EVENTOUT	
		PB4	TRACED8 TIM16_BKIN TIM3_CH1 -	SAI4_CK2 SPI1_MISO/I2S1_SDI SPI3_MISO/I2S3_SDI SPI2_NSS/I2S2_WS	SPI6_MISO SDMMC2_D3 -	SAI4_SCK_A UART7_TX - EVENTOUT	
		PA8	MCO1 TIM1_CH1 - TIM8_BKIN2	I2C3_SCL SPI3_MOSI/I2S3_SDO - USART1_CK	SDMMC2_CKIN SDMMC2_D4 OTG_FS_SOF/OTG_HS_SOF -	SAI4_SD_B UART7_RX LCD_R6 EVENTOUT	
		PB9	HDP7 TIM17_CH1 TIM4_CH4 DFSDM1_DATIN7	I2C1_SDA SPI2_NSS/I2S2_WS I2C4_SDA SDMMC2_CDIR	UART4_TX FDCAN1_TX SDMMC2_D5 SDMMC1_CDIR	SDMMC1_D5 DCMI_D7 LCD_B7 EVENTOUT	
		PC6	HDP1 - TIM3_CH1 TIM8_CH1	DFSDM1_CKIN3 I2S2_MCK - USART6_TX	SDMMC1_D0DIR SDMMC2_D0DIR SDMMC2_D6 DSI_TE	SDMMC1_D6 DCMI_D0 LCD_HSYNC EVENTOUT	
		PC7	HDP4 - TIM3_CH2 TIM8_CH2	DFSDM1_DATIN3 - I2S3_MCK USART6_RX	SDMMC1_D123DIR SDMMC2_D123DIR SDMMC2_D7 -	SDMMC1_D7 DCMI_D1 LCD_G6 EVENTOUT	
	LED	PA13					Low: LED on

PIN	USED FOR	MP1 PAD	Alternate Function 0-3	Alternate Function 4-7	Alternate Function 8-11	Alternate Function 12-15	Remarks
Onboard peripherals wiring (cont.)							
WLAN/BT 2AE MURATA		PG15	DEBUG_TRACED7 - SAI1_D2 -	I2C2_SDA - SAI1_FS_A USART6_CTS/USART6_NSS	- - SDMMC3_CK -	- DCMI_D13 - -	
		PF1	- - -	I2C2_SCL - -	- SDMMC3_CMD SDMMC3_CDIR	FMC_A1 - -	
		PF0	- - -	I2C2_SDA - -	- SDMMC3_D0 SDMMC3_CKIN	FMC_A0 - -	
		PF4	- - -	- - USART2_RX	- SDMMC3_D1 SDMMC3_D123DIR	FMC_A4 - -	
		PF5	- - -	- - USART2_TX	- SDMMC3_D2 -	FMC_A5 - -	
		PD7	DEBUG_TRACED6 - DFSDM1_DATIN4	I2C2_SCL DFSDM1_CKIN1 -	SPDIFRX_IN0 SDMMC3_D3 -	FMC_NE1 - -	
		PE7	TIM1_ETR TIM3_ETR DFSDM1_DATIN2	- - UART7_RX	- - -	FMC_D4/FMC_DA4 - -	
		PF7	TIM17_CH1 - -	SPI5_SCK SAI1_MCLK_B UART7_TX	- - -	- - -	
		PE9	TIM1_CH1 - DFSDM1_CKOUT	- - UART7_RTS	- - -	FMC_D6/FMC_DA6 - -	
		PE10	TIM1_CH2N - DFSDM1_DATIN4	- - UART7_CTS	- - -	FMC_D7/FMC_DA7 - -	
		PF11	- - -	SPI5_MOSI - -	- SAI2_SD_B -	DCMI_D12 LTDC_G5	BT_DEV_WAKE
		PF12	DEBUG_TRACED4 - -	- - -	- - ETH1_RXD4	FMC_A6 - -	BT_HOST_WAKE
		PF13	DEBUG_TRACED5 - DFSDM1_DATIN6	I2C4_SMBA I2C1_SMBA DFSDM1_DATIN3	- - ETH1_RXD5	FMC_A7 - -	BT_REG_EN
		PF14	DEBUG_TRACED6 - DFSDM1_CKIN6	I2C4_SCL I2C1_SCL -	- - ETH1_RXD6	FMC_A8 - -	WL_HOST_WAKE
		PG0	DEBUG_TRACED0 - DFSDM1_DATIN0	- - -	- - ETH1_TXD4	FMC_A10 - -	WL_REG_EN
		PC13					RTC_LSCO

Electrical characteristics

Absolute maximum ratings

Parameter	Symbol	Min	Max	Remarks
Power supply	VIN	0V	3.9V	
Input voltage on USB VBUS pins	USBA_VBUS USBB_VBUS	0V	6V	
Input voltage on USB DN/DP pins	USBA_DN/DP USBB_DN/DP	0V	5.5V	
Input voltage on any other pins		0V	3.9V	
Storage temperature range	T _{STORAGE}	-40°C	150°C	Version without eMMC
		-40°C	85°C	Version with eMMC

Operating ranges

Parameter	Symbol	Min	Max	Remarks
Power supply	VIN	3.1V	3.6V	
I/O input low level voltage	V _{IL}	-	0.3 x VIN	
I/O input high level voltage	V _{IH}	0.7 x VIN	-	
I/O output voltage	Refer to STM32MP1 datasheet, chap. Output voltage levels.			VDD=VIN=3.3V typ.
Operating temperature range	T _{AMB}	-25°C -40°C	85°C	QSMP /E85 QSMP /I
Processor junction temperature	T _J	-40°C	125°C	

Power supply currents

Parameter	Symbol	VIN	Current	Remarks
At U-Boot prompt	I _{UBOOT}	3.3V	195mA	All pins left unconnected
At Linux prompt	I _{LINUX}	3.3V	170mA	
Sleep	I _{SLEEP}	3.3V	6mA	
Maximum calculated (without WLAN/BT)	I _{MAX}	3.3V	700mA	Calculated on max. IDD's @ 80% onboard power supply efficiency.
Power supply rating	I _{SUPP}	3.3V	1A	With margin for sizing the power supply

Alternate UART pin mappings

	RX	TX	RTS/DE	CTS/NSS	CK	Remarks
USART1	9, 36, 77, 89	21, 90, 99	6	5, 97	8	
USART2	93	22, 94	24, 96	16, 63, 95	19	
USART3	30, 41, 91	42, 76, 92	7	14, 15, 55	39, 72, 91	
UART4	5, 11, 24, 32, 40, 41, 54, 65, 89	6, 12, 16, 38, 42, 64, 90	78	28		
UART5	13, 40, 91	14, 39	38	37		
USART6		34	70	35	1, 38, 56	
UART7		78				
UART8			3, 56	63, 71		

Alternate function mappings

	USART1	USART2	USART3	UART4	UART5	USART6	UART7	UART8	TIM1	TIM2	TIM3	TIM4	TIM5	TIM8	TIM12	TIM13	TIM14	TIM15	TIM16	TIM17	SP11	SP12	SP13	SP14	SP16	SA11	SA12	SA13	SA14	MMC1	FDCAN1	FDCAN2	I2C1	I2C2	I2C3	I2C4	I2C5	I2C6		
1						CK			CH2															NSS			SD_B													
2									CH1									CH1							MISO		CK2				D0DIR									
3								RTS	CH4																MOSI			MCLKB			DIR									
4																									SCK		CK1										SCL			
5	CTS			RX					CH4														NSS									RX						SCL	SCL	
6	RTS			TX					ETR																			FS_B				TX						SDA	SDA	
7			RTS						IN1	IN1		CH1																FS_A						SCL				SCL		
8	CK																					SCK				SCK									SCL				SCL	
9	RX																									MISO									SDA		SDA	SDA	SDA	
10																																		SDA			SDA			
11				RX																									SCK_A			RX							SDA	SDA
12				TX																									SD_A				TX						SCL	SCL
13					RX				BKIN		CH2										BKIN	MOSI			MOSI					D1			RX	SMBA			SMBA			
14			CTS		TX				CH1N	OUT													SCK										TX							
15			CTS							IN2																			SD_A						SMBA			SMBA		
16		CTS		TX					BKIN	CH1			CH1	ETR				BKIN											SD_B											
17									OUT			CH2																	SCK_A					SDA			SDA			
18														CH3															FS_A											
19		CK											ETR									NSS		NSS		NSS				D2										
20									ETR																															
21	TX								CH2														SCK													SMBA				
22		TX							CH1	CH3		OUT	CH3					CH1											SCKB											
23																							MOSI					D1												
24		RTS		RX					CH1N	CH2	OUT		CH2					CH1N												MCLKB										
25									CH1N		CH2			CH1N			CH1													MOSI			D1							
26																																								
27																												D3			D4									
28				CTS					CH2N		CH3			CH2N																										
29																																				SCL				
30			RX							CH4																									SDA					
31									BKIN2																															
32				RX					_CH1			CH3						CH1														CKIN	RX		SCL			SCL		
33																								MISO																
34					TX				ETR																		MOSI				D1									
35					CTS				OUT																	SCK	CK2			CK1										
36	RX								_CH1N			CH2						CH1N																SDA			SDA			
37				CTS							CH4			CH4																		D1				SDA				
38				TX	RTS	CK					CH3			CH3																		D0								
39			CK		TX																						MOSI					D3	CK							
40				RX	RX						ETR																					CMD							SMBA	
41			RX	RX																							MISO				SCK_B	D3								
42			TX	TX																							SCK					MCLKB	D2							

	USART1	USART2	USART3	UART4	UART5	USART6	UART7	UART8	TIM1	TIM2	TIM3	TIM4	TIM5	TIM8	TIM12	TIM13	TIM14	TIM15	TIM16	TIM17	SP11	SP12	SP13	SP14	SP16	SAI1	SAI2	SAI3	SAI4	MMC1	FDCAN1	FDCAN2	I2C1	I2C2	I2C3	I2C4	I2C5	I2C6	
53									CH3															MISO			FS_B												
54				RX																											RX								
55			CTS																																				
56						CK		RTS																		MCLKA													
57																											MCLKB												
58													ETR																						SDA				
59									CH2						CH2																				SMBA				
60													CH1																				SMBA			SMBA			
61													CH2																					SCL		SCL			
62													CH3																					SDA			SDA		
63		CTS						CTS	BKIN									BKIN																					
64				TX										CH1N																		TX							
65				RX										CH2N																		RX							
66														CH3N																									
67													CH4										NSS																
68														BKIN2									SCK																
69														CH4									MISO																
70					RTS				IN1																MISO				CK2										
71								CTS																			SD_B												
72			CK						BKIN										BKIN					MISO				FS_B								SMBA			
73															BKIN												MCLKA												
74															CH1												SCK_A												
75															CH2												SD_A												
76			TX																									SCK_B											
77	RX								CH3															NSS					FS_B										
78				RTS			TX			CH1												NSS		NSS		NSS				D2	CDIR								
79									IN2																		SCK_B												
80									CH3N		CH4				CH3N																								
81									BKIN2									CH2						MOSI		D1	MCLKB			D2									
82									CH1N									CH1N						NSS		D2				CKIN									
89	RX			RX																				MOSI			D1												
90	TX			TX																																			
91			CK		RX				BKIN														NSS										RX		SMBA			SMBA	
92			TX							CH3													SCK												SCL				
93		RX							CH1N									CH1N						MOSI			D1												
94		TX																																					
95		CTS																					SCK								DIR								
96		RTS																										FS_A											
97	CTS																					NSS				NSS								SDA		SDA	SDA	SDA	
98									BKIN		CH1				BKIN		CH1						MISO			MISO				CK2									
99	TX																						MOSI			MOSI								SCL		SMBA	SMBA	SCL	
100									CH1						CH1N								SCK				SCK			CK1									