


Features:

- High precision resistance tolerance: $\pm 0.02\%$
- Low TCR down to $\pm 5 \text{ ppm}/^\circ\text{C}$
- Advanced sulfur resistance verified according to ASTM B 809
- RoHS compliant, REACH compliant, lead free, and halogen free
- AEC-Q200 qualified



Electrical Specifications


Type/Code	Power Rating @ 85°C (W)	Maximum Working Voltage (V)	Maximum Overload Voltage (V)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance			
					±0.02%	±0.05%	±0.1%	±0.5%
RNHT0402	0.063	75	100	± 5	100 - 3K			
				± 10	100 - 3K	47 - 100K		
				± 25		47 - 100K		47 - 150K
RNHT0603	0.1	100	200	± 5	100 - 5.1K			
				± 10	100 - 5.1K	47 - 270K		
				± 25		47 - 270K	47 - 332K	47 - 1M
				± 50	-	-	-	10 - 47
RNHT0805	0.125	150	300	± 5	100 - 10.2K			
				± 10	100 - 10.2K	47 - 475K		
				± 25		47 - 475K	47 - 2.7M	
				± 50	-	-	-	10 - 47
RNHT1206	0.25	200	400	± 5	100 - 33.2K			
				± 10	100 - 33.2K	47 - 1M		
				± 25		47 - 1M	47 - 5.1M	
				± 50	-	-	-	10 - 47

Max Working Voltage: $\sqrt{P \cdot R}$ or max working voltage listed above, whichever is lower.

Overload Voltage: $2.5 \cdot \sqrt{P \cdot R}$ or max overload voltage listed above, whichever is lower.


Operating Temperature Range is -55 to $+155^\circ\text{C}$

Mechanical Specifications




Type/Code	Typical Unit Weight (mg)	L Body Length	W Body Width	T Body Height	D1 Top Termination	D2 Bottom Termination	Unit
RNHT0402	0.54	0.039 ± 0.002 1.00 ± 0.05	0.020 ± 0.002 0.50 ± 0.05	0.012 ± 0.002 0.30 ± 0.05	0.008 ± 0.004 0.20 ± 0.10	0.008 ± 0.004 0.20 ± 0.10	inches mm
RNHT0603	1.8	0.061 ± 0.004 1.55 ± 0.10	0.031 ± 0.004 0.80 ± 0.10	0.018 ± 0.004 0.45 ± 0.10	0.012 ± 0.008 0.30 ± 0.20	0.012 ± 0.008 0.30 ± 0.20	inches mm
RNHT0805	4.7	0.079 ± 0.006 2.00 ± 0.15	0.049 ± 0.006 1.25 ± 0.15	0.022 ± 0.004 0.55 ± 0.10	0.012 ± 0.008 0.30 ± 0.20	0.016 ± 0.008 0.40 ± 0.20	inches mm
RNHT1206	9.0	0.120 ± 0.006 3.05 ± 0.15	0.061 ± 0.006 1.55 ± 0.15	0.022 ± 0.004 0.55 ± 0.10	0.017 ± 0.008 0.42 ± 0.20	0.014 ± 0.010 0.35 ± 0.25	inches mm

Power Derating Curve:



Single Pulse Characteristics



Performance Characteristics

Test	Test Method	Test Specifications	Test Condition
Temperature Coefficient of Resistance (TCR)	JIS-C-5201-1 4.8 IEC-60115-1 4.8	Refer to Electrical Specification table	-55 to +125°C, 25°C is the reference temperature
Short Time Overload	JIS-C-5201-1 4.13	$\leq 47\Omega \Delta R \pm 0.1\%$ $> 47\Omega \Delta R \pm 0.05\%$	RCWV*2.5 or max. overload voltage whichever is lower for 5 seconds
Endurance	MIL-STD-202 Method 108	$\Delta R \pm 0.25\%$	RCWV for 1000 hours with 1.5 hours "ON" and 0.5 hours "OFF"
Biased Humidity	MIL-STD-202 Method 103	$\Delta R \pm 0.25\%$	1000 hours; 85°C / 85% RH, 10% of operating power.
High Temperature Exposure	MIL-STD-202 Method 108	$\leq 47\Omega \Delta R \pm 0.25\%$ $> 47\Omega \Delta R \pm 0.1\%$ for 0603/0805/1206 sizes $> 47\Omega \Delta R \pm 0.2\%$ for 0402 size	at +155°C for 1000 hours
Temperature Cycling	JESD22 Method JA-104	$\leq 47\Omega \Delta R \pm 0.25\%$ $> 47\Omega \Delta R \pm 0.1\%$	-55 to +125°C, 1000 cycles
Resistance to Soldering Heat	JIS-C-5201-1 4.18 IEC-60115-1 4.18	$\Delta R \pm 0.1\%$	260 $\pm$ 5°C for 10 seconds
Insulation Resistance	JIS-C-5201-1 4.6 IEC-60115-1 4.6	$> 1000 M\Omega$	Apply 100V _{DC} for 1 minute

Performance Characteristics (cont.)


Test	Test Method	Test Specifications	Test Condition
Bending Strength (Board Flex)	JIS-C-5201-1 4.33	$\Delta R \pm 0.1\%$	Bending once for 60 seconds Bending displacement: 1206 sizes: 3 mm
Solderability	JIS-C-5201-1 4.17 IEC-60115-1 4.17	95% min. coverage	$245 \pm 5^\circ\text{C}$ for 3 seconds
Terminal Strength	AEC Q200-006	No breakage	Force of 1.8kg for 60 seconds
Mechanical Shock	MIL-STD-202 Method 213	$\Delta R \pm 0.1\%$	Wave Form: Tolerance for half sine shock pulse. Peak value is 100g's. Normal duration (D) is 6.
Vibration	MIL-STD-202 Method 204	$\Delta R \pm 0.1\%$	5 g for 20 minutes, 12 cycles each of 3 orientations. 10 - 2000 Hz
ESD	AEC-Q200-002	$\Delta R \pm 0.5\%$	Human body model 0402, 0603: 0.2 KV 0805, 1206: 1 KV
Resistance to Solvent	MIL-STD-202 Method 215	Marking unsmeared	Add aqueous wash chemical - OKEM clean or equivalent
Sulfur Test	ASTM B-809-95 Modified	$\Delta R \pm 1\%$	$105 \pm 2^\circ\text{C}$, no power rating for 1000 hours
Flammability	UL-94	No ignition of the tissue paper or scorching of the pinewood board	V-0 or V1 are acceptable. Electrical test not required.

RCWV (Rated Continuous Working Voltage) = $\sqrt{P \cdot R}$ or Max. Operating Voltage whichever is lower.

Recommended storage temperature is 15 to 28°C ; Humidity $< 80\%$ R.H.


Shelf Life: 2 years from production date.

Recommended Resistor Reflow Profile




Number of reflow cycles allowed is 3 times.

Recommended Solder Pad




Type/Code	A	B	C	Unit
RNHT0402	0.020 0.50	0.020 0.50	0.024 ± 0.008 0.60 ± 0.20	inches mm
RNHT0603	0.039 1.00	0.039 1.00	0.047 ± 0.008 1.20 ± 0.20	inches mm
RNHT0805	0.047 1.20	0.055 1.40	0.065 ± 0.008 1.65 ± 0.20	inches mm
RNHT1206	0.087 2.20	0.055 1.40	0.079 ± 0.008 2.00 ± 0.20	inches mm

Reel Specifications



Type/Code	ØA	ØB	ØC	W	T	Unit
All sizes	7.008 ± 0.039 178.00 ± 1.00	2.362 ± 0.039 60.00 ± 1.00	0.531 ± 0.028 13.50 ± 0.70	0.374 ± 0.039 9.50 ± 1.00	0.453 ± 0.039 11.50 ± 1.00	inches mm


Taping Specification - Paper Tape



Type/Code	A	B	W	E	F	Unit
RNHT0402	0.028 ± 0.002 0.70 ± 0.05	0.046 ± 0.002 1.16 ± 0.05	0.315 ± 0.004 8.00 ± 0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
RNHT0603	0.043 ± 0.002 1.10 ± 0.05	0.075 ± 0.002 1.90 ± 0.05	0.315 ± 0.004 8.00 ± 0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
RNHT0805	0.063 ± 0.002 1.60 ± 0.05	0.093 ± 0.002 2.37 ± 0.05	0.315 ± 0.004 8.00 ± 0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
RNHT1206	0.079 ± 0.002 2.00 ± 0.05	0.140 ± 0.002 3.55 ± 0.05	0.315 ± 0.004 8.00 ± 0.10	0.069 ± 0.002 1.75 ± 0.05	0.138 ± 0.002 3.50 ± 0.05	inches mm
Type/Code	P0	P ₁	P ₂	ØD0	T	Unit
RNHT0402	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.079 ± 0.002 2.00 ± 0.05	0.061 ± 0.002 1.55 ± 0.05	0.016 ± 0.001 0.40 ± 0.03	inches mm
RNHT0603	0.157 ± 0.004 4.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.061 ± 0.002 1.55 ± 0.05	0.024 ± 0.001 0.60 ± 0.03	inches mm
RNHT0805	0.157 ± 0.004 4.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.061 ± 0.002 1.55 ± 0.05	0.030 ± 0.002 0.75 ± 0.05	inches mm
RNHT1206	0.157 ± 0.004 4.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	0.061 ± 0.002 1.55 ± 0.05	0.030 ± 0.002 0.75 ± 0.05	inches mm

Peel Force of Top Cover Tape - Paper Tape

The peel speed shall be about 300mm/min ± 5%.
The peel force of top cover tape shall be between 8 gf to 60 gf.



Part Marking Specifications

E96 and E24 Values for 0805 and 1206

The nominal resistance is marked on the surface of the overcoating with the use of **four character markings**. Values below 100Ω will use "R" as the decimal holder.

E24 Values for 0603 size

The nominal resistance is marked on the surface of the overcoating with the use of **three character markings**. Values below 100Ω will use "R" as the decimal holder.

Values that are both E24 and E96 follow E96 marking rules.

E24 10 11 12 13 15 16 18 20 22 24 27 30 33 36 39 43 47 51 56 62 68 75 82 91

E96 Values for 0603 size

A two character number is assigned to each standard R-Value (E96) as shown in the chart below.

This is followed by one alpha character which is used as a multiplier.

Each letter from "Y" - "F" represents a specific multiplier.

Alpha Character = Multiplier		Chip Marking	Value
Y = 0.1	C = 1000	01B	10.0 x 100 = 1 KΩ
X = 1	D = 10000	25C	17.8 x 1000 = 17.8 KΩ
A = 10	E = 100000	93D	90.9 x 10000 = 909 KΩ
B = 100	F = 1000000		

E96											
#	R-Value	#	R-Value	#	R-Value	#	R-Value	#	R-Value	#	R-Value
01	10.0	17	14.7	33	21.5	49	31.6	65	46.4	81	68.1
02	10.2	18	15.0	34	22.1	50	32.4	66	47.5	82	69.8
03	10.5	19	15.4	35	22.6	51	33.2	67	48.7	83	71.5
04	10.7	20	15.8	36	23.2	52	34.0	68	49.9	84	73.2
05	11.0	21	16.2	37	23.7	53	34.8	69	51.1	85	75.0
06	11.3	22	16.5	38	24.3	54	35.7	70	52.3	86	76.8
07	11.5	23	16.9	39	24.9	55	36.5	71	53.6	87	78.7
08	11.8	24	17.4	40	25.5	56	37.4	72	54.9	88	80.6
09	12.1	25	17.8	41	26.1	57	38.3	73	56.2	89	82.5
10	12.4	26	18.2	42	26.7	58	39.2	74	57.6	90	84.5
11	12.7	27	18.7	43	27.4	59	40.2	75	59.0	91	86.6
12	13.0	28	19.1	44	28.0	60	41.2	76	60.4	92	88.7
13	13.3	29	19.6	45	28.7	61	42.2	77	61.9	93	90.9
14	13.7	30	20.0	46	29.4	62	43.2	78	63.4	94	93.1
15	14.0	31	20.5	47	30.1	63	44.2	79	64.9	95	95.3
16	14.3	32	21.0	48	30.9	64	45.3	80	66.5	96	97.6

Note: 0402 size is unmarked.

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union's directive regarding "Restrictions on Hazardous Substances" (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status				
Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition
RNHT	Automotive Grade High Temperature Thin Film Chip Resistor	SMD	YES	100% Matte Sn over Ni

"Conflict Metals" Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the "conflict region" of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to "REACH"

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, "The Registration, Evaluation, Authorization and Restriction of Chemicals", otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy

It is the policy of Stackpole Electronics, Inc. to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

How to Order

R	N	H	T	1	2	0	6	B	T	E	1	0	0	R
Product Series		Size		Tolerance		Packaging				TCR		Resistance Value		
RNHT		Size		Code	Tol.	Code	Description	Size	Quantity	Code	ppm	Four characters with the multiplier used as the decimal holder.		
		0402		Y	0.02%	T	7" Reel	0402	10000	Y	5	47 ohm = 47R0		
		0603		A	0.05%		Paper Tape	0603, 0805, 1206	5000	T	10	100 Kohm = 100K		
		0805		B	0.1%					E	25	5.1 Mohm = 5M10		
		1206		D	0.5%					C	50			