

## Specification Sheet

Part Number: MK9PUA

Tool made of heavy duty parts to ensure optimum performance in demanding environments.

Ideal for heavy-duty ties (T50-T250), clamp and button head ties.

Same ergonomic improvements as the MK7P.

Low weight, comfortable grip and easy trigger depression.

Very durable, with adjustable, easy to read tension settings.

Lock-out features available.

Comes with lower air attachment, and optional upper air attachment.



MK9 Pneumatic, Top Air Supply Connection, Plastic Housing, 1/Pkg

|                |           |
|----------------|-----------|
| Article Number | 110-09112 |
|----------------|-----------|

|      |      |
|------|------|
| Type | MK9P |
|------|------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                                |   |
|--------------------------------|---|
| Product Description            | The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties. Like the MK7P, HellermannTyton's MK9P incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P features adjustable, easy to read tension settings. Lock-out features are available. The MK9P is available with lower air attachment (standard) or can be ordered with an upper air attachment. |
| Short Description              | MK9 Pneumatic, Top Air Supply Connection, Plastic Housing, 1/Pkg  |
| Global Part Name               | MK9P-PA66GF30-BK  |
| Length L (Metric)              | 280   |
| Width W (Metric)               | 55  |
| Cable Ties                     | T50 thru T250 Series CTT20 thru CTT175 Series EI-TY Series Button Head Series   |
| Cycle Time                     | 2 strokes per second  |
| Height H (Metric)              | 200   |
| Tension Setting Tools          | Adjustable  |
| Cable Tie Width Max (Imperial) | 0.5   |
| Power Supply                   | Dry or lubricated air   |
| Material                       | Polyamide 6.6, glass fiber reinforced (PA66GF30%)   |

|                              |                            |
|------------------------------|----------------------------|
| Material Shortcut            | PA66GF30                   |
| UV Resistant (Yes/No)        | No                         |
| Use Conditions               | For Indoor and Outdoor Use |
| Reach Compliant (Article 33) | No                         |
| ROHS Compliant               | Yes                        |
| Package Quantity (Imperial)  | 1                          |
| Package Quantity (Metric)    | 1                          |
| Customs Number               | 8467195090                 |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)