

Specification Sheet

Part Number: 156-01093



The 360 degree enclosure ensures the entire bundle is secure when being routed by this clip.

Locking tab on this clip is small enough that it will not interfere with any other portion of the wire routing, but is significant enough to allow for manual disengagement if service is needed.

The cable tie portion of this two-piece design allows for two wire bundles to be routed with the same piece.

LOC Locking Clamp, 10-14mm, Assembled with T50R, PA66HIRHSUV, Black, 2500/ctn

Article Number	156-01093
Type	T50RLOC10-14
Color	Black (BK)
Quantity Per	pack
Product Description	HellermannTyton's two-piece cable tie assembly offers dual bundle routing. The omega clip portion creates a full and secure lock completely around one bundle, while the cable tie creates a secure solution for a second bundle.
Short Description	LOC Locking Clamp, 10-14mm, Assembled with T50R, PA66HIRHSUV, Black, 2500/ctn

Global Part Name	T50RLOC10-14-PA66HS/PA66HIRHSUV-BK
------------------	------------------------------------

Minimum Tensile Strength (Imperial)	50
-------------------------------------	----

Minimum Tensile Strength (Metric)	220
-----------------------------------	-----

Length L (Imperial)	1.72
---------------------	------

Length L (Metric)	43.73
-------------------	-------

Fixation Method	Omega Clip
-----------------	------------

Identification Plate Position	none
-------------------------------	------

Width W (Imperial)	0.47
--------------------	------

Width W (Metric)	12.0
------------------	------

Bundle Diameter Min (Imperial)	0.39
--------------------------------	------

Bundle Diameter Min (Metric)	10.0
------------------------------	------

Bundle Diameter Max (Imperial)	0.55
--------------------------------	------

Bundle Diameter Max (Metric)	14.0
------------------------------	------

Height H (Imperial)	1.72
---------------------	------

Height H (Metric)	43.75
-------------------	-------

Depth D (Imperial)	0.42
--------------------	------

Depth D (Metric)	10.75
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HIRHSUV PA66HS
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)