

Specification Sheet

Part Number: 156-01640

2-Piece assembled fir tree cable tie secures bundles running perpendicular to 9x17 oval mounting hole.

Updated 9x17 mm oval fir tree design maintains bundle orientation.

Fir tree provides low insertion force with high extration resistance, for easy assembly and reliable performance.

Disc feature prevents rattling in high-vibration applicatiосn and protects against debris ingress.



2-Piece Cable Tie with Oval Fir Tree Mount, 8.0" Long, 9.0 x 17.0 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 500/bag

Article Number	156-01640
----------------	-----------

Type	T50RFT9X17A2
------	--------------

Color	Black (BK)
-------	------------

Quantity Per	pack
--------------	------

Product Description	These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. The fir tree base will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be oriented to the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.
---------------------	---

Short Description	2-Piece Cable Tie with Oval Fir Tree Mount, 8.0" Long, 9.0 x 17.0 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 500/bag
Global Part Name	T50RFT9X17A2-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	203.2
Fixation Method	Fir tree for round holes
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.2
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Panel Thickness Min (Imperial)	0.02

Panel Thickness Max (Imperial)	0.22
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	5.5
Mounting Hole Diameter D (Imperial)	0.35 x 0.67
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
Mounting Hole Diameter D Max (Metric)	17.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)