

Specification Sheet

Part Number: 596-01009

- Made with UV-stable inks and materials for durability and weather resistance
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments
- High abrasion and scuff resistance for high-performance labeling
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections



Solar Label, Printable, MAXIMUM DC VOLTAGE LABEL, 3.75" X 1.0", PET, Red, 10/pkg

|                |            |
|----------------|------------|
| Article Number | 596-01009  |
| Type           | MDCV202010 |
| Color          | Red (RD)   |
| Quantity Per   | pack       |

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description       | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| Short Description         | Solar Label, Printable, MAXIMUM DC VOLTAGE LABEL, 3.75" X 1.0", PET, Red, 10/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Global Part Name          | MDCV202010-840/281-RD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width W (Imperial)        | 3.75                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Width W (Metric)          | 92.25                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Thickness T (Imperial)    | 0.0025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Thickness T (Metric)      | 64.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Height H (Imperial)       | 1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Height H (Metric)         | 25.40                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width of Liner (Metric)   | 98.29                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width of Liner (Imperial) | 3.87                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                                |                                                                            |
|--------------------------------|----------------------------------------------------------------------------|
| Material                       | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut              | 840/281                                                                    |
| Adhesive                       | Acrylic                                                                    |
| Halogen Free                   | Yes                                                                        |
| UV Resistant (Yes/No)          | Yes                                                                        |
| Use Conditions                 | For Indoor and Outdoor Use                                                 |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C)                                          |
| Operating Temperature          | -40°F to +302°F (-40°C to +150°C)                                          |
| Reach Compliant (Article 33)   | Yes                                                                        |
| ROHS Compliant                 | Yes                                                                        |
| Certification/Specification    | CSA 66956 UL 969 NEC2023 NEC2020                                           |
| UL Recognized (US)             | Yes                                                                        |
| Package Quantity (Imperial)    | 10                                                                         |
| Package Quantity (Metric)      | 10                                                                         |
| Customs Number                 | 3919905060                                                                 |
| Labels per Column              | 1                                                                          |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)