

TECHNICAL DATA SHEET

Part No. T150L0UVX2
Article No. 111-15460
Type T150L



Used in the solar industry and other applications, HellermannTyton offers cable ties made of UV stabilized PA66UV material. This material provides additional protection against UV radiation for long-term outdoor use and is available in various styles, tensile strengths, and bundle diameters. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Material	Polyamide 6.6 UV-resistant (PA66UV)
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Flammability	UL 94 HB
Halogen Free	Yes
Plenum Rating	AH-2
UV Resistant	Yes
Use Conditions	For Indoor and Outdoor Use
Color	Black (BK)
Pkg. Qty.	25
Carton Qty.	500
Customs Number	3926909988

Cable Tie Head Length (imperial)	0.51 "
Cable Tie Head Length (metric)	13.0 mm
Cable Tie Head Width (imperial)	0.55 "
Cable Tie Head Width (metric)	14.0 mm
Height (imperial)	0.37 "
Height (metric)	9.5 mm
Length (imperial)	32.3 "
Length (metric)	820.0 mm
Max. Bundle Diameter (imperial)	9.65 "
Max. Bundle Diameter (metric)	245.0 mm
Min. Tensile Strength (imperial)	175 lbs
Min. Tensile Strength (metric)	780 N
Serration Side	Inside Serrated
Thickness (imperial)	0.079 "
Thickness (metric)	2 mm
Width (imperial)	0.35 "
Width (metric)	8.9 mm

