
TECHNICAL DATA SHEET

HellermannTyton

Part No. 596-00253
Article No. 596-00253
Type DC2011



Designed with cross-laminated UV stable materials, these variable print Solar Installation Labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Adhesive	Acrylic
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Halogen Free	Yes
UV Resistant	Yes
Use Conditions	For Indoor and Outdoor Use
Color	Red (RD)

Pkg. Qty.	50
Carton Qty.	20
Customs Number	3919102055

Description	2014
Height (imperial)	2.0 "
Height (metric)	50.8 mm
Labels per Column	1
Labels per Row	1
Width (imperial)	4.0 "
Width (metric)	101.6 mm

HF RoHS

Contact HellermannTyton for more information. Visit www.hellermann.tyton.com or call 800.537.1512
Disclaimer: The information in this datasheet is for informational purposes only.
Information is subject to change at any time without notice.

created on 2026-04-15