



## Carrier-Q7-D59

Carrier Board for Qseven® Rel. 2.0 / 2.1 Compliant Modules in the 3.5" Form Factor

### Wide range of interfaces for broad development possibilities



#### HIGHLIGHTS

- 3.5" form factor carrier board for Qseven® modules
- Multiple video interfaces
- Multiple connectivity options
- Embedded industrial interfaces


Available in Industrial Temperature Range



#### FEATURES

Video Interfaces	LVDS Single/Dual Channel 18-24-bit + HDMI® Connector <b>or</b> 2 x eDP connectors + Multimode Display Port	Power Supply	24V <sub>DC</sub> ±5% through Micro-fit 2x2 power connector Coin cell battery Holder for CMOS and RTC
Mass Storage	1 x SATA connector with HDD Power connector 1 x M.2 Socket 2 2242 Key B SSD Slot microSD Slot on combo microSD + SIM connector	Operating Temperature*	-40°C ÷ +85°C (Industrial temperature range)
Networking	Up to 2 x Gigabit Ethernet connectors 1 x M.2 Socket 2 2242/3042 Key B Slot for WWAN Modem Modules, connected to on-board miniSIM slot	Dimensions	146 x 102 mm (5.75" x 4.02")
USB	2 x Superspeed USB 5Gbp Host port on Dual Type-A socket 1 x USB 2.0 Host ports on double Type-A sockets 1 x USB 2.0 Host on internal M.2 Socket 1 x USB 2.0 OTG port on micro-AB socket (USB port shared with USB 2.0 lanes of 1 x USB 3.0)	*All carrier board components must remain within the operating temperature at any and all times, including start-up; carrier operating temperature is independent of the module installed. Please refer to the specific module for more details. Actual temperature will widely depend on application, enclosure and/or environment. Upon customer to consider specific cooling solutions for the final system.	
Audio	Audio interface on internal pin header		
Serial Ports	4-wire RS-232 / RS-422 / RS-485 configurable serial port on DB9 male connector 2 x RS-232 Full-modem serial ports on internal header (need LPC interface from Qseven® module) CAN interface on PCB terminal block		
Other Interfaces	SPI internal pin header LPC Bus internal pin header SM Bus / I2C GPIO expander, makes available 16 x GPIOs on internal pin header Front Panel Header 1 x 28 pin connector for additional features (I2C, ACPI signals, SM Bus, Watch Dog, Thermal Management) +12V Tachometric FAN connector Optional Debug USB port on miniB socket Optional MFG connector for JTAG programming of Qseven® module		

## BLOCK DIAGRAM




# Streamline and expedite your edge computing implementations

## EDGEHOG OS

A flexible operating system that adapts to your needs, thanks to the customization tool and Docker support. Reliability and security are built-in through a dual-partition system and native integration with Exein's robust AI-based protection.

## DATA ORCHESTRATION

Integrate third-party services, simplify data flows and analysis, and enhance business efficiency by enabling easy and fast utilization of AI.



## DEVICE MANAGER

Update, configure, and manage remote devices. Optimize time and costs to maximize operational efficiency and security without the need for costly field interventions.

## PORTAL

Analyze data from remote devices, customize the user experience with applications tailored to user needs, and manage user rights, company access, and tenant privileges.

## SERVICES

### Custom Apps



### Device Manager

### »Edgehog

### Data Orchestration

### »Astarte

### Portal

## EDGEHOG OS

### Containers

### SDK



### Double Partition

### Device Manager Agent

### Incremental Updates

### Immutable OS

Scan to know more about our solution

EDGEHOG OS



CLEA DOCS

