

COAXIAL ADAPTER, MMCX, 50 Ohm, jack / jack (female / female)

31_MMCX-50-0-1/111_O

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration

Interface type	Gender	Standard
MMCX	jack (female)	HUBER+SUHNER-MMCX
MMCX	jack (female)	HUBER+SUHNER-MMCX

Interface and material data

MMCX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
MMCX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 3 GHz	26 dB	1.1
3 GHz ... 6 GHz	18 dB	1.28

COAXIAL ADAPTER, MMCX, 50 Ohm, jack / jack (female / female)
31_MMCX-50-0-1/111_O

Mechanical data

Weight	0.0021 kg
Mating cycles	500

Environmental data

Operation temperature	-55 °C ... 155 °C
-----------------------	-------------------

Material compliance

Item number	Directive / Regulation	Rating	Exemptions / Details
22645960	RoHS 2011/65/EU and (EU) 2015/863	Compliant with exemption	6c
	REACH 1907/2006 Article 33 SVHC	Contains one or more SVHC >0,1%	CAS: 7439-92-1 Lead

Ordering Information Table

Item number	Item description	Packaging type
22645960	31_MMCX-50-0-1/111_OE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2403 / Date of publication: 12.07.2025 / uncontrolled copy