


# High Capacitance Supercapacitors



## ADCT-E02R7S

[Request Samples](#)[Check Inventory](#)

Various Sizes

RoHS/RoHS II Compliant

MSL Level = N/A

### Features

- High Energy density up to 6Wh/Kg
- Low Leakage Current as small as 0.80mA
- Low Self-discharge rate, 72 hours @ discharge <5%
- Excellent cycle life of >500K cycles @25C
- Green, meet RoHS requirements.

### Applications

- Power Assist Circuits
- Power Backup
- Micro Energy Storage
- IoT Energy Harvesting
- SSD applications
- DDR power back up
- RTC System power transfer to battery backup

### Electrical Specifications

Part Numbers*	Rated Voltage (U <sub>R</sub> )	Capacitance	Tolerance	ESR (Max)		Continuous Current (Max)	Peak Current (Max)	Leakage Current (Max)	Stored Energy (Max)	Gravimetric Energy Density
ADCT-E02R7S	DC (V)	Farads	See Part Number Identification	AC ESR (mΩ)	DC ESR (mΩ)	A	A	mA	Wh	Wh/kg
ADCT-E02R7SA227	2.7	220	Q, R	1.65	3.20	17.40	174.3	0.80	0.2228	3.43
ADCT-E02R7SA307	2.7	300	Q, R	1.40	2.20	22.70	244.0	1.00	0.3038	3.87
ADCT-E02R7SA407	2.7	400	Q, R	1.20	1.60	28.48	329.3	1.30	0.4050	4.48
ADCT-E02R7SA507	2.7	500	Q, R	1.20	1.60	28.48	375.0	1.40	0.5063	5.59
ADCT-E02R7SB507	2.7	500	Q, R	1.10	1.40	33.23	397.1	1.50	0.5063	5.01
ADCT-E02R7SA607	2.7	600	Q, R	1.10	1.40	33.23	440.2	1.60	0.6075	6.01
ADCT-E02R7SA757	2.7	750	Q, R	1.00	1.30	37.14	512.7	1.80	0.7594	6.08
ADCT-E02R7SA857	2.7	850	Q, R	0.90	1.20	40.39	568.1	1.95	0.8606	6.00

\*For full part numbers, refer to the part number identification section

**Operating Temperature:** -40°C to +70°C.

**Storage Temperature:** 10°C to +40°C, Max. Humidity <85% RH.

**Test Conditions:** +25°C.

All parameters are measured according to the IEC 62813 standard.

Capacitance and DC ESR are measured with  $I(\text{mA}) = 4(C * U_R)$

**Maximum Surge Voltage:** 2.85V ≤ 30 seconds



**Continuous Current (Max):** DC current at which the body temperature rises by  $\Delta T=15^\circ\text{C}$ .

**Leakage Current:** Measured after 72h at Rated Voltage (U<sub>R</sub>)

# High Capacitance Supercapacitors

**ADCT-E02R7S**[Request Samples](#)[Check Inventory](#)**Various Sizes****RoHS/RoHS II Compliant****MSL Level = N/A**

## Mechanical Specifications

**FRONT VIEW****RIGHT VIEW**

### Dimensions: Inches [mm]

Dimensions	ØD±1.5	L	H±0.5
ADCT-E02R7SA227	35	50	5.5
ADCT-E02R7SA307	35	60	
ADCT-E02R7SA407	35	70	
ADCT-E02R7SA507	35	70	
ADCT-E02R7SB507	35	85	
ADCT-E02R7SA607	35	85	
ADCT-E02R7SA757	35	100	
ADCT-E02R7SA857	35	110	

### Dimensions: mm

# High Capacitance Supercapacitors



**ADCT-E02R7S**

Request Samples



Check Inventory




Various Sizes

**RoHS/RoHS II Compliant**


MSL Level = N/A

## Part Number Identification



\*Only part numbers listed in the Electrical Specs table are available. For custom builds, please contact [Abracon](#).

# High Capacitance Supercapacitors



ADCT-E02R7S

Request Samples



Check Inventory




Various Sizes

RoHS/RoHS II Compliant


MSL Level = N/A

## Wave Profile



Zone	Description	Temperature	Times
1	Preheat	$T_{SMIN} \sim T_{SMAX}$ 25°C ~ 130°C	80 sec. MAX
	Preheat Rate	$T_{PREHEAT}$ +4°C/Sec MAX	
2	Wave Temperature	$T_w$ 245°C ~ 260°C	10 sec. MAX Dual wave
	Wave Peak Temperature	$T_p$ 260°C	5 sec. MAX/wave
3	Cooling Rate	$T_{COOLING}$	-5°C/Sec MAX

# High Capacitance Supercapacitors



**ADCT-E02R7S**

Request Samples



Check Inventory



Various Sizes

**RoHS/RoHS II Compliant**

MSL Level = N/A

## Packaging

The product is packaged in a carton containing multiple inner boxes as follows:

Part Number	Pcs/Inner box	Pcs/Intermediate box	Pcs/outer box
ADCT-E02R7SA227	45	180	360
ADCT-E02R7SA307	45	180	270
ADCT-E02R7SA407	45	180	270
ADCT-E02R7SA507	45	180	270
ADCT-E02R7SB507	45	90	180
ADCT-E02R7SA607	45	90	180
ADCT-E02R7SA757	45	90	180
ADCT-E02R7SA857	45	90	180

## Transport of Product

This product is not subject to US DOT or IATA regulations UN3499 since maximum stored energy is below 10Wh and can be considered Non-Hazardous Goods. Please refer to the [Abracon | UN/IATA Transportation Guidelines](#) for more information.

**ATTENTION:** Abracon LLC's products are Commercial-Off-The-Shelf (COTS, which are designed, intended and validated for use in commercial, industrial and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.