

# Product data sheet

Specifications



## Electronic timer module, type on delay, 1.5....30s, 24....250V DC/AC

LA4DT2U

### Main

Range	TeSys
Product or component type	Serial timer modules
Device short name	LA4DT
Poles description	3P
Product compatibility	LC1D09...D38 LC1D80...D150 LC1D40A...D80A

### Complementary

Mounting location	Top
[Uc] control circuit voltage	24...250 V AC 50/60 Hz 24...250 V DC
Control circuit voltage limits	By mechanical contact: 0.8...1.1 Uc
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
Connections - terminals	Control circuit: connector 1 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: connector 1 cable(s) 1...2.5 mm <sup>2</sup> solid with cable end Control circuit: connector 1 cable(s) 1...2.5 mm <sup>2</sup> flexible without cable end Control circuit: connector 1 cable(s) 1...2.5 mm <sup>2</sup> solid without cable end Control circuit: connector 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: connector 2 cable(s) 1...2.5 mm <sup>2</sup> solid with cable end Control circuit: connector 2 cable(s) 1...2.5 mm <sup>2</sup> flexible without cable end Control circuit: connector 2 cable(s) 1...2.5 mm <sup>2</sup> solid without cable end
Tightening torque	1.7 N.m
Electrical durability	30 Mcycles
Timer type	On delay
Time delay range	1.5...30 s
Reset time	150 ms during time delay 50 ms after time delay
Local signalling	Illuminates during time delay by LED
[Ures] residual voltage	3.3 V
Net weight	0.04 kg

### Environment

Standards	IEC 60255-5
Product certifications	CSA UL
IP degree of protection	IP2X conforming to IEC 60529

Ambient air temperature for operation	-25...55 °C
Permissible ambient air temperature around the device	-25...70 °C
Ambient air temperature for storage	-40...80 °C
Protection type	Built-in by varistor
Heat dissipation	2 W
Immunity to microbreaks	10 ms during time delay 2 ms after time delay

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	4.800 cm
Package 1 Length	5.000 cm
Package 1 Weight	48.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	70
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.695 kg

## Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 1

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 8a21c0d1-be95-4e83-b703-1e8075e942f8

## Use Again

### Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins