

# Product data sheet

Specifications



## APC NetShelter Power Cord Kit (6 ea), Locking, C19 to C20, 1.8m

AP8716S

## Overview

<b>Presentation</b>	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
---------------------	---

<b>Lead time</b>	Usually in Stock
------------------	------------------

## Main

<b>Product or component type</b>	Power cord
<b>Input Connection Type</b>	IEC 60320 C20
<b>Cable length</b>	1.8 m
<b>Number of cables</b>	6

## Physical

<b>Colour</b>	Black
<b>Height</b>	30 cm
<b>Width</b>	8 cm
<b>Depth</b>	7 cm
<b>Product weight</b>	2.16 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable

## Input

<b>Max line current</b>	16 A
<b>Input current limits</b>	16 A

## Output

<b>Max current draw</b>	16 A
<b>Number of power socket outlets</b>	1 IEC 60320 C19
<b>Power cable length</b>	1.8 m

## Conformance

---

<b>Product certifications</b>	CCC CSA PSE UL listed VDE
-------------------------------	---------------------------------------

---

## Environmental

---

<b>Ambient air temperature for operation</b>	0...75 °C
<b>Relative humidity</b>	20...80 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-25...75 °C
<b>Storage Relative Humidity</b>	20...80 %
<b>Storage altitude</b>	0...15240 m

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	30 cm
<b>Package 1 Width</b>	8 cm
<b>Package 1 Length</b>	7 cm
<b>Package 1 Weight</b>	2.16 kg
<b>SCC14</b>	10731304279720

---

## Contractual warranty

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	680
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Halogen-free status	Product contains halogen above thresholds

## Use Again

### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins