

Product data sheet

Specifications



Plug outlet, Linergy HK, 1P+N, 16A, 1 point, 2.5mm², cable length 200

AK5PC12

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| | |
|---|--|
| Range | Linergy |
| Product name | HK |
| Product or Component Type | Plug outlet |
| Poles description | 1P + N |
| [Ith] conventional free air thermal current | 16 A |
| I ² t on activation | 100000 A ² .s |
| Number of points | 1 |
| Number of cables | 2 0.004 in ² (2.5 mm ²) |
| Cable length | 0.7 ft (0.2 m) |
| Quantity per Set | Set of 6 |

Complementary

| | |
|-------------------------------|--|
| [Ui] rated insulation voltage | 600 V CSA 600 V UL 690 V IEC 60439-1 |
| Peak current | 25 kA |
| Width | 0.7 in (18 mm) |
| Height | 1.8 in (46 mm) |
| Depth | 1.5 in (38 mm) |
| Product Weight | 0.077 lb(US) (0.035 kg) |

Environment

| | |
|------------------------|--|
| Standards | IEC 60439 |
| Product Certifications | DNV UL LROS (Lloyds register of shipping) CSA |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10I1122623 |
| Discount Schedule | 0I11 |
| GTIN | 3389110576801 |
| Returnability | No |
| Country of origin | FR |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

| | |
|------------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 1.57 in (4.0 cm) |
| Package 1 Width | 4.33 in (11.0 cm) |
| Package 1 Length | 2.56 in (6.5 cm) |
| Package weight(Lbs) | 1.0 oz (28.0 g) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 5.12 in (13.0 cm) |
| Package 2 Width | 5.31 in (13.5 cm) |
| Package 2 Length | 6.14 in (15.6 cm) |
| Package 2 Weight | 8.2 oz (232.0 g) |
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 96 |
| Package 3 Height | 11.81 in (30.0 cm) |
| Package 3 Width | 15.75 in (40.0 cm) |
| Package 3 Length | 23.62 in (60.0 cm) |
| Package 3 Weight | 9.9 lb(US) (4.5 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

| | |
|--|-----------------------------------|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACH Regulation | REACH Declaration |

Use Again

Repack and remanufacture

| | |
|------------|--|
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |