

Product data sheet

Specifications



Base station, Harmony eXLhoist,
standard, 12 relay outputs, cable
connection, 24...240V AC DC

ZARB12W

⚠ To be discontinued on: Mar 31, 2026

⚠ To be discontinued

Main

Range of product	Harmony eXLhoist
Product or component type	Base station
Device short name	ZARB
Product specific application	Hoisting applications Material handling

Complementary

cable entry	Cable gland
Material	PC (polycarbonate)
[Us] rated supply voltage	24...240 V AC/DC
Vibration resistance	0.075 mm (f = 10...55 Hz)
Shock resistance	15 gn 11 ms
Provided equipment	Internal antenna
Nominal output current	0.54 A at 48 V AC conforming to IEC 60947-5-1
Number of relays	12
Relay type	Motion relay outputs with 9 NO contact Auxiliary relay outputs with 3 NO contact
Safety outputs	2 NC relay outputs
Switching capacity in VA	5 VA DC 26 VA AC
Maximum switching current	6.8 mA
Maximum switching voltage	240 V AC/DC (+ 20 %)
Communication network type	Wireless: bluetooth low energy
Transmission frequency	2.4 GHz
Maximum sensing distance	100 m in free field
Number of channels	40
fixing mode	4 holes
Electrical durability	100000 cycles
Mechanical durability	1000000 cycles
service life	10 year(s)
Width	280 mm
Height	305 mm

Depth	100 mm
-------	--------

Net weight	1.45 kg
------------	---------

Environment

IP degree of protection	IP65
NEMA degree of protection	NEMA 4
Pollution degree	3
Electromagnetic compatibility	Resistance to electrostatic discharge - test level: 4 kV class B (on contact) conforming to IEC 61000-4-2 Resistance to electrostatic discharge - test level: 8 kV class B (in air) conforming to IEC 61000-4-2 Resistance to radiated electromagnetic fields - test level: 10 V/m class B conforming to IEC 61000-4-3
Standards	IEC 61000-6-2
Radio agreement	ARIB ICASA RSS SRRC FCC ANATEL
Relative humidity	0...97 %
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Product certifications	KC UL C-Tick CE EAC CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	28.6 cm
Package 1 Length	30.2 cm
Package 1 Weight	1.6 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	7.2 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	1141
----------------------------------	------

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	6e438e59-42d1-4633-bfe2-cb5ef607659b
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Dimensions



Technical Illustration

Dimensions




Image of product / Alternate images

Alternative







Image of product in real life situation

