

Product data sheet

Specifications



Undervoltage release (MN), TeSys Deca frame 2,24V AC 50Hz

GVAU025

Main

| | |
|----------------------------------|----------------------|
| Range | TeSys TeSys Deca |
| Product or component type | Undervoltage release |
| Device short name | GVAU |

Complementary

| | |
|--|--|
| Range compatibility | TeSys GV2ME TeSys GV2LE TeSys GV2L TeSys GV2P TeSys GV3L TeSys GV3P TeSys Deca |
| [Uc] control circuit voltage | 24 V AC 50 Hz |
| Control circuit voltage limits | 0.85...1.1 Un |
| [Ui] rated insulation voltage | 690 V AC conforming to IEC 60947-1 600 V AC conforming to UL 60947-4-1 600 V AC conforming to CSA C22.2 No 60947-4-1 |
| Threshold tripping voltage | 0.7...0.35 Un |
| Inrush power in VA | 12 VA AC |
| Inrush power in W | 8 W |
| Hold-in power consumption in VA | 3.5 VA AC |
| Hold-in power consumption in W | 1.1 W |
| Operating time | 10...15 ms conforming to IEC 60947-1 |
| On-load factor | 100 % |
| Connections - terminals | Screw clamp terminals 1 cable(s) 1...2.5 mm ² solid Screw clamp terminals 2 cable(s) 1...2.5 mm ² solid Screw clamp terminals 1 cable(s) 0.75...2.5 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.75...2.5 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.75...1.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.75...1.5 mm ² flexible with cable end |
| Tightening torque | < 1.4 N.m on screw clamp terminals |
| Mechanical durability | 10000 cycles with GV3P and GV3L 30000 cycles with GV2ME and GV2P |
| Quantity per set | Set of 10 |
| Height | 89 mm |
| Width | 18 mm |
| Depth | 66 mm |
| Product weight | 0.105 kg |

| | |
|--------|-----------|
| Colour | Dark grey |
|--------|-----------|

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

| | |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

| | |
|------------------|----------|
| Package 1 Height | 3.600 cm |
|------------------|----------|

| | |
|-----------------|----------|
| Package 1 Width | 8.500 cm |
|-----------------|----------|

| | |
|------------------|----------|
| Package 1 Length | 9.300 cm |
|------------------|----------|

| | |
|------------------|-----------|
| Package 1 Weight | 108.000 g |
|------------------|-----------|

| | |
|------------------------|-----|
| Unit Type of Package 2 | S02 |
|------------------------|-----|

| | |
|------------------------------|----|
| Number of Units in Package 2 | 42 |
|------------------------------|----|

| | |
|------------------|-----------|
| Package 2 Height | 15.000 cm |
|------------------|-----------|

| | |
|-----------------|-----------|
| Package 2 Width | 30.000 cm |
|-----------------|-----------|

| | |
|------------------|-----------|
| Package 2 Length | 40.000 cm |
|------------------|-----------|

| | |
|------------------|----------|
| Package 2 Weight | 4.895 kg |
|------------------|----------|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant

California proposition 65

WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Connections and Schema

GVAU...



Technical Illustration

Assembly's dimensions

