

Product data sheet

Specifications



External power supply module, Harmony iPC, AC / DC adapter for HMIPSO and HMIDAD

HMIYPSOMAC1

 To be discontinued on: Apr 30, 2029

 To be discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Harmony iPC
Product or Component Type	External power supply module
Accessory / separate part category	Electrical accessory

Complementary

Accessory / separate part destination	HMIDAD Harmony iPC HMIPSP S-Panel PC performance HMIPSO S-Panel PC
Input voltage	90...260 V AC 47...63 Hz
Input current	1600 mA 100 V AC
Output Voltage	24 V DC
Line Rated Current	2.62 A
Inrush current	70 A at 230 V AC

Environment

Ambient air temperature for operation	32...158 °F (0...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Relative Humidity	0...95 % non-condensing
Product Certifications	CE CSA 60950 cULus UL 60950

Ordering and shipping details

Category	US10MC322575
Discount Schedule	0MC3
GTIN	3606480853784
Returnability	No
Country of origin	TW

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications


Package 1 Height	1.36 in (3.45 cm)
Package 1 Width	2.05 in (5.2 cm)
Package 1 Length	4.65 in (11.8 cm)
Package weight(Lbs)	21.2 oz (600 g)
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	6.55 lb(US) (2.97 kg)

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
F-gas usage performance	Only air and vacuum used for insulation / breaking, no F-gas including SF6
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	1d4618f5-6af2-476b-9c12-08aec44ed716
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	No
Silicon free	No

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.