

Product data sheet

Specifications



Pilot light, Harmony 9001K, metal, polycarbonate, domed, green, 30mm, LED green, 48V

9001KP36LGG9

Main

Range of product Harmony 9001K

Product or component type Pilot light

Device short name 9001K

Complementary

Bezel material Metal

Mounting diameter 30 mm

Shape of signaling unit head Round

Lens type Domed plastic

Cap/operator or lens colour Green

Light source Green LED

Bulb base BA 9s

Light block supply Direct 48 V AC/DC

Connections - terminals Screw clamp terminals, 1 x 0.22...2 x 1.5 mm² conforming to IEC 60947-1

Tightening torque 0.8 N.m conforming to IEC 60947-1

Shape of screw head Cross slotted

Shape of screw head Cross slotted

Operating position Any position

[Ui] rated insulation voltage 250 V (pollution degree 2) conforming to IEC 60947-1

[Uiimp] rated impulse withstand voltage 2.5 kV conforming to IEC 60947-1

Short-circuit protection 10 A cartridge fuse conforming to IEC 60947-5-1

Light source LED

[Ith] conventional free air thermal current 10 A

CAD overall width 54 mm

CAD overall height 70 mm

CAD overall depth 42 mm

[Us] rated supply voltage 48 V AC/DC

Net weight 0.134 kg

Device presentation Complete product

Lens type Domed

[Us] rated supply voltage 48 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Light source colour	Green
Lens material	Polycarbonate
Size	30 mm

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C8201-5-1 EN/IEC 60947-5-4 UL 508 CSA C22.2 No 14 JIS C 852 JIS C8201-1
Product certifications	UL 508 NEMA
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Vibration resistance	7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 NEMA 6

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.572 cm
Package 1 Width	5.334 cm
Package 1 Length	9.144 cm
Package 1 Weight	218.0 g

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Dimensions



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.