Product data sheet

Specifications

Guarded Enclosure, Harmony 9001K, die cast zinc, yellow, red push pull mushroom, 30mm

9001KYG1Y1

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001KY
Product or Component Type	Control station
Material	Die cast zinc alloy

Ordering and shipping details

Category	US10CS121426
Discount Schedule	0CS1
GTIN	785901664956
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.29 in (10.9 cm)
Package 1 Width	4.88 in (12.4 cm)
Package 1 Length	6.18 in (15.7 cm)
Package weight(Lbs)	3.26 lb(US) (1.48 kg)

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ›

How we assess product sustainability ›

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	**12**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Pro-active compliance (Product out of EU RoHS legal scope)**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Take-back	**No**

Offer Marketing Illustration

Product benefits / Features

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Harmony 9001K

Compliant with IEC, UL, CSA, EN and NOM standards, CE marking

-25°C to +70°C operating temperature range

IP66, NEMA 4 rated (Heavy duty, oil tight, waterproof and dust tight without requiring boots)

Contacts and heads designed against vibration (2 to 500 Hz: 7gn), ensuring secure mounting and wiring

American Bureau of Shipping Approved for Marine Applications & meet all US automotive standards

Class I Div. 1 (gas) and Class II Div. 1 (dust) with reed contact blocks