

Product data sheet

Characteristics

APDU10450SW

APC NetShelter Rack PDU Advanced,
Switched, 34.6kW, 3PH, 415V, 60A, 560P6, 42
Outlet



Overview

Presentation

APC NetShelter Rack PDU Advanced provide reliable power distribution to IT Equipment within server and/or networking racks. Switched outlets to turn outlets on or off remotely. PDU level power metering via remote access and local display for power visibility and notification of potential overload. 4-in-1 combination outlets which can be used as either C13, C19, C15, or C21 outlets provide unparalleled deployment flexibility. Maximum outlet density with 42 outlets in a 2.2" wide form factor. Outlets on the PDUs are color coded and/or labeled by breaker and input phase on 3 phase models to simplify deployment. Provides an alternating phase design whereby each of the 3 phases are organized into small outlet groups which alternate from top to bottom of the PDU to facilitate better power cord management and promote better load balancing. Power Sharing allows PDUs cascaded together via 2 ethernet ports enable an Network Management Card to continue functioning in the event of an AC power loss. No interruption in Network communication, sensors operation, and alarm traps. Live Swap Network Management Card (NMC) which can be replaced without powering down the PDU or connected devices to minimize downtime in the unlikely event of an NMC power event. Rated and approved to operate up to 60C (140F) at full load ensures reliability and availability even in today's high density deployments. Gigabit ethernet to enhance and standardize network connectivity across all assets in the data center. A second ethernet port (10/100) is available to allow cascading to other PDUs, connect to a 2nd private network, or provide network redundancy. 1% metering accuracy for the peace of mind to use NetShelter Rack PDU Advanced to bill based on power usage. In addition, the higher level of accuracy ensures the most precise measures for capacity planning and threshold alarm monitoring. Two environmental sensor ports allow for optional sensors (sold separately) to be connected. For data center deployments across multiple regions, these PDUs are both UL and CE rated providing one PDU that can be used globally to simplify and standardize deployment.

Lead time

Usually in Stock

Main

| | |
|-----------------------------|----------------------------|
| Main Input Voltage | 3 phase |
| Product or Component Type | PDU |
| Main Output Voltage | 240 V |
| Plug standard | IEC 60309 60 A 3P+N+PE |
| Number of rack unit | 0U |
| Cable length | 5.91 ft (1.8 m) |
| Communication port protocol | 1000BASE-T 10/100BASE-T |

Physical

| | |
|---------------------|------------------------|
| Color | Black |
| Height | 71.89 in (182.6 cm) |
| Width | 2.20 in (5.6 cm) |
| Depth | 2.95 in (7.5 cm) |
| Net Weight | 27.34 lb(US) (12.4 kg) |
| Mounting Location | Side |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted |

Input

| | |
|--------------------------|----------------------------|
| Line Rated Current | 48 A |
| Acceptable Input Voltage | 200...240 V 346...415 V |
| Input current limits | 60 A |
| Load Capacity | 34600 VA |
| Input Frequency | 50/60 Hz |

Output

| | |
|--------------------------------|----------------------------------|
| Number of power socket outlets | 21 C13/C15/C19/C21 21 C13/C15 |
|--------------------------------|----------------------------------|

Conformance

| | |
|-----------|---|
| Standards | UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 subpart B |
|-----------|---|

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | 23...140 °F (-5...60 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |

Ordering and shipping details

| | |
|---------------------|----------------------|
| GTIN | 731304439110 |
| Package weight(Lbs) | 41.89 lb(US) (19 kg) |

Packing Units

| | |
|------------------|--------------------|
| Package 1 Height | 83.07 in (211 cm) |
| Package 1 width | 10.31 in (26.2 cm) |
| Package 1 Length | 5.20 in (13.2 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|