

Product data sheet

Characteristics

GVSCBT6ST

Galaxy VS Classic Battery Cabinet, UL, Type 6, Seismic Tested



Overview

Presentation	Battery cabinet that includes batteries and battery breaker. The cabinet is seismic compliant.
Lead time	Usually Ships within 2 Weeks

Main

Battery Type	VRLA
--------------	------

Physical

Height	58.46 in (148.5 cm)
Width	44.37 in (112.7 cm)
Depth	33.07 in (84 cm)
Net Weight	3828.00 lb(US) (1736.35 kg)

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)

Batteries & Runtime

Device mounting	Enclosed battery cabinet
-----------------	--------------------------

Ordering and shipping details

GTIN	731304406471
Package weight(Lbs)	3575.90 lb(US) (1622 kg)

Packing Units

Package 1 Height	66.46 in (168.8 cm)
Package 1 width	54.02 in (137.2 cm)
Package 1 Length	39.29 in (99.8 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.