



6-32 THREAD STANDOFF ENGINEERING KIT CAT. NO. STR-632				
HEX. =	Threaded Female		Threaded Male/Female	
	Aluminum	Nylon	Aluminum	Nylon
Length	Cat. No.	Cat. No.	Cat. No.	Cat. No.
.250 [6.35]	2208	1903A	8717	4814
.500 [12.70]	2210	1903C	8414	4816
.750 [19.05]	2211	1903D	8416	4818
1.00 [25.40]	2212	1903E	8418	4820

Cat. No. 9903 6-32 x 1/4" Phillips Drive Machine Screw



NOTES:

1. A KIT HAS 25 PIECES OF EACH CAT.NO. FOR A TOTAL QUANTITY OF 425 PIECES AND IS HOUSED IN A 16 TRAY, LABELED ENCLOSURE.
2. MAT'L - ALUMINUM, CLEAR IRIDITE
MAT'L - NYLON 6/6
3. DRAWS WILL BE ASSEMBLED WITH PLASTIC DIVIDER INSTALLED AND PRODUCT PLACED IN THE FRONT PORTION OF EACH DRAW.
4. SCREWS TO BE PLACED IN THE BACK PORTION OF THE UPPER LEFT MOST DRAW BEHIND THE 1/4" OR 3/8" L. ALUMINUM STANDOFFS.

KEYSTONE ELECTRONICS CORP.				
www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500				
PART NAME				
6-32 THREAD , .250 HEX STANDOFF KIT				
MATERIAL				
AS NOTED				
FINISH			DRN BY	DATE
AS NOTED			NT	2.22.19
TOLERANCES	INCH	[MM]	APP'D	SCALE
DECIMAL	±	[±]	LN	-
ANGULAR	±	UNLESS OTHERWISE SPECIFIED	CODE	DWG NO.
DATE	DESCRIPTION	REV.	C	CTR-632