

## 3.8kW Single-Phase 208/240V Basic PDU, 14 Outlets (12 C13 & 2 C19), NEMA L6-20P Input, 15 ft. (4.57 m) Cord, 1U Rack-Mount

MODEL NUMBER: **PDUH20HVL6**



Delivers 208/240V single-phase AC power to multiple loads from a utility outlet, generator or UPS system in a high-density IT environment. Ideal for data centers, server rooms and network wiring closets.

### Description

The PDUH20HVL6 3.3/3.8kW Single-Phase 208/240V Basic PDU is a versatile no-frills unit for data centers, server rooms and network wiring closets. Perfectly suited for high-density IT environments, the PDUH20HVL6 features 14 total outlets—four C13 in front and eight C13 and two C19 in the rear. The NEMA L6-20P input plug with long 15-ft. (4.57 m) cord connects to your facility's compatible AC power source, generator or protected UPS to distribute power to connected equipment. The switchless design prevents an accidental shutdown, which could lead to costly downtime. The reversible all-metal housing supports a variety of mounting options, including 1U horizontal or 0U vertical mounting in EIA-standard 19-inch racks, under a counter or on a wall or workbench.

### Features

#### Reliable Single-Phase 20A 208/240V Power Distribution

- Ideal no-frills PDU for data centers, server rooms and network wiring closets
- 14 total outlets—4 C13 in front, 8 C13 and 2 C19 in rear
- NEMA L6-20P input plug with 15-ft. (4.57 m) power cord
- Rear-panel grounding lug

#### Switchless Design

- Prevents accidental shutdowns and costly downtime

#### Versatile Installation Options

- Reversible all-metal housing faces front or rear in rack
- The PDUH20HVL6 rack PDU (rPDU) supports 1U horizontal or 0U vertical mounting in EIA-standard 19 in. racks
- Also mounts on wall, workbench or under a counter

### Highlights

- NEMA L6-20P input with 15 ft. (4.57 m) power cord
- 14 total outlets—12 C13 and 2 C19; Compatible with Eaton Tripp Lite power cords
- Switchless design prevents accidental shutdown
- Reversible all-metal housing
- Installs in rack, on wall or under counter

### Package Includes

- PDUH20HVL6 3.3/3.8kW Single-Phase 208/240V Basic PDU
- Mounting hardware
- Owner's manual

## Specifications

OVERVIEW	
UPC Code	037332158970
PDU Type	Basic
INPUT	
Input Phase	Single-Phase
PDU Input Voltage	208; 240
Recommended Electrical Service	Single-phase 20A 208/230V service
Maximum Input Amps	16
Maximum Input Amps Details	Agency de-rated to 16A continuous
Input Connection Type	NEMA L6-20P
PDU Plug Type	NEMA L6-20P
Input Cord Details	Input cable is attached
Input Cord Length (ft.)	15
Input Cord Length (m)	4.57
OUTPUT	
Output Capacity (kW)	3.84
Output Capacity Details	3.84kW (240V), 3.33kW (208V) / 20A total capacity (Agency de-rated 16A); 16A max per C19 outlet; 12A max per C13 outlet
Frequency Compatibility	50 / 60 Hz
Output Receptacle Details	Compatible with Eaton Tripp Lite Power Cords
Output Receptacles	(12) C13; (2) C19
Output Nominal Voltage	208/240V
SURGE / NOISE SUPPRESSION	
Automatic Shut-Off	No
PHYSICAL	
Material of Construction	Metal
Rack Height	1U
Form Factors Supported	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation
Minimum Required Rack Depth (cm)	17.27
Minimum Required Rack Depth (inches)	6.8
Outlets Measurement (Center to Center)	Distance between front (C13) outlets = 28.75mm; Distance between rear (C19) outlets = 55mm; Distance between rear (C13) outlets = 28.75mm



Powering Business Worldwide

TRIPP LITE  
SERIES

PDU Form Factor	Horizontal (1U)
Shipping Dimensions (hwd / in.)	11.00 x 2.25 x 20.25
Shipping Dimensions (hwd / cm)	27.94 x 5.72 x 51.44
Shipping Weight (lbs.)	5.90
Shipping Weight (kg)	2.68
Unit Dimensions (hwd / in.)	1.750 x 17.250 x 3.750
Unit Dimensions (hwd / cm)	4.45 x 43.8 x 9.5
Unit Weight (lbs.)	3.75
Unit Weight (kg)	1.70
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-22° to 122°F (-30° to 50°C)
Relative Humidity	5% to 95% non-condensing
Operating Elevation	0-10000 ft. (0-3000 m)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Grounding	Grounding lug
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CAN/CSA-C22.2 No. 62368-1 (Canada); NOM (Mexico); UL 62368-1
Product Compliance	RoHS; FCC Part 15 Class A (USA)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	5-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.