

A11WBM-P27XBC0-0000

odu_amc®_hd



straight_break_away_plug_for_bend_relief

size_1_ip6k8_ip6k9k_coding_b_red_27_contacts_pins_solder_cup_data_transmission_hdmi®_1.3_8.13_gbits

	Basic information	
	Part number	A11WBM-P27XBC0-0000
	Category	connector
	Type of connector	plug
	Assembly situation	straight
	Size	6b86b2

Contact insert description

Special features	data_transmission
Transmission type	HDMI® 1.4 (10.2 Gbit/s)
Contact type	pins
Contact diameter	886be3
Termination type	solder_cup
Wire cross section AWG	5ef463

Technical information

Max. current single contact	28a407	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Max. current insert	0.4 A	VDE 0298-4:2013
Test voltage	0.75 kV DC	EIA-364-20F:2019-02

Cable description

Cable outlet	overmolding
Min. cable diameter	3.2
Max. cable diameter	8.5

Mechanical and environmental data


Locking principle	break_away
Keying	b
Mating cycles	0f8eb4
IP class	IP68 / IP6K9K
Max. operating temperature	125 °C
Min. operating temperature	-51 °C
Weight	11.31 g

ip_protection_class_refers_to_mated_condition


Material and surface treatments

Material	cu_alloy_with_ruthenium_finish
Insulator material	peek
Contact material	gold


DIMENSIONS:



CODING: B



POSITIONS: 27 positions



Further technical information and downloads

Connection diagram

[connection_diagram_27_pin_hdmi_1_4_typ_a](#)

[3D-File \[STP File\]](#)

[Assembly Instruction](#)

[Technical specifications](#)