THERMAL MANAGEMENT SOLUTIONS & THERMAL INTERFACE

Thermal Management Solutions for BGAs 7

Thermal Interface 8

BGA THERMAL SOLUTIONS MATRIX

The following table represents Wakefield-Vette's recommendations for a variety of standard BGA sizes. However, this is by no means a complete list of components that can be used with these heat sinks. To determine suitability for your particular component, request a BGA heat sink evaluation kit.

BGA Sizes (mm)	Heat Sink Footprint (mm)	Heat Sink Height (inches)	Recommended Series #	Attachment Method
17	17 x 17	.40	D10650	Adhesive
19	19 x 19	1.00	602	Adhesive
21	21 x 21	.40	D10850	Adhesive
21	21 x 21	.25 .35 .45 .60	624	Adhesive
23	22 x 22	.40 .60	604	Adhesive
23	22 x 22	.75	605	Adhesive
25	25 x 25	.25 .35 .45 .60	625	Adhesive
27	28 x 28	.25 .35 .45 .60	658	Adhesive
29	30 x 30	.77	606	Adhesive
31	31 x 28	.65	607	Adhesive
31	31 x 31	.80	611	Adhesive
33	32 x 32	.35 .40	610	Adhesive
35	35 x 35	.65	612	Adhesive
35	35 x 35	.25 .35 .45 .60	642	Adhesive
35	35 x 35	.25 .35 .45 .60	630	Adhesive
37.5	37 x 37	.50	613	Adhesive
37.5	37 x 37	.65	659	Adhesive
45.7 x 35.5	37 x 47	.80	617	Adhesive
40	38 x 38	.30 .50 1.00	614	Adhesive
37.5	38 x 38	.29	660	Adhesive
40	40 x 28	.35	643	Clip
40	40 x 40	.26 .53	655	Adhesive
42.5	41 x 41	.41	615	Adhesive
45	43 x 43	.20 .25 .35 .45 .60	628	Adhesive
45	43 x 43	.15	662	Adhesive
47.5	47 x 47	.80	616	Adhesive
50	50 x 50	.40 .65 .80 1.00	698	Adhesive
50	51 x 51	.20 1.00	618	Adhesive
50	52 x 51	.80	622	Adhesive
50	53 x 47	.40 .65 .80 1.00	798	Adhesive
50	64 x 51	.24	620	Adhesive
up to 45	73 x 50	.50 1.00	609	Clip
up to 45	73 x 50	.95	619	Clip

RoHS COMPLIANCE

Please note that Wakefield-Vette part numbers designated with an "E" in this catalog denote new parts in compliance with the RoHS initiative, with the exception of our Precision Clamps. Wakefield-Vette will still continue to offer non-RoHS compliant versions of these parts. Please be aware that many Wakefield-Vette Standard parts have always been compliant since their design inception and therefore will not carry the "E" designation.

Wakefield-Vette requests that you refer to the RoHS compliance tool on our website at www.wakefield-vette.com to verify RoHS compliance. If you require further clarification or information regarding RoHS, please contact the factory.

WAKEFIELDTHERMAL

THERMAL INTERFACE MATERIAL PART NUMBER GUIDE

All of the heat sinks shown in this catalog are available with any of the following thermal tape and interface materials, pre-applied at the factory. Use the "T" series, thermally enhanced, pressure sensitive adhesives to attach the heat sink to the electronic package and provide a good thermal link to the heat sink. Specify these materials in applications where the heat sink will be fixed to the electronic package by some mechanical means other than a tape. Please note that none of these materials are for use in applications requiring electrical isolation from the electronic device. All options other than -T1 and -T4 are RoHS compliant.

Note: To obtain the estimated thermal resistance of the interface material in your application, divide the thermal impedance value by the area of the pad in square inches. For example, a 2" x 2" piece of T4 has a resistance of 1.10 C-in^2/W v 4 in^2=0.275 C/W

"T" Series Thermally Enhanced Pressure Sensitive Adhesives

Suffix	Manufacturer Product	Thermal Impedance C-in^2/W	Thickness, Inches	Package Surface, Comments
-T1	Chomerics, T405	0.47	0.006	Metal/ceramic; aluminum carrier
-T1E	Chomerics, T405R	0.47	0.006	RoHS-compliant version of -T1
-T3	Chomerics, T412	0.25	0.009	Metal/ceramic; very good performance and conformity
-T4	Chomerics, T410	1.10	0.007	Plastic
-T4E	Chomerics, T410R	1.10	0.007	RoHS-compliant version of -T4
-T5	Chomerics, T411	1.00	0.011	Plastic; conforms to out-of-flat packages
-T6	3M, 8810	0.88	0.010	Metal/ceramic; very good adhesion and conformity
-T7	Bergquist, BP 108	1.28	0.008	Metal/ceramic; electrically insulating

ORDERING INFORMATION

Once you have chosen heat sink and thermal interface material that meets your thermal & mechanical requirements it is easy to designate the part number. Simply add the interface material suffix referenced on the chart above to the base part number for the heat sink. The base part number already includes information regarding its size and finish.

Example:

To order the 658 Series heat sink at .350" tall with the T5 thermal interface material, specify part number:

658-35AB - T5

From Catalog Page XX

From Table on Page XX

INTEGRATED CIRCUIT COOLING HEAT SINKS

Heat Sinks For BGAs, Super BGAs, & FPBGAs 12–27

Deltem™ Composite Heat Sinks For BGAs 18

Heat Sinks For Microprocessors & ASICs 28–30

Pin Fin Heat Sinks 31

Elliptical Fin Heat Sinks 32

Pin Fin & Elliptical Fin Heat Sinks 33

Ceramic Heat Sink For To Devices w/ OmniKlip 34–35

Wave Series Heat Sink With Integrated Clip Assembly 36–43



With the increase in heat dissipation from microelectronics devices and the reduction in overall form factors, thermal management becomes a more important element of electronic product design.

Both the performance reliability and life expectancy of electronic equipment are inversely related to the component temperature of the equipment. The relationship between the reliability and the operating temperature of a typical silicon semi-conductor device shows that a reduction in the temperature corresponds to an exponential increase in the reliability and life expectancy of the device. Therefore, long life and reliable performance of a component may be achieved by effectively controlling the device operating temperature within the limits set by the device design engineers.

Heat sinks are devices that enhance heat dissipation from a hot surface,usually the case of a heat generating component, to a cooler ambient, usually air. For the following discussions, air is assumed to be the cooling fluid. In most situations, heat transfer across the interface between the solid surface and the coolant air is the least efficient within the system, and the solid-air interface represents the greatest barrier for heat dissipation. A heat sink lowers this barrier mainly by increasing the surface area that is in direct contact with the coolant. This allows more heat to be dissipated and/or lowers the device operating temperature. The primary purpose of a heat sink is to maintain the device temperature below the maximum allowable temperature specified by the device manufacturers.

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs



624 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs

The **624 Series** is an omnidirectional pin fin heat sink for both natural and forced-convection applications.

Applications include network routers and switches, high-resolution printers, digital cameras, consumer video games, digital video disks (DVD) and global positioning systems (GPS).

PRODUCT FEATURES

- Available in four standard heights, .25 inch, .35 inch, .45 inch, and .60 inch.
- Available with pressure sensitive adhesives for quick and easy mounting. See Page 8.

Standard P/N	Base Dimensions in. Sq.	Fin Height "A" in. (mm)	Typical Applications	Weight lbs. (grams)
624-25AB	.827 (21)	.250 (6.4)	21mm BGA	.009 (4.09)
624-35AB	.827 (21)	.350 (8.9)	21mm BGA	.011 (4.99)
624-45AB	.827 (21)	.450 (11.4)	21mm BGA	.015 (6.81)
624-60AB	.827 (21)	.600 (15.2)	21mm BGA	.026 (11.80)
Material: Aluminum, Black Anodized				

624 THERMAL PERFORMANCE



MECHANICAL DIMENSIONS



Dimensions: in.

625 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs



PRODUCT FEATURES

- Available in four standard heights, .25 inch, .35 inch, .45 inch, and .60 inch.
- Available with pressure sensitive adhesives for quick and easy mounting. See Page 8.

The **625 Series** is an omnidirectional pin fin heat sink for both natural and forced-convection applications.

Applications include network routers and switches, high-resolution printers, digital cameras, consumer video games, digital video disks (DVD) and global positioning systems (GPS).

Standard P/N	Base Dimensions in. Sq.	Fin Height "A" in. (mm)	Typical Applications	Weight lbs. (grams)
625-25AB	.984 (25)	0.250 (6.4)	25 mm BGA	.012 (5.45)
625-35AB	.984 (25)	0.350 (8.9)	25 mm BGA	.014 (6.36)
625-45AB	.984 (25)	0.450 (11.4)	25 mm BGA	.018 (8.17)
625-60AB	.984 (25)	0.600 (15.2)	25 mm BGA	.030 (13.62)
Material: Aluminum, Black Anodized				

625 THERMAL PERFORMANCE



MECHANICAL DIMENSIONS



Dimensions: in.

UNIDIRECTIONAL FIN HEAT SINK FOR BGAs 659 SERIES



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Typical Application	Heat Sink Finish	Weight lbs. (grams)
659-65AB	1.45 (36.8) sq0	.650 (16.5)	37mm BGA	Black Anodized	0.050 (22.68)
Notes: 1. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.					

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS





655 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs AND POWERPC™

Standard P/N	Base Dimensions in. (mm)	Dimension "A" in. (mm)	Dimension "B" in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
655-26AB	1.600 (40.6) sq	0.260 (6.6)	0.125 (3.2)	40mm BGA	Black Anodized	0.038 (17.01)
655-53AB	1.600 (40.6) sq	0.525 (13.3)	0.145 (3.7)	40mm BGA	Black Anodized	0.050 (22.68)
Notes: 1. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.						

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS



OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs AND POWERPC™ 658 SERIES



Standard P/N	Base Dimensions in. (mm)	Dimension "A" in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
658-25AB	1.100 (27.9) sq	0.250 (6.4)	27mm BGA	Black Anodized	0.013 (5.67)
658-35AB	1.100 (27.9) sq	0.350 (8.9)	27mm BGA	Black Anodized	0.015 (6.70)
658-45AB	1.100 (27.9) sq	0.450 (11.4)	27mm BGA	Black Anodized	0.019 (8.50)
658-60AB	1.100 (27.9) sq	0.600 (15.2)	27mm BGA	Black Anodized	0.031 (14.17)
Notes: 1. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.					

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS



KEY:
■ 658-25AB
+ 658-35AB
△ 658-45AB
o 658-60AB

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs



660 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Typical Application	Heat Sink Finish	Weight lbs. (grams)
660-29AB	1.530SQ. (38.9)SQ.	0.285 (7.2)	37mm BGA	Black Anodized	0.031 (14.17)
Notes: 1. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.					

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS



642 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



PRODUCT FEATURES

- Available in four standard heights, .25 inch, .35 inch, .45 inch, and .60 inch.
- Available with pressure sensitive adhesives for quick and easy mounting. See Page 8.

The **642 Series** is an unidirectional pin fin heat sink for both natural and forced-convection applications.

Applications include network routers and switches, high-resolution printers, digital cameras, consumer video games, digital video disks (DVD) and global positioning systems (GPS).

Standard P/N	Base Dimensions in. Sq.	Fin Height "A" in. (mm)	Typical Applications	Weight lbs. (grams)
642-25AB	1.378 (35)	.250 (6.4)	35 mm BGA	.022 (9.99)
642-35AB	1.378 (35)	.350 (8.9)	35 mm BGA	.027 (12.26)
642-45AB	1.378 (35)	.450 (11.4)	35 mm BGA	.031 (14.07)
642-60AB	1.378 (35)	.600 (15.2)	35 mm BGA	.039 (17.71)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

642 THERMAL PERFORMANCE



Performance shown is with T4 thermal adhesive applied.

OMNIDIRECTIONAL PIN FIN HEAT SINK FOR LIMITED HEIGHT BGAs 662 SERIES



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
662-15AG	1.713 (43.5) sq	0.150 (3.8)	45mm BGA	Gold Iridite	0.019 (8.50)
662-15AB	1.713 (43.5) sq	0.150 (3.8)	45mm BGA	Black Anodized	0.019 (8.50)
Notes: 1. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.					

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS





628 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Dimensions "A" in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
628-20AB	1.750 (44.5) x 1.700 (43.2)	0.200 (5.1)	45mm BGA	Black Anodized	0.031 (14.17)
628-25AB	1.750 (44.5) x 1.700 (43.2)	0.250 (6.4)	45mm BGA	Black Anodized	0.038 (17.01)
628-35AB	1.750 (44.5) x 1.700 (43.2)	0.350 (8.9)	45mm BGA	Black Anodized	0.044 (19.84)
628-40AB	1.750 (44.5) x 1.700 (43.2)	0.400 (10.2)	45mm BGA	Black Anodized	0.050 (22.68)
628-65AB	1.750 (44.5) x 1.700 (43.2)	0.650 (16.5)	45mm BGA	Black Anodized	0.056 (25.51)
Notes: 1. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.					

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

NATURAL CONVECTION CHARACTERISTICS



FORCED CONVECTION CHARACTERISTICS



KEY:
△ 628-20AB
● 628-25AB
▲ 628-35AB
○ 628-40AB
■ 628-65AB

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs



630 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs

The **630 Series** is an omnidirectional pin fin heat sink for both natural and forced-convection applications.

Applications include network routers and switches, high-resolution printers, digital cameras, consumer video games, digital video disks (DVD) and global positioning systems (GPS).

Standard P/N	Base Dimensions in. Sq.	Fin Height "A" in. (mm)	Typical Applications	Weight lbs. (grams)
630-25AB	1.378 (35)	.250 (6.4)	35mm BGA	.009 (4.09)
630-35AB	1.378 (35)	.350 (8.9)	35mm BGA	.011 (4.99)
630-45AB	1.378 (35)	.450 (11.4)	35mm BGA	.015 (6.81)
630-60AB	1.378 (35)	.600 (15.2)	35mm BGA	.026 (11.80)
Material: Aluminum, Black Anodized				

PRODUCT FEATURES

- Available in four standard heights, .25 inch, .35 inch, .45 inch, and .60 inch.
- Available with pressure sensitive adhesives for quick and easy mounting. See Page 8.

MECHANICAL DIMENSIONS



Dimensions: in.



698 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Dimensions "A" in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
698-40AB	2.100 (53.3) sq.	0.400 (10.2) sq.	45mm BGA	Black Anodized	0.075 (34.02)
698-65AB	2.100 (53.3) sq.	0.650 (16.5) sq.	45mm BGA	Black Anodized	0.119 (53.86)
698-80AB	2.100 (53.3) sq.	0.800 (20.3) sq.	45mm BGA	Black Anodized	0.125 (56.70)
698-100AB	2.100 (53.3) sq.	1.000 (25.4) sq.	45mm BGA	Black Anodized	0.144 (65.20)
Notes: 1. Optional factory preapplied pressure-sensitive adhesive. See Page 8.					

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

FORCED CONVECTION THERMAL PERFORMANCE DATA (FLOW PARALLEL TO EXTRUSION DIRECTION)



798 SERIES PIN FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Dimensions "A" in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
798-40AB	2.100 (53.3) x 1.860 (47.2)	0.400 (10.2)	45mm BGA	Black Anodized	0.063 (28.35)
798-65AB	2.100 (53.3) x 1.860 (47.2)	0.650 (16.5)	45mm BGA	Black Anodized	0.106 (48.19)
798-80AB	2.100 (53.3) x 1.860 (47.2)	0.800 (20.3)	45mm BGA	Black Anodized	0.113 (51.03)
798-100AB	2.100 (53.3) x 1.860 (47.2)	1.000 (25.4)	45mm BGA	Black Anodized	0.131 (59.53)

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

FORCED CONVECTION THERMAL PERFORMANCE DATA (FLOW PARALLEL TO EXTRUSION DIRECTION)



KEY:
□ 798-40AB ▲ 798-65AB ○ 798-80AB ■ 798-100AB

NOTES:

1 . Heat sink mounting surface flatness: 0.004" TIR

2. Optional factory pre-applied pressure-sensitive adhesive. See Page 8.



643 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs

The **Series 643-35AP** is an omnidirectional pin fin heat sink for both natural and forced-convection applications designed to fit a 40 mm BGA.

Applications include network routers and switches, high-resolution printers, digital cameras, consumer video games, digital video disks (DVD) and global positioning systems (GPS).

Standard P/N	Base Dimensions in. (mm)	Fin Height in. (mm)	Typical Applications	Weight lbs. (grams)
643-35AP	1.60 (40.64) x 1.10 (27.94)	0.350 (8.89)	40 mm BGA	.070 (31.78)
Material: Aluminum, Plain Finish				

PRODUCT FEATURES

- Available with pressure sensitive adhesives to ensure good thermal performance. See page 8.
- Can be ordered with the **829SC clip**. Order clip separately. *(Clip cannot be purchased without heat sink)*

MECHANICAL DIMENSIONS



Dimensions: in.

643 THERMAL PERFORMANCE



Performance shown is with S5 interface material applied.

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

DELTEM™ COMPOSITE HEAT SINKS FOR BGAs



DELTEM™ D10650-40 PIN FIN HEAT SINK

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Weight lbs. (grams)
D10650-40	0.650 (16.5) sq	0.400 (10.2)	0.004 (1.91)
Notes: Available with pressure sensitive adhesives for quick and easy mounting. See Page 8.			

PIN FIN HEAT SINK DELTEM™ D10850-40



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Typical Applications	Weight lbs. (grams)
D10850-40	0.850 (21.6) sq	0.400 (10.2)	21mm BGA	0.006 (3.9)
Notes: Available with pressure sensitive adhesives for quick and easy mounting. See Page 8.				

MECHANICAL DIMENSIONS

DELTEM™ D10650-40 PIN FIN HEAT SINK



Dimensions: in. (mm)

DELTEM™ D10850-40 PIN FIN HEAT SINK



Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS



NATURAL AND FORCED CONVECTION CHARACTERISTICS



HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs

PIN FIN HEAT SINK FOR BGAs HEAT SINK/CLIP ASSEMBLY FOR BGAs AND POWERPC™ PACKAGES 609 SERIES



Standard P/N	Base Dimensions in. (mm)	Dimensions "A" in. (mm)	Typical Applications	Heat Sink Finish	Weight lbs. (grams)
609-50AB	2.895 (73.5) x 2.000 (50.8)	0.500 (12.7)	40&45mm BGA	Black Anodized	0.094 (42.5)
609-100AB	2.808 (71.32) x 1.700 (43.2)	1.00 (25.4)	40&45mm BGA	Black Anodized	0.130 (59.0)
Note: Optional factory pre-applied thermal interface material. S3 (Bergquist Q-Pad 3, 0.14 °C in2/w) S4 (Bergquist Softface, 0.07 °C in2/w)					

MECHANICAL DIMENSIONS



(609-50AB) (609-100AB)

609-50AB HEAT SINK AND CLIP ASSEMBLY

Dimensions: in. (mm)

Designed to fit a .063" thick PCB electronic package thickness of .110"

FORCED CONVECTION THERMAL PERFORMANCE DATA (FLOW PARALLEL TO EXTRUSION DIRECTION)



*Performance is for shrouded conditions. 609-100 will perform better than 609-50 in cases with bypass.



619 SERIES FAN HEAT SINK FOR BGA AND POWERPC™ PACKAGES

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Typical Applications	Heat Sink Finish	Thermal Performance	Weight lbs.(grams)
61995AB124D1	2.871 (72.92) x 1.98 (50.29)	0.953 (24.21)	40&45mm BGA	Black Anodized	1.2° C/W	.150 (68.10)
61995AB054D1	2.871 (72.92) x 1.98 (50.29)	0.953 (24.21)	40&45mm BGA	Black Anodized	1.2° C/W	.150 (68.10)
Note: Optional factory pre-applied thermal interface material. See 609 series.						

FEATURES AND BENEFITS

- Captivated clips for ease of assembly.
- Low acoustic noise.
- Impingement air flow.
- Accommodates BGA packages up to 45 mm in size.

MECHANICAL DIMENSIONS



See 609 Series for PCB hole layout for clip attachment

Dimensions: in.

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs



602 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
602-100AP	.750 (19.1) sq	1.000 (25.4)	Plain	.021 (9.59)
Material: Aluminum, Plain Finish				

MECHANICAL DIMENSIONS



602 THERMAL PERFORMANCE



604 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
604-40AB 604-60AB	.850 (21.6) sq .850 (21.6) sq	.400 (10.2) .600 (15.2)	Black Anodized Black Anodized	.012 (5.60) .016 (7.47)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



604 THERMAL PERFORMANCE



605 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
605-75AB	.880 (22.4) sq	.750 (19.1)	Black Anodized	.030 (13.5)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



605 THERMAL PERFORMANCE



606 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
606-77AB	1.185 (30.1) sq	.767 (19.5)	Black Anodized	.041 (18.7)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



606 THERMAL PERFORMANCE



WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs

607 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
607-65AB	1.200 (30.5) x 1.105 (28.1)	.650 (16.5)	Black Anodized	.041 (18.7)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



607 THERMAL PERFORMANCE



610 SERIES OMNIDIRECTIONAL PIN FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
610-35AB 610-40AB	1.240 (31.5) sq 1.240 (31.5) sq	.350 (8.9) .400 (10.2)	Black Anodized Black Anodized	.022 (10.0) .024 (10.8)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



610 THERMAL PERFORMANCE



611 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
611-80AB	1.200 (30.5) sq	.800 (20.3)	Black Anodized	.036 (16.3)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



611 THERMAL PERFORMANCE



612 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
612-65AB	1.390 (35.3) sq	.650 (16.5)	Black Anodized	.054 (24.5)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



612 THERMAL PERFORMANCE



WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs



613 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
613-50AB	1.450 (36.8) sq	.500 (12.7)	Black Anodized	.046 (20.8)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



613 THERMAL PERFORMANCE



614 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
614-30AB	1.500 (38.1) sq	.300 (7.6)	Black Anodized	.030 (13.8)
614-50AB	1.500 (38.1) sq	.500 (12.7)	Black Anodized	.048 (21.8)
614-100AP	1.500 (38.1) sq	1.000 (25.4)	Plain	.046 (20.9)
Material: Aluminum, Black Anodized or Plain				

MECHANICAL DIMENSIONS



614 THERMAL PERFORMANCE



615 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
615-41AB	1.600 (40.6) sq	.410 (10.4)	Black Anodized	.046 (21.0)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



615 THERMAL PERFORMANCE



616 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
616-80AB	1.85 (47.0) sq	.800 (20.3)	Black Anodized	.054 (24.5)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



616 THERMAL PERFORMANCE



WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR BGAs, SUPER BGAs, PBGAs, & FPBGAs



617 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs

Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
617-80AB	1.450 (36.8) x 1.850 (47.0)	.800 (20.3)	Black Anodized	.082 (37.2)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



617 THERMAL PERFORMANCE



618 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
618-20AB 618-100AP	2.00 (50.8) sq 2.00 (80.8) sq	.200 (5.1) 1.000 (25.4)	Black Anodized Plain	.046 (21.0) .122 (55.5)
Material: Aluminum, Black Anodized or Plain				

MECHANICAL DIMENSIONS



618 THERMAL PERFORMANCE



620 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
620-24AB	2.500 (63.5) x 2.000 (50.8)	.235 (6.0)	Black Anodized	.063 (28.6)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



620 THERMAL PERFORMANCE



622 SERIES UNIDIRECTIONAL FIN HEAT SINK FOR BGAs



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Heat Sink Finish	Weight lbs. (grams)
622-80AB	2.050 (52.1) x 2.000 (50.8)	.800 (20.3)	Black Anodized	.123 (56.0)
Material: Aluminum, Black Anodized				

MECHANICAL DIMENSIONS



622 THERMAL PERFORMANCE



WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR MICROPROCESSORS & ASICs

569, 579, 589, 599 SERIES

HEAT SINKS & CLIP FOR INTEL'S PENTIUM, PENTIUM MMX, AMD'S K6 & K62, CYRIX'S 6X86 & MEDIA GX, CENTAUR/IDT'S WINCHIP C6

PRODUCT FEATURES

- Compact design heat sinks can comfortably fit a variety of Robust Socket 7-based PC boxes.
- Robust clip attachments.
- Clips are not captive to sink.
- To order heat sink with optional interface material pre-applied at the factory, add S4 or S5 suffix to the part number. (See Product Designation)

Standard P/N	Base Dimensions in. (mm)	Fin Height in. (mm)	Thermal Resistance at 200 LFM (°C/W)	Interface Material Options
569-100AK	2.34 (59.44) x 2.68 (67.95)	1.00 (25.4)	1.7	Pages 74–76
579-150AK	2.15 (54.71) x 1.95 (49.53)	1.50 (38.10)	1.6	Pages 74–76
589-150AK	2.15 (54.71) x 3.10 (78.74)	1.50 (38.10)	1.5	Pages 74–76
599X-100AB	1.96 (49.78) x 2.67 (67.95)	1.00 (25.4)	1.9	Pages 74–76
Material: Aluminum, Black Anodized				



569-100AK SERIES

MECHANICAL DIMENSIONS



Dimensions: in.

PRODUCT DESIGNATION

569 - 100 XX - XX

- MODEL NUMBER
- HEIGHT: 100 = 1.00"
- THERMAL INTERFACE: S4 = DELTALINK IV; BLANK = NO THERMAL PAD
- CLIP: AK = SPRING CLIP

650 & 651 SERIES

14-16 Pin DIPs

LOW-COST HEAT SINKS FOR DIPs AND SRAMs



These extruded heat sinks serve as low-cost heat dissipation solutions for DIPs with pin counts from 14 to 16. Use an epoxy such as Wakefield-Vette Engineering DeltaBond™ 152 or 155, or use Wakefield-Vette 2-part DeltaBond™ 156 modified acrylic adhesive. The 650 and 651 are also available in natural aluminum finish. They can be ordered as 650P or 651P.

Standard P/N	Length in. (mm)	Width in. (mm)	Height in. (mm)	Typical Applications	Weight lbs. (grams)
650B	0.250 (6.4)	0.740 (18.9)	0.240 (6.1)	14-Pin, 16-Pin DIP	0.003 (1.36)
651B	0.750 (19.1)	0.415 (10.5)	0.240 (6.1)	14-Pin, 16-Pin DIP	0.005 (2.27)

MECHANICAL DIMENSIONS



650B 651B

Dimensions: in. (mm)

NATURAL AND FORCED CONVECTION CHARACTERISTICS



NOTES:

1. Finish: black anodize
2. TIR: Total Indicator Reading. This is a measure of flatness across the greatest dimension of a surface.

649 SERIES

18 x 18 PGA

SPIDERCLIP™ HEAT SINK ASSEMBLY FOR MOTOROLA MC68040™, MC68060



Standard P/N	Base Dimensions in. (mm)	Height in. (mm)	Base Thickness in. (mm)	Clip Color	Heat Sink Finish	Weight lbs. (grams)
649-33AB	1.70 (43.2) sq	0.315 (8.0)	0.090 (2.3)	Gray	Black Anodized	0.044 (19.84)
649-51AB	1.86 (47.2) sq	0.510 (13.0)	0.090 (2.3)	Gray	Black Anodized	0.056 (25.51)

MECHANICAL DIMENSIONS



Dimensions: in. (mm)

649-33AB SPIDERCLIP™ ASSEMBLY

Dimensions: in. (mm)

649-51AB SPIDERCLIP™ ASSEMBLY

NATURAL AND FORCED CONVECTION CHARACTERISTICS



WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

HEAT SINKS FOR MICROPROCESSORS & ASICs



669 SERIES

SPIDERCLIP™ HEAT SINK ASSEMBLY FOR INTELDX4™, AMD AM486DX2, AND AM486DX4

17 x 17 SPGA

661 SERIES

HEAT SINK WITHOUT CLIP

669 Series SpiderClip™ Heat Sink Assemblies may be applied to the following:

- Intel 80486DX and 80486DX2™ (168 PGA)
- Intel DX4™ (168 PGA)
- Intel 80486SX (168 PGA) and I860XR (208 PGA)
- AMD Am 486 Microprocessors AM486DX2, AM486DX4
- Intel 82495 Cache Controller
- AMD Am 29000 Microcontrollers
- Intel I960CA, I960CF Enbedded Controllers

Standard P/N	Base Dimensions in. (mm)	Dimensions "A" Height in. (mm)	Base Thickness in. (mm)	Clip Color	Standard Finish	Weight lbs. (grams)
669-32AG	1.70 (43.2) sq	0.315 (8.0)	0.090 (2.3)	Black	Gold Iridite	0.044 (19.84)
669-33AB	1.70 (43.2) sq	0.315 (8.0)	0.090 (2.3)	Black	Black Anodized	0.044 (19.84)
669-40AB	1.70 (43.2) sq	0.400 (10.2)	0.090 (2.3)	Black	Black Anodized	0.044 (19.84)
669-52AB	1.70 (43.2) sq	0.520 (13.2)	0.090 (2.3)	Black	Black Anodized	0.050 (22.68)
661-32AG	1.70 (43.2) sq	0.315 (8.0)	0.090 (2.3)	N/A	Gold Iridite	0.044 (19.84)
661-33AB	1.70 (43.2) sq	0.315 (8.0)	0.090 (2.3)	N/A	Black Anodized	0.044 (19.84)
661-40AB	1.70 (43.2) sq	0.400 (10.2)	0.090 (2.3)	N/A	Black Anodized	0.044 (19.84)
661-52AB	1.70 (43.2) sq	0.520 (13.2)	0.090 (2.3)	N/A	Black Anodized	0.050 (22.68)

MECHANICAL DIMENSIONS

669-32AG



669-33AB, 669-40AB, 669-52AB





Dimensions: in. (mm)

Dielectric Breakdown (Nylon Clip Coating)
Dielectric Strength: 100 VDC/mil
Breakdown Voltage: 200 VDC (minimum)

669-32AG SPIDERCLIP™ ASSEMBLY



669-52AB SPIDERCLIP™ ASSEMBLY



NATURAL AND FORCED CONVECTION CHARACTERISTICS



KEY:
□ 669-32AG 0.315 (8.0) Pin Height, low density pin pattern
▲ 669-33AB 0.315 (8.0) Pin Height, high density pin pattern
◆ 669-40AB 0.400 (10.2) Pin Height, high density pin pattern
■ 669-52AB 0.520 (13.2) Pin Height, high density pin pattern

PIN FIN HEAT SINK

RoHS

900 SERIES



Wakefield-Vette's **900 Series** Heat Sinks for Chipset can match up to devices from Intel, Xilinx, TI, Motorola, ATI, AMD, Nvidia, Vishay, Powerex, Infineon, Microsemi, and many more.

These heat sinks are designed for air flow applications in the Telecom, Data Center, Networking, Cloud Computing, and many more Industries.

				Forced Convection							Forced Convection		
Series	Height	Chip Size	Natural Convection	200 LFM	400 LFM	600 LFM	Series	Height	Chip Size	Natural Convection	200 LFM	400 LFM	600 LFM
901	12	19mm	12.74 C/W	6.6 C/W	4.79 C/W	4.16 C/W	906	12	31mm	10.71 C/W	3.49 C/W	2.28 C/W	1.69 C/W
	15	19mm	12.05 C/W	6.3 C/W	4.51 C/W	3.86 C/W		15	31mm	10.14 C/W	3.18 C/W	2.03 C/W	1.5 C/W
	18	19mm	11.35 C/W	5.97 C/W	4.16 C/W	3.47 C/W		18	31mm	9.57 C/W	2.93 C/W	1.86 C/W	1.33 C/W
	21	19mm	10.66 C/W	5.66 C/W	3.89 C/W	3.21 C/W		21	31mm	9.01 C/W	2.72 C/W	1.69 C/W	1.2 C/W
	23	19mm	10.55 C/W	5.36 C/W	3.64 C/W	2.99 C/W		23	31mm	8.88 C/W	2.5 C/W	1.54 C/W	1.07 C/W
	28	19mm	10.27 C/W	4.91 C/W	3.36 C/W	2.71 C/W		28	31mm	8.56 C/W	2.26 C/W	1.38 C/W	.96 C/W
	33	19mm	9.99 C/W	4.52 C/W	3.07 C/W	2.49 C/W		33	31mm	8.24 C/W	2.09 C/W	1.27 C/W	.88 C/W
902	12	21mm	12.4 C/W	6.61 C/W	4.37 C/W	3.7 C/W	907	12	33mm	10.37 C/W	3.32 C/W	2.18 C/W	1.62 C/W
	15	21mm	11.73 C/W	5.84 C/W	4.09 C/W	3.42 C/W		15	33mm	9.82 C/W	3.14 C/W	1.99 C/W	1.45 C/W
	18	21mm	11.06 C/W	5.51 C/W	3.76 C/W	3.07 C/W		18	33mm	9.28 C/W	2.89 C/W	1.78 C/W	1.3 C/W
	21	21mm	10.38 C/W	5.20 C/W	3.49 C/W	2.84 C/W		21	33mm	8.73 C/W	2.67 C/W	1.60 C/W	1.13 C/W
	23	21mm	10.27 C/W	4.9 C/W	3.26 C/W	2.62 C/W		23	33mm	8.60 C/W	2.45 C/W	1.43 C/W	.99 C/W
	28	21mm	9.98 C/W	4.55 C/W	2.98 C/W	2.42 C/W		28	33mm	8.27 C/W	2.24 C/W	1.28 C/W	.87 C/W
	33	21mm	9.7 C/W	4.18 C/W	2.73 C/W	2.21 C/W		33	33mm	7.94 C/W	2.03 C/W	1.15 C/W	.77 C/W
903	12	23mm	12.06 C/W	5.72 C/W	3.95 C/W	3.24 C/W	908	12	35mm	10.03 C/W	3.06 C/W	1.97 C/W	1.49 C/W
	15	23mm	11.41 C/W	5.39 C/W	3.67 C/W	2.99 C/W		15	35mm	9.5 C/W	2.85 C/W	1.81 C/W	1.34 C/W
	18	23mm	10.76 C/W	5.05 C/W	3.35 C/W	2.67 C/W		18	35mm	8.98 C/W	2.6 C/W	1.64 C/W	1.19 C/W
	21	23mm	10.11 C/W	4.74 C/W	3.1 C/W	2.46 C/W		21	35mm	8.46 C/W	2.4 C/W	1.5 C/W	1.07 C/W
	23	23mm	9.99 C/W	4.44 C/W	2.87 C/W	2.31 C/W		23	35mm	8.32 C/W	2.19 C/W	1.34 C/W	.97 C/W
	28	23mm	9.70 C/W	4.09 C/W	2.62 C/W	2.12 C/W		28	35mm	7.99 C/W	1.97 C/W	1.19 C/W	.83 C/W
	33	23mm	9.41 C/W	3.83 C/W	2.43 C/W	1.96 C/W		33	35mm	7.65 C/W	1.82 C/W	1.06 C/W	.7 C/W
904	12	27mm	11.38 C/W	4.84 C/W	3.11 C/W	2.32 C/W	909	12	37.5mm	9.60 C/W	2.93 C/W	1.90 C/W	1.36 C/W
	15	27mm	10.78 C/W	4.48 C/W	2.84 C/W	2.12 C/W		15	37.5mm	9.11 C/W	2.71 C/W	1.72 C/W	1.19 C/W
	18	27mm	10.17 C/W	4.13 C/W	2.56 C/W	1.88 C/W		18	37.5mm	8.61 C/W	2.52 C/W	1.53 C/W	1.05 C/W
	21	27mm	9.56 C/W	3.82 C/W	2.32 C/W	1.72 C/W		21	37.5mm	8.11 C/W	2.25 C/W	1.36 C/W	.88 C/W
	23	27mm	9.44 C/W	3.51 C/W	2.11 C/W	1.6 C/W		23	37.5mm	7.98 C/W	2.04 C/W	1.2 C/W	.75 C/W
	28	27mm	9.13 C/W	3.26 C/W	1.97 C/W	1.49 C/W		28	37.5mm	7.63 C/W	1.82 C/W	1.01 C/W	.63 C/W
	33	27mm	8.82 C/W	3.07 C/W	1.82 C/W	1.39 C/W		33	37.5mm	7.29 C/W	1.6 C/W	.87 C/W	.52 C/W
905	12	29mm	11.04 C/W	4.08 C/W	2.55 C/W	1.98 C/W	910	12	40mm	9.18 C/W	2.84 C/W	1.86 C/W	1.36 C/W
	15	29mm	10.46 C/W	3.82 C/W	2.32 C/W	1.78 C/W		15	40mm	8.71 C/W	2.64 C/W	1.65 C/W	1.18 C/W
	18	29mm	9.87 C/W	3.58 C/W	2.14 C/W	1.58 C/W		18	40mm	8.24 C/W	2.4 C/W	1.44 C/W	.98 C/W
	21	29mm	9.28 C/W	3.33 C/W	1.96 C/W	1.44 C/W		21	40mm	7.77 C/W	2.21 C/W	1.27 C/W	.86 C/W
	23	29mm	9.16 C/W	3.13 C/W	1.82 C/W	1.34 C/W		23	40mm	7.63 C/W	2 C/W	1.15 C/W	.73 C/W
	28	29mm	8.84 C/W	2.82 C/W	1.64 C/W	1.2 C/W		28	40mm	7.27 C/W	1.77 C/W	.99 C/W	.62 C/W
	33	29mm	8.53 C/W	2.59 C/W	1.47 C/W	1.07 C/W		33	40mm	6.92 C/W	1.58 C/W	.85 C/W	.51 C/W

Material: AL 6063
Finish: Black Anodize

Series	Chip Size	Construction	Height	Chip Height	Finish	Interface
	19-	2-	12-	1-	B-	1
901	19 21 23 27 29 31 33 35 37.5	2= Pin Fin	12 = 11.6 15 = 14.6 18 = 17.6 21 = 20.6 23 = 22.6 28 = 27.6 33 = 32.6	1 = .9-2.1 2 = 2.2-3.4	B = BLK ANO	0 = None 1 = T725

Refer to Page 33 for
Installation Instructions

WAKEFIELDTHERMAL

ELLIPTICAL FIN HEAT SINK

900 SERIES

RoHS

Wakefield-Vette's **900 Series** Heat Sinks for Chipset can match up to devices from Intel, Xilinx, TI, Motorola, ATI, AMD, Nvidia, Vishay, Powerex, Infineon, Microsemi, and many more.

These heat sinks are designed for air flow applications in the Telecom, Data Center, Networking, Cloud Computing, and many more Industries.

				Forced Convection							Forced Convection		
Series	Height	Chip Size	Natural Convection	200 LFM	400 LFM	600 LFM	Series	Height	Chip Size	Natural Convection	200 LFM	400 LFM	600 LFM
901	12	19mm	12.74 C/W	6.6 C/W	4.79 C/W	4.16 C/W	906	12	31mm	10.71 C/W	3.49 C/W	2.28 C/W	1.69 C/W
	15	19mm	12.05 C/W	6.3 C/W	4.51 C/W	3.86 C/W		15	31mm	10.14 C/W	3.18 C/W	2.03 C/W	1.5 C/W
	18	19mm	11.35 C/W	5.97 C/W	4.16 C/W	3.47 C/W		18	31mm	9.57 C/W	2.93 C/W	1.86 C/W	1.33 C/W
	21	19mm	10.66 C/W	5.66 C/W	3.89 C/W	3.21 C/W		21	31mm	9.01 C/W	2.72 C/W	1.69 C/W	1.2 C/W
	23	19mm	10.55 C/W	5.36 C/W	3.64 C/W	2.99 C/W		23	31mm	8.88 C/W	2.5 C/W	1.54 C/W	1.07 C/W
	28	19mm	10.27 C/W	4.91 C/W	3.36 C/W	2.71 C/W		28	31mm	8.56 C/W	2.26 C/W	1.38 C/W	.96 C/W
	33	19mm	9.99 C/W	4.52 C/W	3.07 C/W	2.49 C/W		33	31mm	8.24 C/W	2.09 C/W	1.27 C/W	.88 C/W
902	12	21mm	12.4 C/W	6.61 C/W	4.37 C/W	3.7 C/W	907	12	33mm	10.37 C/W	3.32 C/W	2.18 C/W	1.62 C/W
	15	21mm	11.73 C/W	5.84 C/W	4.09 C/W	3.42 C/W		15	33mm	9.82 C/W	3.14 C/W	1.99 C/W	1.45 C/W
	18	21mm	11.06 C/W	5.51 C/W	3.76 C/W	3.07 C/W		18	33mm	9.28 C/W	2.89 C/W	1.78 C/W	1.3 C/W
	21	21mm	10.38 C/W	5.20 C/W	3.49 C/W	2.84 C/W		21	33mm	8.73 C/W	2.67 C/W	1.60 C/W	1.13 C/W
	23	21mm	10.27 C/W	4.9 C/W	3.26 C/W	2.62 C/W		23	33mm	8.60 C/W	2.45 C/W	1.43 C/W	.99 C/W
	28	21mm	9.98 C/W	4.55 C/W	2.98 C/W	2.42 C/W		28	33mm	8.27 C/W	2.24 C/W	1.28 C/W	.87 C/W
	33	21mm	9.7 C/W	4.18 C/W	2.73 C/W	2.21 C/W		33	33mm	7.94 C/W	2.03 C/W	1.15 C/W	.77 C/W
903	12	23mm	12.06 C/W	5.72 C/W	3.95 C/W	3.24 C/W	908	12	35mm	10.03 C/W	3.06 C/W	1.97 C/W	1.49 C/W
	15	23mm	11.41 C/W	5.39 C/W	3.67 C/W	2.99 C/W		15	35mm	9.5 C/W	2.85 C/W	1.81 C/W	1.34 C/W
	18	23mm	10.76 C/W	5.05 C/W	3.35 C/W	2.67 C/W		18	35mm	8.98 C/W	2.6 C/W	1.64 C/W	1.19 C/W
	21	23mm	10.11 C/W	4.74 C/W	3.1 C/W	2.46 C/W		21	35mm	8.46 C/W	2.4 C/W	1.5 C/W	1.07 C/W
	23	23mm	9.99 C/W	4.44 C/W	2.87 C/W	2.31 C/W		23	35mm	8.32 C/W	2.19 C/W	1.34 C/W	.97 C/W
	28	23mm	9.70 C/W	4.09 C/W	2.62 C/W	2.12 C/W		28	35mm	7.99 C/W	1.97 C/W	1.19 C/W	.83 C/W
	33	23mm	9.41 C/W	3.83 C/W	2.43 C/W	1.96 C/W		33	35mm	7.65 C/W	1.82 C/W	1.06 C/W	.7 C/W
904	12	27mm	11.38 C/W	4.84 C/W	3.11 C/W	2.32 C/W	909	12	37.5mm	9.60 C/W	2.93 C/W	1.90 C/W	1.36 C/W
	15	27mm	10.78 C/W	4.48 C/W	2.84 C/W	2.12 C/W		15	37.5mm	9.11 C/W	2.71 C/W	1.72 C/W	1.19 C/W
	18	27mm	10.17 C/W	4.13 C/W	2.56 C/W	1.88 C/W		18	37.5mm	8.61 C/W	2.52 C/W	1.53 C/W	1.05 C/W
	21	27mm	9.56 C/W	3.82 C/W	2.32 C/W	1.72 C/W		21	37.5mm	8.11 C/W	2.25 C/W	1.36 C/W	.88 C/W
	23	27mm	9.44 C/W	3.51 C/W	2.11 C/W	1.6 C/W		23	37.5mm	7.98 C/W	2.04 C/W	1.2 C/W	.75 C/W
	28	27mm	9.13 C/W	3.26 C/W	1.97 C/W	1.49 C/W		28	37.5mm	7.63 C/W	1.82 C/W	1.01 C/W	.63 C/W
	33	27mm	8.82 C/W	3.07 C/W	1.82 C/W	1.39 C/W		33	37.5mm	7.29 C/W	1.6 C/W	.87 C/W	.52 C/W
905	12	29mm	11.04 C/W	4.08 C/W	2.55 C/W	1.98 C/W	910	12	40mm	9.18 C/W	2.84 C/W	1.86 C/W	1.36 C/W
	15	29mm	10.46 C/W	3.82 C/W	2.32 C/W	1.78 C/W		15	40mm	8.71 C/W	2.64 C/W	1.65 C/W	1.18 C/W
	18	29mm	9.87 C/W	3.58 C/W	2.14 C/W	1.58 C/W		18	40mm	8.24 C/W	2.4 C/W	1.44 C/W	.98 C/W
	21	29mm	9.28 C/W	3.33 C/W	1.96 C/W	1.44 C/W		21	40mm	7.77 C/W	2.21 C/W	1.27 C/W	.86 C/W
	23	29mm	9.16 C/W	3.13 C/W	1.82 C/W	1.34 C/W		23	40mm	7.63 C/W	2 C/W	1.15 C/W	.73 C/W
	28	29mm	8.84 C/W	2.82 C/W	1.64 C/W	1.2 C/W		28	40mm	7.27 C/W	1.77 C/W	.99 C/W	.62 C/W
	33	29mm	8.53 C/W	2.59 C/W	1.47 C/W	1.07 C/W		33	40mm	6.92 C/W	1.58 C/W	.85 C/W	.51 C/W

Material: AL 6063
Finish: Black Anodize

Series	Chip Size	Construction	Height	Chip Height	Finish	Interface
901-	**19-**	**1-**	**12-**	**1-**	**B-**	**1**
XXX	XX	X	XX	X	X	X
901 902 903 904 905 906 907 908 909 910	19 21 23 27 29 31 33 35 37.5 40	1= Elliptical Fin 2= Pin Fin	12 = 11.6 15 = 14.6 18 = 17.6 21 = 20.6 23 = 22.6 28 = 27.6 33 = 32.6	1 = .9-2.1 2 = 2.2-3.4	B = BLK ANO	0 = None 1 = T725

Refer to Page 33 for
Installation Instructions

PIN FIN & ELLIPTICAL FIN HEAT SINK

900 SERIES



Wakefield-Vette's heat sink assembles onto chip set using the space that is between the PCB and the substrate of the solder balls. The solder balls provide a minimal gap of .5mm to .7mm. Attachment feature is below a .4mm thickness. The clipping system will not interfere or damage chip. Contact area is the edge of chip.



ASSEMBLY INSTRUCTIONS:



Step 1

Hook the clip under one side of the BGA chip set.



Step 2

Rotate assembly down until opposite side clip engages substrate edge of BGA chip set.



Step 3

Make sure the sop rods are clearing from edges of BGA chip set.



Step 4

Press firmly down to make sure clips fully engage edges of chip set. Heat Sink should not move around easily.

RANDOM VIBRATION TEST
Frequency: 5 Hz to 500 Hz
Acceleration: 3.13 grms
P.S.D: 0.01 g2/HZ (5 Hz)
0.02 g2/HZ (20 Hz to 500 Hz)
Test Axis: X, Y, Z axis
Test Time: 10 mins (Each axis)
Total Test Time: 30 mins

SHOCK TEST SPECIFICATION:
Wave Form: Half sine wave
Acceleration: 50 g
Duration Time: 11 ms
No. of Shock: Each axis 3 times
Shock Direction: ±X, ±Y, ±Z axis
Reliability & Communication Testing Instruments

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

CERAMIC HEAT SINK FOR TO DEVICES W/ omniKlip

omniKlip™

CE-OMNI-38 HEAT SINK

RoHS

Wakefield-Vette introduces heat sinks made from alumina and aluminum nitride for thermal management of high-power/ voltage electronics, photovoltaic, LED, power resistors and other applications. While electrically insulating and thermally conducting, the ceramic heat sink is an effective combination for the circuit board and heat sink reliability of cooling thermally sensitive components and circuits. The power chip dies can be directly bonded onto ceramic heat sink as a module substrate to eliminate the thermal barriers to quickly dissipate the generated heat. These heat sinks extend component life and enhance performance.

FEATURES

- An innovative ceramic (Patent Pending) heat sink with unique design combines the tin plated solderable integral omniKlip spring with a molded aluminum oxide (Al_2O_3) or aluminum nitride (AlN) heat sink body to be mountable onto the PCB directly with no other fasteners needed. Unlike any others, this type of heat sink provides ease of assembly and an all-in-one solution (one part does all). It can be used with different package devices, such as TO-220, TO-247, TO-264 and TO-218 package, etc. series power devices with either natural or forced convention cooling.

WkV Part Number	Description	Package Cooled	Attachment Method	Length	Width	Height Off Base (Fin Height)	Thermal Resistance @ Forced Air Flow	Thermal Resistance @ Natural
CE-OMNI-38	Ceramic Heat Sink for TO Devices w/omniKlip	TO-220, TO-247	Solderable Feet	38.4mm	34mm	9.2mm	3.8°C/W @ 200 LFM	7.0°C/W @ 200 LFM

Material: 95% Al_2O_3, Surface Area: 11,408mm², Weight: 22 g
RoHS Compliant







Common Ceramic Heat sinks are a rectangular or square shape ceramic as commonly seen in an extrusion heat sink that provides the most common use in cooling. It can be used as Chip-on-heat-sink (on the metalized surface) and makes it possible to achieve an extremely compact design for the entire cooling system. Using ceramic as the material for a heat sink ensures outstanding thermal conductivity and electrical insulation; the closer it is used to a source of heat, the greater the cooling advantage it offers.





Material: 95% Al_2O_3, Surface Area: 5,979mm², Weight: 15 g

Additional Configurations & Custom Ceramic Heat Sinks

Contact Wakefield-Vette for more information or visit www.wakefield-vette.com

WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

WAVE SERIES HEAT SINK WITH INTEGRATED CLIP ASSEMBLY



WAVE SERIES™

WAVE SERIES BGA HEAT SINKS

RoHS

The Wakefield-Vette **Wave Series Heat Sink Series** are a superior choice for cooling BGA applications in which limited height/footprint while achieving maximum surface area. The Wave Series Heat Sinks include a unique clipping mechanism that allows for superior heat transfer while securing the heat sink to the BGA itself. The clipping mechanism allows for easy installation in high production assembly.

FEATURES AND BENEFITS

- Approximately 12% better thermal performance than traditional footprint heat sinks.
- Height- A low profile design allows for more surface area in a height restricted application.
- Clipping mechanism included with heat sink.
- Surface Area - Fin array allows for more surface area for forced convection.
- Easily customizable.
- Easily compatible with major BGA device manufacturers components such as: Motorola, Freescale, TI, Intel, etc.

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-23-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	23	23	40	12.5	6055.1	10.5	6.76
WAVE-23-165	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	23	23	46.5	16.5	7634.6	14.5	5.08
WAVE-26-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	26	26	52.9	12	8305.2	10	5.21
WAVE-29-127	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	29	29	61.4	12.7	11810.5	10.7	4.08
WAVE-32-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	32	32	50.2	12	10957.5	10	4.64
WAVE-34-21	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	34	34	70	21	21268.4	19	2.19
WAVE-35-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	62	12	15180.8	10	3.83
WAVE-35-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	63.3	12.5	15792.6	10.5	3.63
WAVE-35-15	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	58.1	15	15612.7	13	3.15
WAVE-35-21	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	74.6	21	21721.8	19	2.11
WAVE-366-175	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	36.6	36.6	63.6	17.5	18637.8	15.5	2.55
WAVE-40-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	40	40	66.9	12	17689.4	10	3.36
WAVE-40-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	40	40	68.3	12.5	18410.1	10.5	3.16
WAVE-425-117	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	42.5	42.5	67.4	11.7	21668.3	9.3	3.40
WAVE-45-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	45	45	72	12	22303.7	10	2.96

Material Specifications: Heat Sink: Aluminum Alloy 6063-T5 with black anodized finish. Spring Clip: 304 Stainless Steel, 1.2mm [0.47"] DIA
RoHS Compliant

BGA HEAT SINKS WAVE 2X SERIES

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-23-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	23	23	40	12.5	6055.1	10.5	6.76
WAVE-23-165	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	23	23	46.5	16.5	7634.6	14.5	5.08

WAVE-23-125



MECHANICAL DIMENSIONS



WAVE-23-165

MECHANICAL DIMENSIONS



Wave 2X



WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

WAVE SERIES HEAT SINK WITH INTEGRATED CLIP ASSEMBLY

WAVE 2X SERIES BGA HEAT SINKS

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-26-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	26	26	52.9	12	8305.2	10	5.21
WAVE-29-127	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	29	29	61.4	12.7	11810.5	10.7	4.08

WAVE-26-12



MECHANICAL DIMENSIONS



WAVE-29-127



MECHANICAL DIMENSIONS





BGA HEAT SINKS WAVE 3X SERIES

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-32-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	32	32	50.2	12	10957.5	10	4.64
WAVE-34-21	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	34	34	70	21	21268.4	19	2.19

WAVE-32-12



MECHANICAL DIMENSIONS



WAVE-34-21

MECHANICAL DIMENSIONS





WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

WAVE SERIES HEAT SINK WITH INTEGRATED CLIP ASSEMBLY

WAVE 3X SERIES BGA HEAT SINKS

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-35-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	62	12	15180.8	10	3.83
WAVE-35-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	63.3	12.5	15792.6	10.5	3.63

WAVE-35-12



MECHANICAL DIMENSIONS



WAVE-35-125

MECHANICAL DIMENSIONS





BGA HEAT SINKS WAVE 3X SERIES

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-35-15	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	58.1	15	15612.7	13	3.15
WAVE-35-21	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	35	35	74.6	21	21721.8	19	2.11
WAVE-366-175	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	36.6	36.6	63.6	17.5	18637.8	15.5	2.55

WAVE-35-15

MECHANICAL DIMENSIONS



WAVE-35-21



MECHANICAL DIMENSIONS



WAVE-365-175

MECHANICAL DIMENSIONS





WAKEFIELDTHERMAL

INTEGRATED CIRCUIT
COOLING HEAT SINKS

WAVE SERIES HEAT SINK WITH INTEGRATED CLIP ASSEMBLY

WAVE 4X SERIES BGA HEAT SINKS

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-40-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	40	40	66.9	12	17689.4	10	3.36
WAVE-40-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	40	40	68.3	12.5	18410.1	10.5	3.16
WAVE-425-117	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	42.5	42.5	67.4	11.7	21668.3	9.3	3.40
WAVE-45-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	45	45	72	12	22303.7	10	2.96

WAVE-40-12

MECHANICAL DIMENSIONS



WAVE-40-125

MECHANICAL DIMENSIONS



Wave 4X



BGA HEAT SINKS WAVE 4X SERIES

			Mechanical Dimensions (mm)						
WkV Part Number	Description	Attachment Method	Length	Width	Fin Width	Height	Surface Area (sq mm)	Height Off Base (Fin Height)	Thermal Resistance - Forced Conv. @ 200 LFM
WAVE-40-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	40	40	66.9	12	17689.4	10	3.36
WAVE-40-125	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	40	40	68.3	12.5	18410.1	10.5	3.16
WAVE-425-117	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	42.5	42.5	67.4	11.7	21668.3	9.3	3.40
WAVE-45-12	Wave Heat Sink BGA Chipset Aluminum Top Mount	Spring-Anchor	45	45	72	12	22303.7	10	2.96

WAVE-425-117

MECHANICAL DIMENSIONS



WAVE-45-12

MECHANICAL DIMENSIONS



Wave 4X