

402B



SUPER DUSTER™ 152

Super Duster 152 is a compressed air duster can made with 100% HFC152A gas. The powerful blast of 402B spray duster blows away microscopic dust, lint, and foreign particles.

We recommended 402B dust-off spray for use in the home or office over 402A, which is specifically designed for electronics.

Features & Benefits

100% HFC 152A gas

Economical

Ozone safe

Non-VOC

Non-flammable aerosol*

Zero residue

High flow delivery system

Filtered to 0.2 microns

Suitable for use in food facilities as a Non-Food Chemical – Canadian and NFS recognition letters available on request

Storage and Handling

Store between -20 and 27 °C in a dry area, away from sunlight. Store in well-ventilated places (see SDS).

Properties

| | |
|--------------------------------|--------------------|
| Color | Colorless |
| Odor | Slight, ether-like |
| Purity | ≥99.9 % |
| Moisture (maximum) | ≤10 ppm |
| Non-volatile Residue (maximum) | ≤0.01 % |
| Boiling Point | -25 °C |
| Flash Point | -50 °C |
| Ozone Depleting Potential | 0.00 |
| Shelf Life | 5 y |

Disclaimer: This information is believed to be accurate. It is intended for professional end-users who have the skills required to evaluate and use the data properly. M.G. Chemicals Ltd. does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

MG Chemicals 1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6 ISO 9001:2015 Quality Management System SAI Global File: 004008
support@mgchemicals.com North America +(1) 800-340-0772 International +(1) 905-331-1396 Europe +44 1663 362888 24 September 2025 / Ver. 2.0



Available Packaging

| Part # | Packaging | Net Vol. | Net Wt. |
|-----------|-----------|----------|---------|
| 402B-285G | Aerosol | 313 mL | 285 g |
| 402B-400G | Aerosol | 439 mL | 400 g |

Application Instructions

Read the product SDS for more detailed instructions before using this product.

To remove safety tab:

1. Firmly hold the head of the nozzle and trigger in place.
2. Pull tab forward on top of nozzle until it snaps off.

To clean surfaces:

1. Power off electrical or electronic equipment.
2. Spray directly on dusty component using bursts of spray. Clean contaminations from top to bottom to avoid redeposit of dust on clean areas.
3. Use extension tube to direct the spray in hard to reach corners.