

The drawing shows a side view of a cable assembly. It consists of a central cable with two conductors, terminated at both ends with connectors. The left connector is labeled 'A' and the right connector is labeled 'B'. A dimension line labeled 'L' indicates the length of the cable between the two connectors. Below the drawing is a table with the following content:




TABLE		
FG PART #	L	TITLE
2291162112	150±5	CP3.3 22AWG F-F 150 mm
2291162115	500±5	CP3.3 22AWG F-F 500 mm

NOTE:
1. CRIMPING TO BE DONE AS PER MOLEX STANDARDS.
2. THE PRODUCT SPECIFICATION RELIES ON THE TERMINALS & WIRE SPEC.

NOTE:

1. CRIMPING TO BE DONE AS PER MOLEX STANDARDS.
2. THE PRODUCT SPECIFICATION RELIES ON THE TERMINALS & WIRE SPEC.

REVISION HISTORY							
INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							
CURRENT REV DESC: EC NO: 816292 DRWN: BHARAB5 CHK'D: NAVEEB6 APPR: RPAI01 INITIAL REVISION: DRWN: BHARAB5 APPR: RPAI01			molex				
			SEE TABLE				
			PRODUCT CUSTOMER DRAWING				
			DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
			2291162112		PSD	000	A
THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER		SHEET NUMBER
		A3-SIZE	229116	SEE TABLE	GENERAL MARKET		1 OF 1

DETAIL	DESCRIPTION	DETAIL	DESCRIPTION
	Continues Taping		PVC sleeve or Silicon sleeve
	HST		T Dimension
	Woven Braid		Convuluted Tube
	Spot Taping		Customer Specific requirements

[illegible]