

# Solid State Relays

## Industrial, 1-Phase ZS, Standard Range

### Types RA 24.. .. 06/RA 48.. .. 12



- AC Solid State Relay
- Zero switching
- Direct copper bonding technology
- Rated operational current: 25, 50 and 90 AACrms
- Blocking voltage: Up to 1200 V<sub>p</sub>
- Rated operational voltage: Up to 480 VACrms
- 2 input ranges: 3 to 32 VDC and 90 to 280 VAC/DC
- Isolation: OPTO (input-output) 4000 VACrms



#### Product Description

The zero switching relay with antiparallel thyristor output is the most widely used industrial SSR due to its multiple application possibilities. The relay can be used for resistive, inductive and capacitive loads. The zero switching relay switches ON when the sine curve just crosses zero and switches OFF when the current crosses zero.

#### Ordering Key

**RA 24 25 -D 06**

Solid State Relay \_\_\_\_\_  
 Switching mode \_\_\_\_\_  
 Rated operational voltage \_\_\_\_\_  
 Rated operational current \_\_\_\_\_  
 Control voltage \_\_\_\_\_  
 Blocking voltage \_\_\_\_\_

#### Type Selection

Switching mode	Rated operational voltage	Rated operational current	Control voltage	Blocking voltage
A: Zero switching	24: 230 VACrms 48: 480 VACrms	25: 25 AACrms 50: 50 AACrms 90: 90 AACrms	D: 3 to 32 VDC HA: 90 to 280 VAC/DC	06: 650 V <sub>p</sub> 12: 1200 V <sub>p</sub>

#### Selection Guide

Rated operational voltage	Blocking voltage	Control voltage	Rated operational current 25 AACrms	50 AACrms	90 AACrms
230 VACrms	650 V <sub>p</sub>	3 to 32 VDC 90 to 280 VAC/DC	<b>RA 2425 -D 06</b>	<b>RA 2450 -D 06</b>	<b>RA 2450 HA 06</b>
480 VACrms	1200 V <sub>p</sub>	3 to 32 VDC 90 to 280 VAC/DC	<b>RA 4825 -D 12</b>	<b>RA 4850 -D 12</b>	<b>RA 4890 -D 12</b>

## General Specifications

	RA 24... 06	RA 48... 12
Operational voltage range	24 to 280 VACrms	42 to 530 VACrms
Blocking voltage	$\geq 650 V_p$	$\geq 1200 V_p$
Zero voltage turn-on	$\leq 20 V$	$\leq 40 V$
Operational frequency range	45 to 65 Hz	45 to 65 Hz
Power factor	$\geq 0.5 @ 230 VACrms$	$\geq 0.5 @ 480 VACrms$
Approvals	CE, cURus, CSA, EAC	CE, cURus, CSA, EAC

## Output Specifications

	RA..25 ...	RA ..50 ...	RA ..90 ...
Rated operational current AC 51 AC 53a	25 Arms 5 Arms	50 Arms 15 Arms	90 Arms 20 Arms
Minimum operational current	150 mArms	250 mArms	400 mArms
Rep. overload current t=1 s	$\leq 55$ Arms	$\leq 125$ Arms	$\leq 150$ Arms
Non-rep. surge current t=10 ms	325 A <sub>p</sub>	600 A <sub>p</sub>	1150 A <sub>p</sub>
Off-state leakage current @ rated voltage and frequency	$\leq 3$ mArms	$\leq 3$ mArms	$\leq 3$ mArms
I <sup>2</sup> t for fusing t=10 ms	$\leq 525 A^2s$	$\leq 1800 A^2s$	$\leq 6600 A^2s$
On-state voltage drop @ rated current	$\leq 1.6$ Vrms	$\leq 1.6$ Vrms	$\leq 1.6$ Vrms
Critical dV/dt commuting	$\geq 500$ V/ $\mu$ s	$\geq 500$ V/ $\mu$ s	$\geq 500$ V/ $\mu$ s
Critical dV/dt off-state	$\geq 500$ V/ $\mu$ s	$\geq 500$ V/ $\mu$ s	$\geq 500$ V/ $\mu$ s

## Input Specifications

	RA .... -D ..	RA .... HA ..
Control voltage range	3 to 32 VDC	90 to 280 VAC/DC
Pick-up voltage	$\geq 3$ VDC	$\leq 90$ VAC/DC
Drop-out voltage	$\leq 1$ VDC	$\geq 10$ VAC/DC
Reverse voltage	$\leq 32$ VDC	
Input impedance	1.5 k $\Omega$	44 k $\Omega$
Response time pick-up	$\leq 1/2$ cycle	$\leq 1$ cycle
Control pulse width	$\geq 0.5$ ms	$\geq 0.5$ ms
Response time drop-out	$\leq 1/2$ cycle	$\leq 1/2$ cycle


## Isolation

Rated isolation voltage Input to output	$\geq 4000$ VACrms
Rated isolation voltage Output to case	$\geq 4000$ VACrms
Insulation resistance Input to output	$\geq 10^{10}$ $\Omega$
Insulation resistance Output to case	$\geq 10^{10}$ $\Omega$
Insulation capacitance Input to output	$\leq 8$ pF
Insulation capacitance Output to case	$\leq 100$ pF


## Housing Specifications

Weight	Approx. 110 g
Housing material	Noryl GFN 1, black
Base plate	25, 50 A 90 A
	Aluminium, nickel-plated Copper, nickel-plated
Potting compound	Polyurethane
Relay	
Mounting screws	M5
Mounting torque	$\leq 1.5$ Nm
Control terminal	
Mounting screws	M3 x 6
Mounting torque	$\leq 0.5$ Nm
Power terminal	
Mounting screws	M5 x 6
Mounting torque	$\leq 2.4$ Nm

## Functional Diagram




## Dimensions



All dimensions in mm

## Connection Diagram



## Heatsink Dimensions (load current versus ambient temperature)

RA ..25 .. ..

Load current [A]	Thermal resistance [°C/W]						Power dissipation [W]
	2	1.7	1.4	1	0.71	0.40	
25	32						
22.5	27						
20	23						
17.5	20						
15	16						
12.5	13						
10	10						
7.5	7						
5	5						
2.5	2						

Ambient temp. [°C]

RA ..50 .. ..

Load current [A]	Thermal resistance [°C/W]						Power dissipation [W]
	0.92	0.76	0.60	0.45	0.29	-	
50	63						
45	55						
40	47						
35	40						
30	33						
25	26						
20	20						
15	15						
10	9						
5	4						


Ambient temp. [°C]

RA ..90 .. ..

Load current [A]	Thermal resistance [°C/W]						Power dissipation [W]
	0.63	0.53	0.42	0.32	-	-	
90	97						
80	84						
70	71						
60	59						
50	47						
40	36						
30	26						
20	17						
10	8						

Ambient temp. [°C]

## Heatsink Selection



Heatsink Range Overview:

[https://www.gavazziautomation.com/images/PIM/DATASHEET/ENG/SSR\\_Accessories.pdf](https://www.gavazziautomation.com/images/PIM/DATASHEET/ENG/SSR_Accessories.pdf)

Heatsink Selector Tool:

[https://www.gavazziautomation.com/nsc/HQ/EN/heat\\_sink\\_selector\\_tool](https://www.gavazziautomation.com/nsc/HQ/EN/heat_sink_selector_tool)

## Ordering Key

**RHS..**

- Heatsinks and fans
- 5.40°C/W to 0.12°C/W thermal resistance
- DIN, panel or thru wall mounting
- Single or multiple SSR mounting

## Applications


This relay is designed for use in applications in which it is exposed to high surge conditions. Care must be taken to ensure proper heatsinking when the relay is to be used at high sustained currents. Adequate electrical connection between relay terminals and cable must be ensured.

### Thermal characteristics

The thermal design of Solid State Relays is very impor-

tant. It is essential that the user makes sure that cooling is adequate and that the maximum junction temperature of the relay is not exceeded.

If the heatsink is placed in a small closed room, control panel or the like, the power dissipation can cause the ambient temperature to rise. The heatsink is to be calculated on the basis of the ambient temperature and the increase in temperature.



Thermal resistance:  
 $R_{th\ j-c}$  = junction to case

$R_{th\ c-s}$  = case to heatsink  
 $R_{th\ s-a}$  = heatsink to ambient

Direct bonding  
In the design of the output power semiconductor direct bonding of the copper layer and the ceramic substrate has been applied. This is to ensure uninhibited heat transfer and high thermal fatigue strength.


The relay has been designed for applications requiring large numbers of load cycles.

$$I_{rms} = \sqrt{\frac{I_{ON}^2 \times t_{ON}}{t_{ON} + t_{OFF}}}$$

Ex: RA 24 50 -D 06:  
Load current = 45 A  
 $t_{ON} = 30$  s  
 $t_{OFF} = 15$  s

$$I_{rms} = \sqrt{\frac{45^2 \times 30}{30 + 15}}$$

The rms current will be 36.7 A.



## Thermal Specifications

	RA ..25 .. ..	RA ..50 .. ..	RA ..90 .. ..
Operating temperature	-20° to +70°C (-4° to +158°F)	-20° to +70°C (-4° to +158°F)	-20° to +70°C (-4° to +158°F)
Storage temperature	-40° to +100°C (-40° to +212°F)	-40° to +100°C (-40° to +212°F)	-40° to +100°C (-40° to +212°F)
Junction temperature	≤ 125°C (≤ 257°F)	≤ 125°C (≤ 257°F)	≤ 125°C (≤ 257°F)
$R_{th}$ junction to case	≤ 1.25°C/W	≤ 0.65°C/W	≤ 0.3°C/W
$R_{th}$ junction to ambient	≤ 12°C/W	≤ 12°C/W	≤ 12°C/W

## Environmental Specifications

Pollution degree	2 (non-conductive pollution with possibilities of condensation)
EU RoHS compliant	Yes
China RoHS compliant	Refer to Environmental Information (Page 6)

## Environmental Information

The declaration in this section is prepared in compliance with People's Republic of China Electronic Industry Standard SJ/T11364-2014: Marking for the Restricted Use of Hazardous Substances in Electronic and Electrical Products.

Part Name	Toxic or Harardous Substances and Elements					
	Lead (Pb)	Mercury (Hg)	Cadmium (Cd)	Hexavalent Chromium (Cr(VI))	Polybrominated biphenyls (PBB)	Polybrominated diphenyl ethers (PBDE)
Power Unit Assembly	x	o	o	o	o	o
o: Indicates that said hazardous substance contained in homogeneous materials for this part are below the limit requirement of GB/T 26572.						
x: Indicates that said hazardous substance contained in one of the homogeneous materials used for this part is above the limit requirement of GB/T 26572.						

## 环境特性

这份申明根据中华人民共和国电子工业标准  
SJ/T11364-2014 : 标注在电子电气产品中限定使用的有害物质

零件名称	有毒或有害物质与元素					
	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴化联苯 (PBB)	多溴联苯醚 (PBDE)
功率单元	x	o	o	o	o	o
o:此零件所有材料中含有的该有害物低于GB/T 26572的限定。						
x:此零件某种材料中含有的该有害物高于GB/T 26572的限定。						



## Accessories



- Graphite thermal pad with adhesive on one side
- Type KK071CUT
- Dimensions: 35 x 43 x 0.25 mm
- Packing quantity: 50 pcs.

All accessories can be ordered pre-assembled with Solid State Relays.  
Other accessories include DIN rail adaptors and varistors

For further information refer to Accessories datasheets at:  
[https://www.gavazziautomation.com/images/PIM/DATASHEET/ENG/SSR\\_Accessories.pdf](https://www.gavazziautomation.com/images/PIM/DATASHEET/ENG/SSR_Accessories.pdf)