



# Stamp-Pico Mate

SKU:K051



## Description

**Stamp-Pico Mate** is an accessory kit for the Stamp-Pico minimum core board. The kit includes a Stamp-Pico along with female headers, male headers, a HY2.0-4P female socket and other practical accessories, allowing you to integrate the Stamp-Pico into your circuit quickly and easily.

Stamp-Pico is a cost-effective **Wi-Fi minimum core board** powered by the **ESP32** SoC with two low-power **Xtensa® 32-bit LX** microprocessors running at up to 240 MHz. Thanks to its compact size and outstanding performance, Stamp-Pico can be effortlessly embedded into your application circuit to build IoT solutions.

## Tutorial



### UIFlow

This tutorial shows you how to control the Stamp-Pico with the UIFlow graphical programming platform.



### UiFlow2

This tutorial shows you how to control the Stamp-Pico with the UiFlow2 graphical programming platform.



### Arduino IDE

This tutorial shows you how to program the Stamp-Pico with the Arduino IDE.

## Features

- ESP32-PICO-D4 (2.4 GHz Wi-Fi)
- Multiple I/O breakouts supporting various mounting methods (SMT, DIP, flying leads)
- Integrated programmable RGB LED and button
- ESP32 minimum system board
- High-temperature plastic armor for better protection of the 3D antenna and components
- On-board 5 V → 3.3 V DC/DC circuit, 12 × GPIO, 1 × programmable RGB LED, 1 × button
- Professionally tuned RF circuit for stable and reliable wireless communication
- Development Platform
  - UIFlow1
  - UIFlow2
  - Arduino IDE
  - ESP-IDF
  - PlatformIO

## Includes

- 1 × Stamp-Pico
- 1 × 2.54-9P Male Header
- 1 × 2.54-9P Female Header
- 1 × 2.54-6P Male Header

- 1 × 2.54-6P Female Header
- 1 × High-temperature Sticker
- 1 × HY2.0-4P Female Socket (90°)
- 1 × Hex Key L-Shape 1.5 mm (For M2 Screw)

## Applications

---

- Smart home
- Wearable devices
- Medical equipment

## Specifications


---

Specification	Parameter
SoC	ESP32-PICO-D4@dual-core processor, 240MHz
Package	LGA48 (7×7mm)
Flash	4MB
Wi-Fi	2.4 GHz Wi-Fi
DMIPS	600
SRAM	520KB
Input Voltage	5V@500mA
Power Consumption	Normal standby: 5 V@29 mA / Wi-Fi STA mode: 5 V@60 mA / Classic Bluetooth TX: 5 V@84 mA / DeepSleep: 5 V@0.35 mA
Wireless Range	AP mode: 16 m / BLE mode: 110 m / Classic Bluetooth mode: 90 m
HMI	1 × Programmable physical button, 1 × Programmable RGB LED (SK6812)
Antenna Type	2.4 G 3D antenna
Wi-Fi	802.11 b/g/n (up to 150 Mbps with 802.11 n), spectrum range: 2.4 GHz ~ 2.5 GHz
Peripheral Interface	ADC, DAC, Touch Sensor, SD/SDIO/MMC Host Controller, SPI, SDIO/SPI Slave Controller, EMAC, Motor PWM, LED
IO (12 pins)	PWM, UART, I2C, I2S, IR Remote Controller, GPIO, PCNT
IO (12 pins)	G0, G1, G3, G26, G36, G18, G19, G21, G22, G25, G32, G33
IO Pitch	2.54 mm
Operating Temp.	0 ~ 60 °C
Mounting Screws	M2 × 4 Countersunk Hex Socket Machine Screws
Product Size	24.0 × 18.0 × 4.6 mm
Product Weight	2.6 g
Package Size	138.0 x 93.0 x 7.0mm
Gross Weight	7.6 g


# Learn

## Download Program


Stamp-Pico adopts an ultra-simplified circuit design and therefore does not include an onboard download circuit. To burn firmware, connect a USB-TTL downloader as shown below.



## Reflow Soldering Temperature Curve for the Shell




## Schematics




## PinMap

### SK6812, Button


ESP32-PICO-D4	G27	G39
SK6812	DI	/
Button	/	SW



## Model Size



UNIT: mm



UNIT : mm

PCB

- Stamp-Pico PCB Doc
- LCSC EDA Stamp-Pico Footprint

## Datasheets

- o [ESP32-PICO](#)

## Softwares

### Arduino

- o [Stamp-Pico Arduino Quick Start](#)
- o [Stamp-Pico Button Example](#)
- o [Stamp-Pico IO Example](#)
- o [Stamp-Pico LED Example](#)

### UiFlow1

- o [Stamp-Pico UiFlow1 Quick Start](#)

### UiFlow2

- o [Stamp-Pico UiFlow2 Quick Start](#)

### USB Driver

Before flashing, you need to connect a [USB-TTL downloader board](#) to the Stamp-Pico according to the silkscreen. Install the corresponding driver for the downloader on your PC.



The easiest way is to purchase the Stamp-Pico kit with downloader. The cable order matches STAMP-PICO, allowing direct plug-in flashing without wiring. M5 currently provides downloaders with two driver chips: CP210X (for **CP2104**) / CH9102 (for **CH9102**). After extracting the package, choose the installer matching your OS bitness. (If you are unsure which USB chip your device uses, install both drivers.)

Driver Name	Applicable Chip	Download Link
CP210x_VCP_Windows	CP2104	<a href="#">Download</a>
CP210x_VCP_MacOS	CP2104	<a href="#">Download</a>
CP210x_VCP_Linux	CP2104	<a href="#">Download</a>
CH9102_VCP_SER_Windows	CH9102	<a href="#">Download</a>
CH9102_VCP_SER_MacOS v1.7	CH9102	<a href="#">Download</a>

## Video

[STAMP\\_PICO\\_VIDEO\\_01.mp4](#)

## Product Comparison

COMPARISON	STAMP PICO	STAMP C3U	STAMP C3	STAMP S3
PICTURE				
Number of IO ports	12	14	13	23
FLASH	4M	4M	4M	8M
Serial IC	/	USB CDC	CH9102F	USB CDC
Download method		 	 	
Pin spacing	2.54mm	2.54mm	2.54mm	2.54mm/1.27mm
LCD interface				
CPU frequency	240MHz	160 MHz	160 MHz	240MHz
Size	24 × 18 × 4.6mm	34 × 20 × 4.6mm	34 × 20 × 4.6mm	26 × 18 × 4.6mm