BOURNS®

PST10 Series

10 mm Incremental Potentiometers

*RoHS COMPLIANT

Features

- Compact design
- High reliability
- Mounting hole pin
- RoHS compliant*

Applications

- Industrial controls
- Robotics
- Factory automation equipment
- Motion control systems
- Human-machine interfaces (HMI)
- Commercial equipment
- Position feedback applications

Sustainability

- Small size reduces material use
- High pallet density for lower CO_2
- Eco-logistics-friendly packing
- Recyclable ESD-safe packaging
- High efficiency, low power loss

Product Overview

Bourns® PST10 Series combines a compact hollow-shaft design with non-contact sensing technology to deliver accurate position feedback and long-term reliability. By eliminating mechanical wear associated with conventional potentiometers, this series provides stable analog output and maintenance-free operation throughout its service life. The hollow-shaft configuration simplifies mechanical integration, while the compact package supports space-constrained designs without compromising performance. Designed to help improve system durability and reduce maintenance requirements, the PST10 Series offers consistent electrical performance and dependable operation over an extended operating life.

Derating Curve of Rated Dissipation



Electrical Characteristics

Contact Rating	10 mA @ 5 VDC
Insulation Resistance	100 MΩ min. @ 200 VDC
Dielectric Strength - Sea Level	50 VAC 1 min.
Linear Taper B	Linear
Rated Power	0.15 W
Rated Voltage	150 VAC – 100 VDC
Standard Resistance Range	1 KΩ to 5 MΩ
Total Resistance Tolerance	
1 KΩ to 1 MΩ	±20 %
≥1 MΩ to 5 MΩ	±30 %
Electrical Travel	200 ° ±20 °

Environmental Characteristics

Operating Temperature	-10 °C to +70 °C
Storage Temperature	-25 °C to +80 °C
Soldering Condition	
Dip Soldering	260 °C ±5 °C for 3 s
Manual Soldering	350 °C ±5 °C for 3 s
IP Rating	IP 40

Mechanical Characteristics

Mechanical Angle	235 ° ±10 °
Rotational Torque	10 to 100 gf/cm
Rotational Speed	60 ° / sec.
Rotation Stopper Strength	0.5 Kgf/cm
Push – Pull Strength of Shaft	1.0 Kgf/cm
Shaft Play in Axial Direction	0.5 K gf max.
Rotational Life	10,000 cycles

Product Characteristics

Weight	0.6 grams

Contact Information

www.bourns.com	Phone	Email
Asia-Pacific	+886-2 2562-4117	asiacus@bourns.com
Europe	+36 88 885 877	eurocus@bourns.com
Mexico	+52 614 478 0400	mexicus@bourns.com
The Americas	+1-951 781-5500	americus@bourns.com

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

BOURNS®

PST10 Series

10 mm Incremental Potentiometers

*RoHS COMPLIANT

Product Dimensions

PST10H Horizontal PC Board Mounting Hole Pin



Mounting Hole Details

PST10H



Hole Style

PST10H

Style K1	Style J	Style S
		

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

BOURNS®

PST10 Series

10 mm Incremental Potentiometers

*RoHS COMPLIANT

Product Dimensions

PST10V Vertical PC Board Mounting Hole Pin



DIMENSIONS: MM (INCHES)

Mounting Hole Details

PST10V



DIMENSIONS: MM (INCHES)

Hole Style

PST10V

Style H	Style J	Style S
		

Code H	L0	L2	L5
	2.0 +0.02/-0 (.079 +.001/-0)	2.02 +0.02/-0 (.080 +.001/-0)	2.05 +0.02/-0 (.081 +.001/-0)

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

BOURNS®

PST10 Series

10 mm Incremental Potentiometers

*RoHS COMPLIANT

How to Order

PST10 2 - 1 01 HL0 - N 503

Model Series
PST10

10 mm Incremental Potentiometer
- 1 = Horizontal
- 2 = Vertical

Detent Option
- 1 = No Detents

Key Shaft
- 01 = Hole

Shaft Style
- HL0 = 2.00 Hexagon Key Shaft (vertical model only)
- HL2 = 2.02 Hexagon Key Shaft (vertical model only)
- HL5 = 2.05 Hexagon Key Shaft (vertical model only)
- J = 2.0 Arrow Key Shaft
- K1 = 2.4 Arrow Key Shaft (horizontal model only)
- S = 2.0 Cross Key Shaft

Switch Configuration
- N = No Switch

Resistance
- Resistance Code

Resistance (Ohms)	Resistance Code
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
50,000	503
100,000	104
200,000	204
500,000	504
1,000,000	105

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Legal Disclaimer Notice

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain "typical" applications are based on Bourns' knowledge of typical requirements in generic applications. Bourns assumes that "typical" applications include failsafe/backup features to address critical risks to users and are designed to allow rework of Bourns® product to avoid scrap of a device solely due to malfunctioning Bourns® product. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Thus, users should always verify the actual performance of the Bourns® product in their specific devices and applications and make their own independent judgments regarding the suitability of Bourns® product and the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real-world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification even if such industry standard or qualification is a "state of art". Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage, such as without limitation nuclear, life-critical medical and certain automotive and aviation applications. Except as set forth in the bullet points below or unless expressly and specifically approved in writing on a case-by-case basis by an authorized Bourns' representative, use of any Bourns® products in such unauthorized high-risk applications is at the user's sole risk.

- Bourns considers implantable/invasive devices and devices/procedures designed as life-supporting or life-sustaining by the U.S. Food and Drug Administration or equivalent organizations outside of the United States as "life-critical" medical applications. Bourns expressly identifies those Bourns® standard products that are suitable for use in typical medical applications that are not life-critical in its publication entitled "Bourns Medical Grade Component Guide."

- Bourns expressly identifies those Bourns® standard products that are suitable for use in typical automotive applications associated with any Automotive Safety Integrity Level (ASIL) in its publication entitled "Bourns Automotive Grade Component Guide." Bourns' designation of Bourns® product as compliant with the AEC-Q standard does not by itself mean that Bourns has approved such product for use in an automotive application.

- Bourns expressly identifies Bourns® standard products that are suitable for use in the typical aviation applications/systems requiring System Design Assurance Level (RTCA DO-254 DAL) of C, D or E in its publication entitled "Bourns Civilian Aerospace/Aviation Grade Component Guide." Bourns does not test its products for compliance with United States Federal Aviation Administration standards or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aviation applications. Use of Bourns® standard components in aviation applications associated with RTCA DO-254 DAL A or B without proper approval noted above shall be at the user's sole risk.

- Bourns will review and authorize on a case-by-case basis the use of Bourns® standard products which are at least AEC-Q compliant in space-related civil applications (rockets, satellites) with a negotiated cross-waiver and indemnity agreement.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Use of Bourns® products or Bourns' technology in military/defense applications must be reviewed with Bourns for compliance with applicable export control laws and embargoes. Users shall not sell, transfer, export or re-export (which includes transfers within a country) any Bourns® products or technology or technical data for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology or technical data in any facility which engages in activities relating to such devices. Further, Bourns® products and Bourns' technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products and technology may not, without prior authorization from Bourns and/or the Government of a country where such product/technology is designed and/or manufactured, be resold, transferred, or re-exported (including within the same country) to any party not eligible to receive commodities, software, and technical data originating in such country.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties (those not based on parameters specified in Bourns' data sheets and/or specifications), including implied warranties of fitness for a particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:
Web Page: https://www.bourns.com/legal/disclaimers-terms-and-policies
PDF: https://www.bourns.com/docs/Legal/disclaimer.pdf

K2540 08/26R

CALIFORNIA WARNING: Can expose you to lead, a carcinogen and reproductive toxicant.
See www.P65Warnings.ca.gov