

Han-Quintax module, female



Image is for illustration purposes only. Please refer to product description.

Identification

| | |
|--------------------|---------------------|
| Category | Modules |
| Series | Han-Modular® |
| Type of module | Han-Quintax® module |
| Size of the module | Double module |

Version

| | |
|--------------------|-------------------|
| Termination method | Crimp termination |
| Gender | Female |

Technical characteristics

| | |
|-----------------------|---------------------|
| Insulation resistance | >10 ¹⁰ Ω |
| Limiting temperature | -40 ... +85 °C |
| Mating cycles | ≥500 |

Material properties

| | |
|---|------------------------|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |

Material properties

| | |
|--------------------------------------|-------------------------------------|
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Not contained |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) + A1 (2023-10) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 60664-1 IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals | DNV GL |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 2 |
| Net weight | 13.5 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140184817 |
| eCl@ss | 27440207 Adapter for industrial connectors (module/contact insert) |
| ETIM | EC002312 |
| UNSPSC 24.0 | 39121469 |