


4:1 Heat Shrink Tubing

specifications

Heat shrink with a 4:1 shrink ratio shall be used to insulate and protect oversized electrical and electronic components, cables, terminals, and connectors. This tube shall be recovered with a heat gun that provides consistent shrinking without burning or charring the outer wall of the tube. The heat shrink tube shall include an adhesive inner wall, which seals and protects components from moisture and corrosion. The heat shrink tube shall be UL Recognized and RoHS Compliant to assure quality material and to provide confidence that the product meets the application requirements.



technical information

Material:	Irradiated cross-linked polyolefin outer wall with an inner wall of specifically designed hot melt adhesive
UL recognized:	File number E342365
Flammability:	Flame retardant outer wall meets UL 224 VW-1
Color:	Black
Voltage rating:	Up to 600 volts
Application temperature:	-67°F to 257°F (-55°C to 125°C)
Shrink temperature:	248°F (120°C)
Water absorption:	1.0% MAX. per ASTM D570
Dielectric strength:	Greater than 19.7 kV/mm
Environmental compliance:	Compliant per European Directive 2002/95/EC on the Restriction of Hazardous Substances (RoHS)

key features and benefits

4 to 1 shrink ratio	Permits fewer sizes to cover a larger range of applications to provide increased mechanical protection and the ability to repair most damaged cable jackets without removing the connectors
Variety of diameters	Enable specific sizes to be chosen based on application requirements to provide a lower installed cost and the flexibility to protect different size electrical and electronic components, cables, terminals and connectors, especially oversized terminals and connectors
Convenient packaging	Available in boxes that include 4' lengths to help maintain a manageable and organized inventory
Quality material	Suitable for use in 600 V applications to comply with UL standards

applications

Heat shrink with a 4:1 shrink ratio offers an economical and simple way to provide increased mechanical protection. With high quality material, Panduit 4:1 heat shrink tubing delivers optimum reliability for the insulation, protection, harnessing, and identification of oversized electrical and electronic components, cables, terminals, and connectors. A variety of sizes

accommodate cable and termination sizes from 0.04" up to 2.0" in diameter, are suitable for indoor and outdoor applications and approved for use up to 600 volts. Ideal for the repair of damaged cable jackets, this solution speeds maintenance without the need to remove connectors, which also ensures continuity of the related systems in the physical infrastructure.

4:1 Heat Shrink Tubing

0.158" expanded diameter:	HSTT4A15-48-Q
0.315" expanded diameter:	HSTT4A31-48-Q
0.472" expanded diameter:	HSTT4A47-48-Q
0.630" expanded diameter:	HSTT4A62-48-5
0.945" expanded diameter:	HSTT4A94-48-5
1.26" expanded diameter:	HSTT4A125-48-5
2.05" expanded diameter:	HSTT4A200-48-5

Heat Gun and Accessories

Heat gun:	HSG115V-650
Shrink tube reflector for tubing up to ¾":	HSG-A1
Shrink tube reflector for tubing up to 1½":	HSG-A2
Black polyethylene storage case:	HSG-A4

4:1 Heat Shrink Tubing

sizes and dimensions

Part Number	Nominal Diameter		Min. Expanded I.D.		Max. Recovered I.D.		Nominal Recovered Wall Thickness		Length	
	In.	mm	In.	mm	In.	mm	In.	mm	Ft.	m
HSTT4A15-48-Q	.158	4.0	.158	4.0	.039	1.0	.043	1.10	4.00	1.2
HSTT4A31-48-Q	.315	8.0	.315	8.0	.079	2.0	.043	1.10	4.00	1.2
HSTT4A47-48-Q	.472	12.0	.472	12.0	.118	3.0	.055	1.40	4.00	1.2
HSTT4A62-48-5	.630	16.0	.630	16.0	.158	4.0	.070	1.80	4.00	1.2
HSTT4A94-48-5	.945	24.0	.945	24.0	.236	6.0	.088	2.25	4.00	1.2
HSTT4A125-48-5	1.260	32.0	1.260	32.0	.315	8.0	.100	2.54	4.00	1.2
HSTT4A200-48-5	2.050	52.0	2.050	52.0	.512	13.0	.100	2.54	4.00	1.2

size selection for heat shrink tubing

Generally, the largest tube that shrinks down tightly onto an object should be chosen. This allows the heat shrink tubing maximum stress relief and will yield the longest service life.

Example:

A multi-conductor cable needs to be covered with HSTT4A 4:1 heat shrink tubing. The area to be covered has a measured outside diameter of 0.500" (12.7mm). Based on expanded and recovered ID attributes, the following three part numbers are possible options.

Part Number	Expanded I.D. In. (mm)	Recovered I.D. In. (mm)
HSTT4A62-48-5	0.630 (16.0)	0.158 (4.0)
HSTT4A94-48-5	0.945 (24.0)	0.236 (6.0)
HSTT4A125-48-5	1.26 (32.0)	0.315 (8.0)

The optimal choice is HSTT4A125-48-5 since the tube will recover more than HSTT4A62-48-5 and HSTT4A94-48-5. While the HSTT4A62-48-5 and HSTT4A94-48-5 will fit over the 0.500" (12.7mm) outside diameter, the recovered I.D. is smaller than that of the HSTT4A125-48-5. In general, heat shrink should recover at least 10% – 20% to reduce stress and yield the longest service life.

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.3767.7011

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300 and reference WASP08

PANDUIT®

©2011 Panduit Corp.
ALL RIGHTS RESERVED.

WW-WASP08

11/2011