

# GPAL 400X300X1,5 SR/BK/GD - Engraving plate for outdoor use



0814034

<https://www.phoenixcontact.com/us/products/0814034>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving plate for outdoor use, Plate, silver/black, unmarked, can be labeled with: P1 ENGRAVING UNIT, ENGRAVING UNIT, mounting type: screw, rivet, text field height: 300 mm, text field width: 400 mm



## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 0814034       |
| Packing unit                         | 5 pc          |
| Minimum order quantity               | 5 pc          |
| Sales key                            | BG19          |
| Product key                          | BG2415        |
| GTIN                                 | 4017918977757 |
| Weight per piece (including packing) | 381.566 g     |
| Weight per piece (excluding packing) | 292.9 g       |
| Customs tariff number                | 76169990      |
| Country of origin                    | DE            |

# GPAL 400X300X1,5 SR/BK/GD - Engraving plate for outdoor use



0814034

<https://www.phoenixcontact.com/us/products/0814034>

## Technical data

### Product properties

|              |              |
|--------------|--------------|
| Product type | Gerätemarker |
|--------------|--------------|

### Marking

|                           |           |
|---------------------------|-----------|
| Identification technology | Engraving |
|---------------------------|-----------|

### Dimensions

|        |        |
|--------|--------|
| Width  | 400 mm |
| Length | 300 mm |

### Material specifications

|       |                      |
|-------|----------------------|
| Color | multicolored (RAL -) |
|       | black (RAL 9005)     |

### Environmental and real-life conditions

#### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
|---------------|--------------------------------|

#### Wipe resistance of inscriptions

|               |                                     |
|---------------|-------------------------------------|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
|---------------|-------------------------------------|

#### Ambient conditions

|                                                     |                                                                                 |
|-----------------------------------------------------|---------------------------------------------------------------------------------|
| Ambient temperature (operation)                     | -20 °C ... 85 °C                                                                |
| Recommended ambient temperature (storage/transport) | 23 °C                                                                           |
| Recommended humidity (storage/transport)            | 50 % (Storage in a dry and dark place in the original packaging is recommended) |

### Mounting

|               |              |
|---------------|--------------|
| Mounting type | screw, rivet |
|---------------|--------------|

# GPAL 400X300X1,5 SR/BK/GD - Engraving plate for outdoor use



0814034  
<https://www.phoenixcontact.com/us/products/0814034>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27281103 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001288 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

0814034  
<https://www.phoenixcontact.com/us/products/0814034>

Environmental product compliance

|                                     |                            |
|-------------------------------------|----------------------------|
| EU REACH SVHC                       |                            |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)