

PVB 5 - Feed-through terminal block



0870052

<https://www.phoenixcontact.com/us/products/0870052>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 30 A, number of connections: 10, number of positions: 1, connection method: Spade connection, 1 level, cross section: 0.5 mm² - 6 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

Commercial data

Item number	0870052
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BE05
Product key	BE511X
GTIN	4017918240769
Weight per piece (including packing)	52.81 g
Weight per piece (excluding packing)	52.81 g
Customs tariff number	85369010
Country of origin	PL

PVB 5 - Feed-through terminal block



0870052

<https://www.phoenixcontact.com/us/products/0870052>

Technical data

Product properties

Product type	Feed-through terminal block
Number of positions	1
Number of connections	10
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
---------------------	------

Connection data

Number of connections per level	10
---------------------------------	----

1 level

Connection method	Spade connection
Spade connection	6.3/2.8 x 0.8 mm
Conductor cross-section rigid	0.5 mm ² ... 6 mm ²
Cross section AWG	20 ... 10 (converted acc. to IEC)
Conductor cross-section flexible	0.5 mm ² ... 6 mm ²
Conductor cross-section, flexible [AWG]	20 ... 10 (converted acc. to IEC)
Nominal current	30 A (current data for slip-on connections in acc. with EN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross-section.)
Maximum load current	30 A (current data for slip-on connections in acc. with EN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross-section.)
Nominal voltage	800 V (voltage data for slip-on connections in acc. with EN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross-section.)

Dimensions

Width	35.6 mm
-------	---------

Material specifications

Color	gray
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA

Mechanical properties

Mechanical data

PVB 5 - Feed-through terminal block



0870052

<https://www.phoenixcontact.com/us/products/0870052>

Open side panel	No
-----------------	----

Mounting

Mounting type	NS 35/7,5
	NS 35/15

PVB 5 - Feed-through terminal block



0870052

<https://www.phoenixcontact.com/us/products/0870052>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com