

# REL-FO/LRC-230AC/2X21/MS - Single relay

1308330

<https://www.phoenixcontact.com/us/products/1308330>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in miniature relay with mechanical switching position indicator, FASTON connection, 2 changeover contacts, status display: LED (yellow), RC element, Input voltage: 230 V AC

## Commercial data

Item number	1308330
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	C460
Product key	DKF937
GTIN	4063151559090
Weight per piece (including packing)	27.89 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85364900
Country of origin	CN

# REL-FO/LRC-230AC/2X21/MS - Single relay



1308330

<https://www.phoenixcontact.com/us/products/1308330>

## Technical data

### Notes

Notes on operation	Do not use to separate SELV/PELV circuits from other circuits, because safe isolation is not guaranteed. (applies to the optocoupler variants)
Notes on operation	The outputs are not suitable for switching different outer conductors.
Notes on operation	The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.

### Product properties

Product type	Single relay
Product family	ESSENTIAL edition
Operating mode	100% operating factor
Mechanical service life	approx. $3 \times 10^7$ cycles
Relay type	Electromechanical relay

### Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation	Basic insulation
Oversupply category	II
Pollution degree	3

### Data management status

Date of last data management	05.09.2025
------------------------------	------------

### Electrical properties

Maximum power dissipation for nominal condition	1 W
Test voltage (Winding/contact)	5 kV <sub>rms</sub> (50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact)	3 kV <sub>rms</sub> (50 Hz, 1 min., changeover contact/changeover contact)
Test voltage (open contact)	1 kV <sub>rms</sub> (50 Hz, 1 min., open contact)

### Air clearances and creepage distances between the power circuits

Rated insulation voltage	250 V AC
Rated surge voltage	2.5 kV

### Input data

Coil side	
Nominal input voltage U <sub>N</sub>	230 V AC
Input voltage range	184 V AC ... 253 V AC
Mains frequency	50/60 Hz
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at U <sub>N</sub>	4.5 mA (50 Hz)
Input power dissipation for U <sub>N</sub>	1 W

# REL-FO/LRC-230AC/2X21/MS - Single relay

1308330

<https://www.phoenixcontact.com/us/products/1308330>



Typical response time	2 ms ... 10 ms
Typical release time range	5 ms ... 20 ms
Protective circuit	RC element
Status display	LED (yellow)
Coil resistance	24100 Ω ±10 %

## Output data

### Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	AgSnO
Maximum switching voltage	250 V AC
	30 V DC
Minimum switching voltage	5 V (10 mA)
Limiting continuous current	8 A
Maximum inrush current	16 A (20 ms, N/O contacts)
Inrush current, minimum	10 mA (5 V)
Interrupting rating (ohmic load) max.	192 W (24 V DC)
	240 W (30 V DC)
	2000 VA (250 V AC)

## Connection data

Connection method	FASTON connection
-------------------	-------------------

## Dimensions

Width	13 mm
Height	31.1 mm
Depth	34 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Relay)	RT II (Relay)
Degree of protection (Installation location)	IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	≤ 2000 m

## Standards and regulations

Standards/regulations	IEC 61810-1
	IEC 60664-1

### Air clearances and creepage distances between the power circuits

Standards/regulations	IEC 60664-1
-----------------------	-------------

# REL-FO/LRC-230AC/2X21/MS - Single relay

1308330

<https://www.phoenixcontact.com/us/products/1308330>




## Mounting

Mounting position	any
-------------------	-----

## Drawings

Diagram



- 1) DC coil: maximum continuous voltage at limiting continuous current
- 2) DC coil: minimum operate voltage for pre-excitation with UN and limiting continuous current
- 3) AC coil: maximum continuous voltage at limiting continuous current
- 4) AC coil: minimum operate voltage for pre-excitation with UN and limiting continuous current


# REL-FO/LRC-230AC/2X21/MS - Single relay

1308330

<https://www.phoenixcontact.com/us/products/1308330>



Diagram



Interrupting rating  
1) AC, ohmic load  
2) DC, ohmic load


# REL-FO/LRC-230AC/2X21/MS - Single relay



1308330

<https://www.phoenixcontact.com/us/products/1308330>

Diagram




Electrical service life

1) 30 V DC, ohmic load


2) 250 V AC, ohmic load

Diagram



Service life reduction factor with various cos phi

Diagram



Permissible humidity for operation and storage.

The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures  $\leq 0^\circ\text{C}$  must be prevented

Area B: Condensation at ambient temperatures  $> 0^\circ\text{C}$  must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature  $\leq 25^\circ\text{C}$ .

# REL-FO/LRC-230AC/2X21/MS - Single relay

1308330

<https://www.phoenixcontact.com/us/products/1308330>



## Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1308330>



**cUL Recognized**

Approval ID: FILE E 172140



**UL Recognized**

Approval ID: FILE E 172140

## Classifications

### ECLASS

ECLASS-13.0	27371601
ECLASS-15.0	27371601

### ETIM

ETIM 9.0	EC001437
----------	----------

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

# REL-FO/LRC-230AC/2X21/MS - Single relay



1308330

<https://www.phoenixcontact.com/us/products/1308330>

## Mandatory accessories

ECOR-1-BSC2/FO/2X21 - Relay base

1308332

<https://www.phoenixcontact.com/us/products/1308332>

ECOR-1 relay base, for FASTON relay, Fork-type cable lug, 2 changeover contacts, Input voltage 230 V AC



---

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)