


# SACC-DSI-FSB-5CON-L180/12SHEMV - Device connector rear mounting



1410649

<https://www.phoenixcontact.com/us/products/1410649>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Socket, M12, B-coding, Wave soldering, this item is expected to be lead-free from Q4 2025 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

## Commercial data

Item number	1410649
Packing unit	20 pc
Minimum order quantity	100 pc
Note	Made to order (non-returnable)
Product key	ABQEHD
GTIN	4046356905077
Weight per piece (including packing)	14.845 g
Weight per piece (excluding packing)	13.489 g
Country of origin	DE

# SACC-DSI-FSB-5CON-L180/12SHEMV - Device connector rear mounting



1410649

<https://www.phoenixcontact.com/us/products/1410649>

## Technical data

### Notes

Order information:	Lock nut is included in the scope of delivery
--------------------	-----------------------------------------------

### Mounting

Mounting type	Rear mounting
Tightening torque	2 Nm ... 3 Nm

### Product properties

Product type	Circular connectors (device side)
Number of positions	5
Shielded	yes
Coding	B
Thread type	M12

### Connection data

#### Conductor connection

Connection method	Wave soldering
Contact connection type	Socket
Tightening torque	2 Nm ... 3 Nm

### Connector

#### Connection 1

Head design	Socket
Head thread type	M12
Coding	B

### Environmental and real-life conditions

#### Ambient conditions

UL Type Rating	Type 4 (indoor use only)
----------------	--------------------------

# SACC-DSI-FSB-5CON-L180/12SHEMV - Device connector rear mounting



1410649

<https://www.phoenixcontact.com/us/products/1410649>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1410649>

 <b>UL Recognized</b> Approval ID: E118976-20100522				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
keine				
	60 V	4 A	22	-

# SACC-DSI-FSB-5CON-L180/12SHEMV - Device connector rear mounting



1410649

<https://www.phoenixcontact.com/us/products/1410649>

## Classifications

### ECLASS

ECLASS-13.0	27440110
ECLASS-15.0	27440110

### ETIM

ETIM 9.0	EC003568
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# SACC-DSI-FSB-5CON-L180/12SHEMV - Device connector rear mounting



1410649

<https://www.phoenixcontact.com/us/products/1410649>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50 An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
----------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	5a081e53-cb72-4a98-bf49-f5fca0ba1004

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)