

FBSK 2-10/ZFKDS 10 - Plug-in bridge



1986644

<https://www.phoenixcontact.com/us/products/1986644>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fixed bridge, fully insulated, pitch: 10 mm, no. of positions: 2

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1986644 |
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales key | AA18 |
| Product key | AARZFE |
| GTIN | 4017918973100 |
| Weight per piece (including packing) | 4.57 g |
| Weight per piece (excluding packing) | 4.556 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

FBSK 2-10/ZFKDS 10 - Plug-in bridge



1986644

<https://www.phoenixcontact.com/us/products/1986644>

Technical data

Product properties

| | |
|-----------------------|----------------------------|
| Product type | Bridge |
| Product family | FBSK |
| Product line | COMBICON Terminals Special |
| Number of positions | 2 |
| Pitch | 10 mm |
| Number of connections | 2 |
| Number of rows | 1 |
| Number of potentials | 2 |

Dimensions

| | |
|-------|-------|
| Pitch | 10 mm |
|-------|-------|

Material specifications

Material data - contact

| | |
|------------------|--|
| Note | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material | Cu alloy |

Material data - housing

| | |
|---|------------|
| Color (Housing) | red (3001) |
| Insulating material | PA |
| Insulating material group | I |
| CTI according to IEC 60112 | 600 |
| Flammability rating according to UL 94 | V0 |
| Glow wire flammability index GWFI according to EN 60695-2-12 | 850 |
| Glow wire ignition temperature GWIT according to EN 60695-2-13 | 775 |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C |

Connector

Connection 1

| | |
|----------------------------|-----|
| Insulating material | PA |
| CTI according to IEC 60112 | 600 |

FBSK 2-10/ZFKDS 10 - Plug-in bridge



1986644

<https://www.phoenixcontact.com/us/products/1986644>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27460406 |
| ECLASS-15.0 | 27460406 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002943 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

FBSK 2-10/ZFKDS 10 - Plug-in bridge



1986644
<https://www.phoenixcontact.com/us/products/1986644>

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
| EF3.0 Climate Change | |
| CO2e kg | 0.06 kg CO2e |

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com