

# PSD-S OE LED RFL YE - Optical element



2700126

<https://www.phoenixcontact.com/us/products/2700126>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

LED random flashing beacon element, 24 V DC, yellow



## Your advantages

- Tool-free element changeover
- High light and color intensity
- Can be freely combined
- Minimum LED service life of 50,000 h
- Low power consumption
- Random flashing light prevents familiarization effect
- Degree of protection IP65

## Commercial data

Item number	2700126
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR07
Product key	DRL112
GTIN	4046356491198
Weight per piece (including packing)	82.6 g
Weight per piece (excluding packing)	78 g
Customs tariff number	85318070
Country of origin	DE

# PSD-S OE LED RFL YE - Optical element

2700126

<https://www.phoenixcontact.com/us/products/2700126>



## Technical data

### Notes

Note on application

Note on application

Only for industrial use

### Product properties

Product type	Signal element
Product family	PSD-S
Area of application	Signal tower

### Electrical properties

#### General

Input voltage	24 V DC
Maximum inrush current	max. 500 mA
Current consumption	typ. 25 mA
Source of light type	LED
Operating time	100 %
Service life electrical	max. 50,000 h
Optical signal type	LED random flashing beacon (RLF)

### Dimensions

Dimensional drawing	
Height	65.5 mm
Diameter	70 mm

### Material specifications

Calotte color	yellow
Material	Polycarbonate PC

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP65 (when installed or with end cover)
Ambient temperature (operation)	-20 °C ... 50 °C

# PSD-S OE LED RFL YE - Optical element



2700126

<https://www.phoenixcontact.com/us/products/2700126>

## EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

## Mounting

Mounting type	Plug-in mounting (Seal pre-installed for each element)
Mounting position	any

# PSD-S OE LED RFL YE - Optical element


2700126

<https://www.phoenixcontact.com/us/products/2700126>



## Drawings

Dimensional drawing



# PSD-S OE LED RFL YE - Optical element

2700126

<https://www.phoenixcontact.com/us/products/2700126>



## Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2700126>



**cULus Listed**

Approval ID: E123528

# PSD-S OE LED RFL YE - Optical element

2700126

<https://www.phoenixcontact.com/us/products/2700126>



## Classifications

### ECLASS

ECLASS-13.0	27371220
-------------	----------

### ETIM

ETIM 9.0	EC000232
----------	----------

### UNSPSC

UNSPSC 21.0	46171600
-------------	----------

# PSD-S OE LED RFL YE - Optical element

2700126

<https://www.phoenixcontact.com/us/products/2700126>



## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.	

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	af37c0e9-6b4a-4ca7-8165-9c2f29ad97ab

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

### Phoenix Contact USA

586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)