

# ME B-22,5 MSTBO YE - Filler plug

2914408

<https://www.phoenixcontact.com/us/products/2914408>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing, Filler plug for unoccupied terminal points (MSTBO), width: 20 mm, height: 19.05 mm, depth: 12.3 mm, color: yellow (similar RAL 1018)

## Your advantages

- Easy, tool-free mounting
- Flammability rating V0 in accordance with UL 94

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2914408       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Product key                          | ACHAAZ        |
| GTIN                                 | 4017918957995 |
| Weight per piece (including packing) | 1.29 g        |
| Weight per piece (excluding packing) | 1.1 g         |
| Country of origin                    | DE            |

# ME B-22,5 MSTBO YE - Filler plug

2914408

<https://www.phoenixcontact.com/us/products/2914408>



## Technical data

### Product properties

|                              |                  |
|------------------------------|------------------|
| Product type                 | Filler plug      |
| Housing type                 | DIN rail housing |
| Housing series               | ME               |
| Product family               | ME 22,5..        |
| Ventilation openings present | no               |

### Dimensions

|        |          |
|--------|----------|
| Width  | 20 mm    |
| Height | 19.05 mm |
| Depth  | 12.3 mm  |

### Material specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Color ()                               | yellow (RAL 1018) |
| Material                               | PA                |
| Flammability rating according to UL 94 | V0                |
| CTI according to IEC 60112             | 600               |
| Surface characteristics                | untreated         |

### Environmental and real-life conditions

#### Vibration test

|                        |                             |
|------------------------|-----------------------------|
| Specification          | IEC 60068-2-6:2007-12       |
| Frequency              | 10 - 150 - 10 Hz            |
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.15 mm (10 Hz ... 58.1 Hz) |
| Acceleration           | 2g (58.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |
| Test directions        | X-, Y- and Z-axis           |

#### Glow-wire test

|                  |                        |
|------------------|------------------------|
| Specification    | IEC 60695-2-11:2014-02 |
| Temperature      | 850 °C                 |
| Time of exposure | 30 s                   |

#### Thermal stability / ball thrust test

|               |                        |
|---------------|------------------------|
| Specification | IEC 60695-10-2:2014-02 |
| Temperature   | 125 °C                 |
| Test duration | 1 h                    |
| Force         | 20 N                   |

#### Mechanical strength / tumbling barrel

|               |                     |
|---------------|---------------------|
| Specification | IEC 60998-1:2002-12 |
|---------------|---------------------|

# ME B-22,5 MSTBO YE - Filler plug



2914408

<https://www.phoenixcontact.com/us/products/2914408>

|                |       |
|----------------|-------|
| Height of fall | 50 cm |
| Frequency      | 10    |

## Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Specification                  | IEC 60068-2-27:2008-02            |
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 15g                               |
| Shock duration                 | 11 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

## Degree of protection (IP code)

|               |                                                   |
|---------------|---------------------------------------------------|
| Specification | IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08 |
|---------------|---------------------------------------------------|

## Ambient conditions

|                                         |                                                    |
|-----------------------------------------|----------------------------------------------------|
| Max. IP code to attain                  | IP20                                               |
| Ambient temperature (operation)         | -40 °C ... 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C ... 55 °C                                   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                   |
| Relative humidity (storage/transport)   | 80 %                                               |

## Mounting

|               |          |
|---------------|----------|
| Mounting type | Latching |
|---------------|----------|

# ME B-22,5 MSTBO YE - Filler plug

2914408

<https://www.phoenixcontact.com/us/products/2914408>



## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2914408>



**UL Recognized**

Approval ID: E240868

# ME B-22,5 MSTBO YE - Filler plug

2914408

<https://www.phoenixcontact.com/us/products/2914408>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27190605 |
| ECLASS-15.0 | 27190605 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002779 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# ME B-22,5 MSTBO YE - Filler plug



2914408

<https://www.phoenixcontact.com/us/products/2914408>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)