

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Freely configurable safety module with 20 safe inputs and 4 safe outputs; 4 alarm, 2 clock, and 2 ground switching outputs; diagnostics possible via bus gateways, up to SIL 3, Cat.4/PL e, SIL 3, EN 50156, plug-in screw connection terminal blocks

Your advantages

- Freely configurable safety module for monitoring emergency stops, safety doors, light grids, etc.
- Up to Cat. 4/PL e in accordance with ISO 13849-1, SIL 3 in accordance with EN IEC 62061, SIL 3 in accordance with IEC 61508
- EN 50156
- Option for connecting fieldbus gateways for diagnostics and signaling functions
- Quick startup thanks to comprehensive simulation and test functions
- Easy graphical configuration instead of complex programming
- Easy graphical configuration with the SAFECONF software
- Including IFS-CONFSTICK memory stick for easily storing and saving the configuration
- Multifunctional use for a wide range of safety functions
- With 20 safe inputs, 4 safe outputs, 4 alarm outputs, and 2 clock outputs on a design width of just 67.5 mm

Commercial data

Item number	2986229
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN02
Product key	DNA311
GTIN	4046356477192
Weight per piece (including packing)	395.1 g
Weight per piece (excluding packing)	154 g
Customs tariff number	85371098
Country of origin	DE

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Technical data

Notes

Note on application

Note on application

Only for industrial use

Product properties

Product type	Safety device
Application	Emergency stop Light grid Safety door Two-hand control
Number of possible extension modules	1 (max. continuous current via PSR-TBUS: 4 A)
Control	1 and 2 channel

Insulation characteristics: Air clearances and creepage distances between the power circuits

Overvoltage category	III
Pollution degree	2

Times

Response time	max. 30 ms (plus response time of PSR-TS-SDOR4)
Recovery time	< 10 s

Electrical properties

Maximum power dissipation for nominal condition	6372 mW (at a = 20, b = 2, c = 4, e = 2, I_{clock} = 100 mA, I_{signal} = 100 mA, $I_{Out/GND}$ = 2 A, $I_{Out/Out}$ = 2 A)
Nominal operating mode	100% operating factor
Interfaces	USB DIN rail TBUS for extension modules and bus couplers

Supply

Rated control circuit supply voltage U_S	18 V DC ... 30 V DC (Incl. all tolerances, incl. residual ripple)
Rated control circuit supply voltage U_S	24 V DC (A1/A2)
Rated control supply current I_S	typ. 110 mA
Limiting continuous current	max. 6 A (For looped-through current paths A1/A1 and A2/A2)
Filter time	typ. 20 ms (Load-dependent, in the event of voltage dips at U_S)
Protective circuit	Yes, within the scope of the operating voltage limits
Status display	3 x LED (green), 1 x LED (red)

Input data

Digital

Description of the input	Digital, type HTL
Number of inputs	10 (Two-channel, up to SIL 3) 20 (1-channel, up to SIL 2)

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Input voltage range "0" signal	0 V DC ... 5 V DC (for safe Off)
Input voltage range "1" signal	11 V DC ... 30 V DC
Cable length	max. 2000 m
Status display	20 x LED green (1 LED per input)
Current consumption	typ. 4 mA

Output data

Digital

Number of outputs	4 (Safe semiconductor outputs, up to Cat. 4 in accordance with EN ISO 13849-1) 2 (Ground switching outputs)
Note on protection circuit	Yes, within the scope of the operating voltage limits
Short-circuit protection	Yes
Output voltage	< 5 V (Low state)
Leakage current	max. 2 mA
Max. capacitive load	max. 1 μ F (Electronic components)
Max. inductive load	See "Protective circuit"
Limiting continuous current	2 A (Per channel, see Derating) 2 A (Total current of all outputs)
Nominal output voltage	24 V DC (Supply via 24 V/0 V)
Nominal output voltage range	18 V DC ... 30 V DC (Incl. all tolerances, incl. residual ripple)
Status display	4 x LED green (1 LED per output)
Test pulses	< 1 ms

Signal

Output description	Digital
Number of outputs	4
Voltage	24 V DC (Supply via 24 V/0 V)
Limiting continuous current	100 mA
Short-circuit protection	Yes

Clock

Output description	Digital
Number of outputs	2
Voltage	24 V DC (Supply via 24 V/0 V)
Limiting continuous current	100 mA
Test pulses	< 1 ms
Short-circuit protection	Yes

Connection data

Connection technology	
pluggable	yes
Conductor connection	
Connection method	Screw connection

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Conductor cross section rigid	0.2 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross-section AWG	24 ... 12
Stripping length	7 mm
Screw thread	M3
Tightening torque	0.5 Nm ... 0.6 Nm
	5 lb _f in. ... 7 lb _f in.

Dimensions

Width	67.5 mm
Height	99 mm
Depth	114.5 mm

Material specifications

Color	yellow
Housing material	Polyamide PA non-reinforced

Characteristics

Safety data	
Stop category	0

Safety data: EN ISO 13849	
Category	2 (1-channel parameterization) 4 (2-channel parameterization)
Performance level (PL)	d (1-channel parameterization) e (2-channel parameterization)

Safety data: EN 50156	
Safety Integrity Level (SIL)	max. 3 (Reference IEC 61508)

Safety data: IEC 61508 - High demand	
Safety Integrity Level (SIL)	2 (1-channel parameterization) 3 (2-channel parameterization)

Safety data: IEC 61508 - Low demand	
Safety Integrity Level (SIL)	2 (1-channel parameterization) 3 (2-channel parameterization)

Safety data: EN IEC 62061	
Safety Integrity Level (SIL)	2 (1-channel parameterization) 3 (2-channel parameterization)

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20
Min. degree of protection of inst. location	IP54

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Ambient temperature (operation)	-20 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Maximum altitude	max. 2000 m (See Appendix "Using PSR-TRISAFE modules at altitudes greater than 2000 m above sea level")
Max. permissible humidity (storage/transport)	75 % (On average, 85 % occasionally)
Max. permissible relative humidity (operation)	75 % (On average, 85 % occasionally)
Shock (operation)	10g ($\Delta t = 11$ ms, three shocks in each space direction)
	10g ($\Delta t = 16$ ms, continuous shock, 1000 shocks in each space direction)
Vibration (operation)	2g
Air pressure (operation)	70 kPa ... 108 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above sea level)

Standards and regulations

Air clearances and creepage distances between the power circuits

Standards/regulations DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	On horizontal DIN rail

PSR-SCP- 24DC/TS/S - Safety module


2986229

<https://www.phoenixcontact.com/us/products/2986229>




Drawings

Application drawing




Diagram



PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2986229>



cULus Listed

Approval ID: E140324

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Classifications

ECLASS

ECLASS-13.0	27371819
-------------	----------

ETIM

ETIM 9.0	EC001449
----------	----------

UNSPSC

UNSPSC 21.0	39122200
-------------	----------

PSR-SCP- 24DC/TS/S - Safety module

2986229

<https://www.phoenixcontact.com/us/products/2986229>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.	

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1) 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol(CAS: 79-94-7)
-------------------------------------	--

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com