

MM-TML (EX9,5)R C1 TR/BK - Label

0803981

<https://www.phoenixcontact.com/us/products/0803981>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Label, Roll, transparent/black, unmarked, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: adhesive, Number of individual labels: 1, roll length: 8 m, text field height: 8000 mm, text field width: 9.5 mm

Your advantages

- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing
- The material is cUL certified
- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- Zack marker strips and flat zack marker strips can be marked subsequently with the TML marking foil
- The self-adhesive material in continuous format is particularly suitable for marking terminals without a marker groove

Commercial data

Item number	0803981
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG23
Product key	BG211E
GTIN	4055626212555
Weight per piece (including packing)	53.79 g
Weight per piece (excluding packing)	50 g
Customs tariff number	96121010
Country of origin	CN

MM-TML (EX9,5)R C1 TR/BK - Label

0803981

<https://www.phoenixcontact.com/us/products/0803981>



Technical data

Product properties

Product type	Klemmenmarker
Marking	
Number of individual labels	1
Number of individual labels per row	1
Identification technology	Thermal transfer

Dimensions

Length of roll	8.00 m
Height	9.5 mm
Depth	0.07 mm

Material specifications

Foil strength	23 µm
Adhesive	Acrylic
Color	transparent
Material	Polyester
Components	free from silicone, halogen, and cadmium

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (assembly)	min. -4 °C
Recommended ambient temperature (storage/transport)	21 °C ... 25 °C
Recommended humidity (storage/transport)	45 % ... 55 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	24 months

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

MM-TML (EX9,5)R C1 TR/BK - Label

0803981

<https://www.phoenixcontact.com/us/products/0803981>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/0803981>



cULus Recognized

Approval ID: MH48542

MM-TML (EX9,5)R C1 TR/BK - Label

0803981

<https://www.phoenixcontact.com/us/products/0803981>



Classifications

ECLASS

ECLASS-13.0	27281101
ECLASS-15.0	27281101

ETIM

ETIM 9.0	EC000761
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

MM-TML (EX9,5)R C1 TR/BK - Label

0803981

<https://www.phoenixcontact.com/us/products/0803981>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com