


# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, PROFIBUS (12 Mbps), 2-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug straight M12, coding: B, on free cable end, cable length: 10 m

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1507269       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF04          |
| Product key                          | AF1CKC        |
| GTIN                                 | 4017918900106 |
| Weight per piece (including packing) | 603.4 g       |
| Weight per piece (excluding packing) | 603.4 g       |
| Customs tariff number                | 85444290      |
| Country of origin                    | PL            |

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

## Technical data

### Notes

|         |                                                                                      |
|---------|--------------------------------------------------------------------------------------|
| General | Further products with variable cable lengths can be found in the accessories section |
|---------|--------------------------------------------------------------------------------------|

### Product properties

|                      |                         |
|----------------------|-------------------------|
| Product type         | Data cable preassembled |
| Application          | Standard                |
| Sensor type          | PROFIBUS                |
| Number of positions  | 2                       |
| No. of cable outlets | 1                       |
| Shielded             | yes                     |
| Coding               | B                       |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Interfaces

|                      |                                |
|----------------------|--------------------------------|
| Bus system           | PROFIBUS                       |
| Signal type/category | PROFIBUS, 12 Mbps (max. 100 m) |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | no |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 48 V AC                    |
|                       | 60 V DC                    |
| Nominal current $I_N$ | 4 A                        |
| Transmission medium   | Copper                     |
| Transmission speed    | 12 Mbps (max. 100 m)       |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Material specifications

|                          |                                             |
|--------------------------|---------------------------------------------|
| Material of grip body    | TPU, hardly inflammable, self-extinguishing |
| Contact material         | CuSn                                        |
| Contact surface material | Ni/Au                                       |
| Contact carrier material | PA 6.6                                      |

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

|                               |                              |
|-------------------------------|------------------------------|
| Material for screw connection | Zinc die-cast, nickel-plated |
|-------------------------------|------------------------------|

## Connection data

### Connection assignment

|                                                           |                         |
|-----------------------------------------------------------|-------------------------|
| Contact   Color (signal designation)   Contact (optional) | 2 (Plug)   GN (A cable) |
|                                                           | 4 (Plug)   RD (B cable) |

## Connector

### Connection 1

|                     |                   |
|---------------------|-------------------|
| Type                | Plug straight M12 |
| Number of positions | 2                 |
| Coding type         | B (inverse)       |


### Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

## Cable/line

|              |      |
|--------------|------|
| Cable length | 10 m |
|--------------|------|

### PROFIBUS [910]

|                                 |                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing             |  |
| Cable weight                    | 90 kg/km                                                                             |
| UL AWM Style                    | 21198 (80°C/300 V)                                                                   |
| Number of positions             | 2                                                                                    |
| Shielded                        | yes                                                                                  |
| Cable type                      | PROFIBUS [910]                                                                       |
| Conductor structure             | 1x2xAWG24/19                                                                         |
| Conductor structure signal line | 19x 0.13 mm                                                                          |
| AWG signal line                 | 24                                                                                   |
| Conductor cross section         | 2x 0.25 mm² (Signal line)                                                            |
| Wire diameter incl. insulation  | 2.55 mm ±0.07 mm                                                                     |
| External cable diameter         | 7.80 mm ±0.2 mm                                                                      |
| Outer sheath, material          | PUR                                                                                  |
| External sheath, color          | red lilac RAL 4001                                                                   |
| Conductor material              | Tin-plated Cu litz wires                                                             |
| Material, filler                | PP                                                                                   |
| Material wire insulation        | Foam-Skin PP                                                                         |

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

|                                               |                                                                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Single wire, color                            | red, green                                                                                                                                                                    |
| Overall twist                                 | 2 cores with 2 fillers to the core                                                                                                                                            |
| Optical shield covering                       | 85 %                                                                                                                                                                          |
| Max. conductor resistance                     | $\leq 78.6 \text{ } \Omega/\text{km}$                                                                                                                                         |
| Insulation resistance                         | $\geq 5 \text{ G}\Omega \cdot \text{km}$                                                                                                                                      |
| Wave impedance                                | $150 \text{ } \Omega \pm 10 \text{ } \%$ (3 MHz ... 20 MHz)                                                                                                                   |
| Cable capacity                                | nom. 30 pF/m                                                                                                                                                                  |
| Nominal voltage, cable                        | 300 V                                                                                                                                                                         |
| Test voltage Core/Core                        | 1500 V (50 Hz, 1 min.)                                                                                                                                                        |
| Test voltage Core/Shield                      | 1500.00 V (50 Hz, 1 min.)                                                                                                                                                     |
| Smallest bending radius, fixed installation   | 40 mm                                                                                                                                                                         |
| Smallest bending radius, movable installation | 65 mm                                                                                                                                                                         |
| Dynamic load capacity (bending)               | Max. bending cycles: 4000000, Bending radius: 65 mm, Traversing path: 4.5 m, Traversing rate: 3 m/s, Acceleration: 3 m/s <sup>2</sup> , Ambient temperature: -20 °C ... 60 °C |
|                                               | Max. bending cycles: 5000000, Bending radius: 80 mm, Traversing path: 4.5 m, Traversing rate: 3 m/s, Acceleration: 3 m/s <sup>2</sup> , Ambient temperature: -20 °C ... 60 °C |
| Shield attenuation                            | $\leq 0.049 \text{ dB/m}$ (at 16 MHz)                                                                                                                                         |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                                                                                                                                      |
|                                               | according to IEC 60754-1                                                                                                                                                      |
| Flame resistance                              | UL 1581, Section 1060 and UL 2556, Section 9.3 (FT1)                                                                                                                          |
|                                               | UL 1581, Section 1100 and UL 2556, Section 9.1 (HFT/FT2)                                                                                                                      |
|                                               | IEC 60332-1-2                                                                                                                                                                 |
| Other resistance                              | Low adhesion                                                                                                                                                                  |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)                                                                                                                                  |
|                                               | -30 °C ... 70 °C (Cable, flexible installation)                                                                                                                               |
|                                               | -20 °C ... 60 °C (for installation)                                                                                                                                           |
|                                               | -20 °C ... 60 °C (cable, drag chain applications)                                                                                                                             |

## Environmental and real-life conditions

### Ambient conditions

|                                                                   |                                  |
|-------------------------------------------------------------------|----------------------------------|
| Degree of protection                                              | IP65                             |
|                                                                   | IP67                             |
| Ambient temperature (operation) (male connector/female connector) | -25 °C ... 90 °C (Plug / socket) |

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

## Drawings

Dimensional drawing



Plug, M12 x 1, straight, shielded

Schematic diagram



Pin assignment M12 male connector, 5-pos., B-coded, male side

Circuit diagram



Contact assignment of the M12 plug

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1507269>



### EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387



### UL Listed

Approval ID: FILE E 221474

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 300 V                 | 4 A                   | -                 | -                           |



### cUL Listed

Approval ID: FILE E 221474

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 300 V                 | 4 A                   | -                 | -                           |

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060307 |
| ECLASS-15.0 | 27060307 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-2P-M12MSB/10,0-910 - Bus system cable



1507269

<https://www.phoenixcontact.com/us/products/1507269>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |
| EF3.0 Climate Change                    |                                          |
| CO2e kg                                 | 5.981 kg CO2e                            |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)