

ME-IO 18,8/28 TBUS DEV-PCB - PCB

2202548

<https://www.phoenixcontact.com/us/products/2202548>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Perfboard for the ME-IO 18,8 DEV-KIT; for HSCH 2,5 header; ideal for manual soldering



Your advantages

- Hole matrix PCB for self-assembly
- Hole matrix dimension: 2.54 mm
- Easy installation

Commercial data

Item number	2202548
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	NULL
Product key	ACHEBE
GTIN	4055626142609
Weight per piece (including packing)	16.5 g
Weight per piece (excluding packing)	16.4 g
Customs tariff number	85340011
Country of origin	DK

ME-IO 18,8/28 TBUS DEV-PCB - PCB



2202548

<https://www.phoenixcontact.com/us/products/2202548>

Technical data

Product properties

Product type	PCB
Housing type	DIN rail housing
Housing series	ME-IO
Product family	ME-IO 18,8
Max. number of positions	28 (pitch: 5 mm)

Dimensions

Width	1.6 mm
Height	98.2 mm
Depth	66.8 mm

PCB design

PCB thickness	1.4 mm ... 1.8 mm
---------------	-------------------

Material specifications

Color	green (RAL 6021)
Material	FR 4-21

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	110 °C (depending on power dissipation)
---------------------------------	---

PCB data

Thickness of the PCB	1.4 mm ... 1.8 mm
----------------------	-------------------

ME-IO 18,8/28 TBUS DEV-PCB - PCB



2202548

<https://www.phoenixcontact.com/us/products/2202548>

Classifications

ECLASS

ECLASS-13.0	27260692
ECLASS-15.0	27260692

ETIM

ETIM 9.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%