

CF 1000-10 - Automatic stripping and crimping device



1212456

<https://www.phoenixcontact.com/us/products/1212456>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Automatic stripping and crimping device, input voltage 100 V ... 240 V, electro-pneumatic, for loose ferrules with insulating collar, 4 mm², 6 mm², and 10 mm², without conversion kit

Product description

Scope of supply without conversion kit

Your advantages

- The conductor is stripped in a single step and crimped with a ferrule to a high standard of quality
- Quantity counter
- The pull-out forces meet the requirements of IEC/EN 60999 and IEC/EN 60947
- The automatic stripping and crimping device can be used to process loose ferrules with insulating collars according to DIN 46228-4
- Quick change of cross section without the need for additional adjustments
- Up to 1200 conductors can be processed an hour
- Suitable for bulk processing
- Rugged design

Commercial data

Item number	1212456
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH32
Product key	BH3232
GTIN	4046356526883
Weight per piece (including packing)	29,500 g
Weight per piece (excluding packing)	28,500 g
Customs tariff number	84798100
Country of origin	DE

CF 1000-10 - Automatic stripping and crimping device

1212456

<https://www.phoenixcontact.com/us/products/1212456>



Technical data

Product properties

Product type	Automatic crimping device
Compression	trapezoidal
Insertion length minimum	40 mm
Air consumption per compression	1.2 l
Pressure range	5.00 bar ... 6.00 bar
Product property	Tool for conversion inside the housing Additional mode for stripping the conductor only Processing of loose ferrules with insulating collar Ferrules with enlarged insulating collar (AI-GB ...) can be processed with additional conversion kits Integrated forward and reverse counter that can be reset

Electrical properties

Frequency range	50 Hz ... 60 Hz
Power consumption	70 W
Supply	
Supply voltage range	100 V AC ... 240 V AC (50 Hz ... 60 Hz)

Connection data

Conductor connection	
Cross section range, metric	4 mm ² ... 10 mm ²

Dimensions

Width	250 mm
Height	412 mm
Length	550 mm

Connector

Type of plug	Pin connector pattern type B, EF
--------------	----------------------------------

Standards and regulations

Tests	DIN 46228-4: 1990-09
-------	----------------------

CF 1000-10 - Automatic stripping and crimping device

1212456

<https://www.phoenixcontact.com/us/products/1212456>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1212456>



EAC

Approval ID: RU C-DE.AI30.B.01549

CF 1000-10 - Automatic stripping and crimping device

1212456

<https://www.phoenixcontact.com/us/products/1212456>



Classifications

ECLASS

ECLASS-13.0	17130101
ECLASS-15.0	17130101

ETIM

ETIM 9.0	EC002778
----------	----------

UNSPSC

UNSPSC 21.0	27111500
-------------	----------

CF 1000-10 - Automatic stripping and crimping device

1212456

<https://www.phoenixcontact.com/us/products/1212456>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)-I, 6(b)-II, 6(c), 7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-25
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.	

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	ffdcddd27-48aa-4f49-983a-0ea8b1a9f75e

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com