

# TSPC 5/ 2-STF-7,62 - PCB connector



1728206

<https://www.phoenixcontact.com/us/products/1728206>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB TWIN plug, nominal cross section: 6 mm<sup>2</sup>, color: green, nominal current: 32 A, rated voltage (III/2): 1000 V, contact surface: Sn, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 4, product range: TSPC 5/...-STF, pitch: 7.62 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON PC 5, locking: Screw locking mechanism, mounting method: Screw flange, type of packaging: packed in cardboard

## Your advantages

- Time saving push-in connection, tools not required
- Defined contact force ensures that contact remains stable over the long term
- Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- Integrated double steel spring provides additional safety in the event of temperature and power fluctuations
- Potentials can be easily looped through – ideal for BUS applications
- Screwable flange for superior mechanical stability
- 600 V UL approval in the smallest of dimensions

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1728206       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | AA04          |
| Product key                          | AADFBE        |
| GTIN                                 | 4046356144575 |
| Weight per piece (including packing) | 20.992 g      |
| Weight per piece (excluding packing) | 20 g          |
| Customs tariff number                | 85366990      |
| Country of origin                    | IN            |

# TSPC 5/ 2-STF-7,62 - PCB connector

1728206

<https://www.phoenixcontact.com/us/products/1728206>



## Technical data

### Product properties

|                       |                       |
|-----------------------|-----------------------|
| Product type          | PCB TWIN plug         |
| Product family        | TSPC 5/...-STF        |
| Product line          | COMBICON Connectors L |
| Type                  | Standard              |
| Number of positions   | 2                     |
| Pitch                 | 7.62 mm               |
| Number of connections | 4                     |
| Number of rows        | 1                     |
| Number of potentials  | 2                     |
| Mounting type         | Screw flange          |

### Electrical properties

#### Properties

|                             |        |
|-----------------------------|--------|
| Nominal current $I_N$       | 32 A   |
| Nominal voltage $U_N$       | 1000 V |
| Contact resistance          | 0.6 mΩ |
| Rated voltage (III/3)       | 1000 V |
| Rated surge voltage (III/3) | 8 kV   |
| Rated voltage (III/2)       | 1000 V |
| Rated surge voltage (III/2) | 8 kV   |
| Rated voltage (II/2)        | 1000 V |
| Rated surge voltage (II/2)  | 6 kV   |

### Connection data

#### Connection technology

|                         |                   |
|-------------------------|-------------------|
| Type                    | Standard          |
| Connector system        | COMBICON PC 5     |
| Nominal cross section   | 6 mm <sup>2</sup> |
| Contact connection type | Socket            |

#### Interlock

|                   |                         |
|-------------------|-------------------------|
| Locking type      | Screw locking mechanism |
| Mounting type     | Screw flange            |
| Tightening torque | 0.3 Nm ... 0.7 Nm       |

#### Conductor connection

|                                    |                                            |
|------------------------------------|--------------------------------------------|
| Connection method                  | Push-in spring connection                  |
| Conductor/PCB connection direction | 0 °                                        |
| Conductor cross-section rigid      | 0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| Conductor cross-section flexible   | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |

# TSPC 5/ 2-STF-7,62 - PCB connector



1728206

<https://www.phoenixcontact.com/us/products/1728206>

|                                                                                           |                          |
|-------------------------------------------------------------------------------------------|--------------------------|
| Conductor cross-section AWG                                                               | 24 ... 8                 |
| Conductor cross-section flexible, with ferrule without plastic sleeve                     | 0.25 mm² ... 6 mm²       |
| Conductor cross-section, flexible, with ferrule, with plastic sleeve                      | 0.25 mm² ... 4 mm²       |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.25 mm² ... 1.5 mm²     |
| Cylindrical gauge a x b / diameter                                                        | 4.3 mm x 4.0 mm / 4.0 mm |
| Stripping length                                                                          | 15 mm                    |

## Specifications for ferrules without insulating collar

|                                                              |                                                  |
|--------------------------------------------------------------|--------------------------------------------------|
| recommended crimping tool                                    | 1212034 CRIMPFOX 6                               |
|                                                              | 1213144 CRIMPFOX CENTRUS 6S                      |
|                                                              | 1213146 CRIMPFOX CENTRUS 6H                      |
| ferrules without insulating collar, according to DIN 46228-1 | Cross section: 0.5 mm²; Length: 10 mm ... 15 mm  |
|                                                              | Cross section: 0.75 mm²; Length: 10 mm ... 15 mm |
|                                                              | Cross section: 1 mm²; Length: 10 mm ... 15 mm    |
|                                                              | Cross section: 1.5 mm²; Length: 12 mm ... 15 mm  |
|                                                              | Cross section: 2.5 mm²; Length: 12 mm ... 15 mm  |
|                                                              | Cross section: 4 mm²; Length: 12 mm ... 15 mm    |
|                                                              | Cross section: 6 mm²; Length: 12 mm ... 15 mm    |

## Specifications for ferrules with insulating collar

|                                                           |                                                  |
|-----------------------------------------------------------|--------------------------------------------------|
| recommended crimping tool                                 | 1212034 CRIMPFOX 6                               |
|                                                           | 1213144 CRIMPFOX CENTRUS 6S                      |
|                                                           | 1213146 CRIMPFOX CENTRUS 6H                      |
| ferrules with insulating collar, according to DIN 46228-4 | Cross section: 0.5 mm²; Length: 10 mm ... 15 mm  |
|                                                           | Cross section: 0.75 mm²; Length: 12 mm ... 15 mm |
|                                                           | Cross section: 1 mm²; Length: 12 mm ... 15 mm    |
|                                                           | Cross section: 1.5 mm²; Length: 12 mm ... 15 mm  |
|                                                           | Cross section: 2.5 mm²; Length: 12 mm ... 15 mm  |
|                                                           | Cross section: 4 mm²; Length: 12 mm ... 15 mm    |

## Material specifications

### Material data - contact

|                                          |                                                                                  |
|------------------------------------------|----------------------------------------------------------------------------------|
| Note                                     | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material                         | Cu alloy                                                                         |
| Surface characteristics                  | hot-dip tin-plated                                                               |
| Metal surface terminal point (top layer) | Tin (4 - 8 µm Sn)                                                                |
| Metal surface contact area (top layer)   | Tin (4 - 8 µm Sn)                                                                |

### Material data - housing

|                            |              |
|----------------------------|--------------|
| Color (Housing)            | green (6021) |
| Insulating material        | PA           |
| Insulating material group  | I            |
| CTI according to IEC 60112 | 600          |

# TSPC 5/ 2-STF-7,62 - PCB connector



1728206

<https://www.phoenixcontact.com/us/products/1728206>

|                                                                   |        |
|-------------------------------------------------------------------|--------|
| Flammability rating according to UL 94                            | V0     |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850    |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775    |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C |

## Dimensions

|                     |                                                                                    |
|---------------------|------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Pitch               | 7.62 mm                                                                            |
| Width [w]           | 30.46 mm                                                                           |
| Height [h]          | 35.05 mm                                                                           |
| Length [l]          | 41.45 mm                                                                           |

## Mounting

### Flange

|                   |                   |
|-------------------|-------------------|
| Tightening torque | 0.3 Nm ... 0.7 Nm |
|-------------------|-------------------|

## Notes

|                    |                                                                                                                                                                                          |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes on operation | In accordance with IEC 61984, COMBICON connectors have no switching power (COC). During designated use, they must not be plugged in or disconnected when carrying voltage or under load. |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Mechanical tests

### Conductor connection

|               |                     |
|---------------|---------------------|
| Specification | IEC 60999-1:1999-11 |
| Result        | Test passed         |

### Test for conductor damage and slackening

|               |                     |
|---------------|---------------------|
| Specification | IEC 60999-1:1999-11 |
| Result        | Test passed         |

### Repeated connection and disconnection

|               |                     |
|---------------|---------------------|
| Specification | IEC 60999-1:1999-11 |
| Result        | Test passed         |

### Pull-out test

|                                                                             |                                         |
|-----------------------------------------------------------------------------|-----------------------------------------|
| Specification                                                               | IEC 60999-1:1999-11                     |
| Conductor cross-section/conductor type/tractive force setpoint/actual value | 0.2 mm <sup>2</sup> / solid / > 10 N    |
|                                                                             | 0.2 mm <sup>2</sup> / flexible / > 10 N |
|                                                                             | 10 mm <sup>2</sup> / solid / > 90 N     |

# TSPC 5/ 2-STF-7,62 - PCB connector



1728206

<https://www.phoenixcontact.com/us/products/1728206>

|  |                                       |
|--|---------------------------------------|
|  | 6 mm <sup>2</sup> / flexible / > 80 N |
|--|---------------------------------------|

## Insertion and withdrawal forces

|                                     |                        |
|-------------------------------------|------------------------|
| Specification                       | IEC 60512-13-2:2006-02 |
| Result                              | Test passed            |
| No. of cycles                       | 50                     |
| Insertion strength per pos. approx. | 6 N                    |
| Withdraw strength per pos. approx.  | 5 N                    |

## Resistance of inscriptions

|               |                        |
|---------------|------------------------|
| Specification | IEC 60068-2-70:1995-12 |
| Result        | Test passed            |

## Polarization and coding

|               |                        |
|---------------|------------------------|
| Specification | IEC 60512-13-5:2006-02 |
| Result        | Test passed            |

## Visual inspection

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60512-1-1:2002-02 |
| Result        | Test passed           |

## Dimension check

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60512-1-2:2002-02 |
| Result        | Test passed           |

## Environmental and real-life conditions

### Vibration test

|                        |                             |
|------------------------|-----------------------------|
| Specification          | IEC 60068-2-6:2007-12       |
| Frequency              | 10 - 150 - 10 Hz            |
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.35 mm (10 Hz ... 60.1 Hz) |
| Acceleration           | 5g (60.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |
| Test directions        | X-, Y- and Z-axis           |

### Durability test

|                                              |                       |
|----------------------------------------------|-----------------------|
| Specification                                | IEC 60512-9-1:2010-03 |
| Impulse withstand voltage at sea level       | 7.3 kV                |
| Contact resistance R <sub>1</sub>            | 0.6 mΩ                |
| Contact resistance R <sub>2</sub>            | 0.7 mΩ                |
| Insertion/withdrawal cycles                  | 50                    |
| Insulation resistance, neighboring positions | > 5 MΩ                |

### Climatic test

|                  |                                                                           |
|------------------|---------------------------------------------------------------------------|
| Specification    | ISO 6988:1985-02                                                          |
| Corrosive stress | 0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> /40 °C/1 cycle |
| Thermal stress   | 100 °C/168 h                                                              |

# TSPC 5/ 2-STF-7,62 - PCB connector

1728206

<https://www.phoenixcontact.com/us/products/1728206>



|                                   |         |
|-----------------------------------|---------|
| Power-frequency withstand voltage | 3.31 kV |
|-----------------------------------|---------|

## Ambient conditions

|                                         |                                                     |
|-----------------------------------------|-----------------------------------------------------|
| Ambient temperature (operation)         | -40 °C ... 100 °C (dependent on the derating curve) |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C                                    |
| Relative humidity (storage/transport)   | 30 % ... 70 %                                       |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                    |

## Electrical tests

### Thermal test | Test group C

|                            |                       |
|----------------------------|-----------------------|
| Specification              | IEC 60512-5-1:2002-02 |
| Tested number of positions | 12                    |

### Insulation resistance

|                                              |                       |
|----------------------------------------------|-----------------------|
| Specification                                | IEC 60512-3-1:2002-02 |
| Insulation resistance, neighboring positions | > 5 MΩ                |

### Air clearances and creepage distances |

|                                                        |                     |
|--------------------------------------------------------|---------------------|
| Specification                                          | IEC 60664-1:2007-04 |
| Insulating material group                              | I                   |
| Comparative tracking index (IEC 60112)                 | CTI 600             |
| Rated insulation voltage (III/3)                       | 1000 V              |
| Rated surge voltage (III/3)                            | 8 kV                |
| minimum clearance value - non-homogenous field (III/3) | 8 mm                |
| minimum creepage distance (III/3)                      | 12.5 mm             |
| Rated insulation voltage (III/2)                       | 1000 V              |
| Rated surge voltage (III/2)                            | 8 kV                |
| minimum clearance value - non-homogenous field (III/2) | 8 mm                |
| minimum creepage distance (III/2)                      | 8 mm                |
| Rated insulation voltage (II/2)                        | 1000 V              |
| Rated surge voltage (II/2)                             | 6 kV                |
| minimum clearance value - non-homogenous field (II/2)  | 5.5 mm              |
| minimum creepage distance (II/2)                       | 5.5 mm              |

## Packaging specifications

|                   |                     |
|-------------------|---------------------|
| Type of packaging | packed in cardboard |
|-------------------|---------------------|

# TSPC 5/ 2-STF-7,62 - PCB connector




1728206

<https://www.phoenixcontact.com/us/products/1728206>

## Drawings

Diagram



Type: TSPC 5/...-STF-7,62 with PC 5/...-GF-7,62

# TSPC 5/ 2-STF-7,62 - PCB connector

1728206

<https://www.phoenixcontact.com/us/products/1728206>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1728206>

|                                                                                                                                                       |                       |                       |                   |                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| <div> <b>cULus Recognized</b><br/>Approval ID: E60425-19920722</div> |                       |                       |                   |                             |
|                                                                                                                                                       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B                                                                                                                                                     |                       |                       |                   |                             |
|                                                                                                                                                       | 600 V                 | 31 A                  | 24 - 8            | -                           |
| C                                                                                                                                                     |                       |                       |                   |                             |
|                                                                                                                                                       | 600 V                 | 31 A                  | 24 - 8            | -                           |

# TSPC 5/ 2-STF-7,62 - PCB connector



1728206

<https://www.phoenixcontact.com/us/products/1728206>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27460202 |
| ECLASS-15.0 | 27460202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002638 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# TSPC 5/ 2-STF-7,62 - PCB connector



1728206

<https://www.phoenixcontact.com/us/products/1728206>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)